

AD A 0 46368

2

# NAVAL POSTGRADUATE SCHOOL

Monterey, California



D D C  
RECEIVED  
NOV 15 1977  
2

## THESIS

GENERALIZED HELICOPTER ROTOR  
PERFORMANCE PREDICTIONS

by

James William Loisel

September 1977

Thesis Advisor:

L.V. Schmidt

Approved for public release; distribution unlimited.

AD No. \_\_\_\_\_  
DDC FILE COPY

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Generalized Helicopter Rotor Performance Predictions		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis, September 1977
7. AUTHOR(s) James William Loisel		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 12 138		12. REPORT DATE September 1977
		13. NUMBER OF PAGES 138
		15. SECURITY CLASS. (of this report) Unclassified
		16a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Helicopter Helicopter Performance Helicopter Computer Program		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The Generalized Rotor Performance (GRP) program is a computer program designed for calculating forward flight performance of a helicopter rotor system at a specific flight condition. It can be used to evaluate either an articulated or a hingeless single rotor system in forward flight or in a wind-tunnel test. The program was		

DD FORM 1473  
(Page 1)EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

251 450


SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

4B

## (20. ABSTRACT Continued)

originally designed by the Sikorsky Aircraft Company and purchased by the United States Navy.

The goals of this thesis were (1) to reinvestigate the theory and logic used in the program, (2) to add selected desirable features to the program, (3) to produce a much needed Users' Manual, and (4) to run an analysis comparing the program's calculated results against manufacturer's data. These goals were accomplished and the results of the analysis indicated that the program produces highly accurate results within the normal cruise range of a modern helicopter. ←

ACCESSION FOR	Section	<input checked="" type="checkbox"/>
NTIS	Section	<input type="checkbox"/>
DOC	Section	<input type="checkbox"/>
INFORMATION		
JCS		
BY	DISTRIBUTION/AVAILABILITY CODES	
Dr.		
		

Approved for public release; distribution unlimited.

Generalized Helicopter Rotor  
Performance Predictions

by

James William Loisel  
Lieutenant, United States Navy  
B.S., United States Naval Academy, 1971

Submitted in partial fulfillment of the  
requirements for the degree of

MASTER OF SCIENCE IN AERONAUTICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL  
September, 1977

Author

James William Loisel

Approved by:

Louis V. Schmidt

THESIS ADVISOR

Richard W. Bell

Chairman, Department of Aeronautics

A. D. Johnson

Dean of Science and Engineering

## ABSTRACT

The Generalized Rotor Performance (GRP) program is a computer program designed for calculating forward flight performance of a helicopter rotor system at a specific flight condition. It can be used to evaluate either an articulated or a hingeless single rotor system in forward flight or in a wind-tunnel test. The program was originally designed by the Sikorsky Aircraft Company and purchased by the United States Navy.

The goals of this thesis were (1) to reinvestigate the theory and logic used in the program, (2) to add selected desirable features to the program, (3) to produce a much needed Users' Manual, and (4) to run an analysis comparing the program's calculated results against manufacturer's data. These goals were accomplished and the results of the analysis indicated that the program produces highly accurate results within the normal cruise range of a modern helicopter.

## TABLE OF CONTENTS

I.	INTRODUCTION -----	9
II.	METHOD OF ANALYSIS -----	15
	A. GENERAL COMMENTS -----	15
	B. ANGLE OF ATTACK CALCULATIONS -----	18
	C. METHOD OF SOLUTION FOR THE FLAPPING EQUATION -	24
	D. FORCES, MOMENTS AND RADIAL INTEGRATION -----	27
	E. AZIMUTHAL INTEGRATION METHOD -----	27
	F. MAJOR ITERATION -----	28
	G. FLOW CHART -----	31
III.	GRP USERS' MANUAL -----	33
	A. MAIN ITERATION OPTIONS -----	33
	B. GRP DATA DECK ORDER -----	36
	C. AIRFOIL DATA DECK ORDER -----	36
	D. SPAR DATA DECK REQUIREMENTS -----	41
	E. SAMPLE DATA INPUT FORM -----	42
	F. CASE INPUT LISTINGS -----	48
	G. CASE INPUT DEFAULT VALUES -----	51
	H. CASE INPUT DATA -----	52
	I. CASE INPUT FORMAT -----	74
	J. CASE OPTIONAL OUTPUT INDICATORS -----	75
	K. IBM 360 EXECUTION CONTROL CARDS -----	77
	L. SAMPLE PROGRAM OUTPUT -----	79
IV.	GRP SAMPLE ANALYSIS -----	108
V.	CONCLUSIONS -----	113
	GRP COMPUTER PROGRAM -----	114
	LIST OF REFERENCES -----	137
	INITIAL DISTRIBUTION LIST -----	138

# LIST OF TABLES

TABLE I	ROTOR HORSEPOWER WEIGHT = 16359 LBS -----	109
TABLE II	ROTOR HORSEPOWER WEIGHT = 17321 LBS -----	110
TABLE III	ROTOR HORSEPOWER WEIGHT = 19246 LBS -----	110
TABLE IV	ROTOR HORSEPOWER WEIGHT = 19658 LBS -----	111
TABLE V	ROTOR HORSEPOWER WEIGHT = 20829 LBS -----	111
TABLE VI	ROTOR HORSEPOWER RATIO COMPARISION -----	112

# LIST OF FIGURES

FIGURE 1	BLADE ELEMENT DIAGRAM -----	16
FIGURE 2	ROTOR BLADE MOMENT DIAGRAM -----	16
FIGURE 3	SPANWISE FLOW DIAGRAM -----	19
FIGURE 4	UT DIAGRAM -----	21
FIGURE 5	UP AND UR DIAGRAM -----	22
FIGURE 6	RESULTANT GRP FORCE CALCULATION DIAGRAM -----	30
FIGURE 7	REQUIRED GRP FORCE DIAGRAM -----	30
FIGURE 8	GRP FLOW CHART -----	32
FIGURE 9	RESOLUTION OF GRAVITATIONAL FORCE -----	60
FIGURE 10	SHAFT AND CONTROL AXIS DIAGRAM -----	60
FIGURE 11	TIP SWEEP CALCULATION DIAGRAM -----	73



# TABLE OF SYMBOLS

CD	Sectional Coefficient of Drag
Cl	Sectional Coefficient of Lift
CM	Sectional Coefficient of Moment
U	Resultant of $U_P$ , $U_T$ and $U_R$ velocities
$U_P$	Velocity perpendicular to the plane of rotation
$U_R$	Velocity in radial direction in plane of rotation
$U_T$	Velocity tangential to the plane of rotation
$U_{TR}$	Resultant of $U_T$ and $U_R$ velocities
$c_{.75}$	Chord at 75 percent blade radius
V	Forward flight velocity, feet per seconds
$\alpha$	Lift Curve Slope, $\text{rad}^{-1}$
$\alpha_s$	Shaft axis angle, degrees
$\beta$	Blade flapping angle
$\lambda$	IAMPDA, Inflow Ratio in shaft axis system
$\Omega$	Blade rotational velocity, radians per second
$\Theta_{.75}$	Pitch Angle at the 75 percent radius point at the PSI equal zero azimuthal position
$\Psi$	PSI, blade azimuthal position
$\mu$	Advance Ratio in the shaft axis reference system $\mu = V \cos \alpha_s / \Omega R$
$\rho$	Air Density

## I. INTRODUCTION

The Generalized Rotor Performance (GRP) program is a computer program designed for calculating forward flight performance of a helicopter rotor system at a specific flight condition. It can be used to evaluate either an articulated or a hingeless single rotor system in forward flight or in a wind-tunnel test. The GRP series of programs were originally designed by the Sikorsky Aircraft Corporation with the cooperation of the United Aircraft Research Laboratories. Work began on this series of programs in 1955 and has continued to date. The United States Navy purchased this program in 1964 and has used it in the Naval Air Systems Command as a helicopter performance computer program.

The goals of this thesis were (1) to reinvestigate the theory and logic used in the program, (2) to ensure that the Navy's version of this program performed the calculations according to the design theory, (3) to produce a much needed Users' Manual, (4) to add certain desirable features to and correct errors found in the program, (5) to run an analysis comparing the program's calculated results against manufacturer's data and (6) to document areas that may need further attention. The work was done with the help and cooperation of both faculty at the Naval Postgraduate School and personnel in the Naval Air System Command.

The output available from the program includes rotor shaft horsepower, rotor profile horsepower, main rotor torque, lift, drag, thrust, H force, rolling and pitching moments and other forces and moments calculated in the shaft, control and relative wind reference axis systems. Also available are the azimuthal histories of the blade's flapping angles, rates and accelerations, plus azimuthal and

radial histories of angles of attack, CL, CD, Mach number, sweep angles and air load distribution. In addition, the program will calculate a Fourier coefficient series for flapping angle, radial station air loads and azimuthal Z force distribution.

The program can be divided figuratively into three main routines. The first routine determines a steady state flapping solution. The second routine determines the forces and moments generated by this flapping solution. The third routine compares the calculated results of lift, drag and other options to those desired by the user. If the calculated values are not within a predetermined tolerance, the program will, by use of a first order Taylor series, generate new values to reenter into the blade flapping routine.

The program uses a combined blade element/momentum strip theory. The blade's radius is divided into a maximum of 15 segments. The blade is advanced around the azimuth in a prescribed number of degrees. At each particular azimuthal position, velocities are computed in the perpendicular (UP), tangential (UT) and radial (UR) directions. From these velocities and a known pitch angle distribution, the local angles of attack are calculated. From these angles of attack, the forces at each radial blade segment are determined. Once the forces are known, the local moments can be found. From the summation of these moments at a particular azimuthal position, the blade flapping acceleration is calculated. This acceleration, combined with the calculated flapping angle and rate, is used to advance the blade to the next azimuthal position. A steady state flapping condition is assumed to exist when the blade flapping angle and rate at the PSI equal zero and 360 degree azimuthal position are within a prescribed tolerance of each other.

This method of calculation accounts for retreating blade stall, the reverse flow region and compressibility effects. The program can accommodate a full range of geometric and design variables including flapping hinge offset, elastic flapping hinge restraint, first and second harmonic cyclic inputs and spanwise variations in blade twist, local mass densities, chord and tip sweep. The program uses no small angle assumptions and has no restrictions on tip speed, forward velocity or advance ratio. The rotor system can be oriented in any direction in space and can be given any rotor shaft or aircraft roll, pitch or yaw angular velocities. The program will perform calculations in straight and level flight or a uniform induced velocity may be added to simulate climbs and descents. The GRP will accept up to five different airfoil data decks plus one blade spar characteristics data deck. Lift and drag information is entered into the program in the form of CL and CD versus Angle of Attack Tables for up to 15 different Mach numbers. The user has a choice of six methods of solution depending upon the desired restrictions. The user has available nine printout options, two of which are program debugging options. There are also error printout messages that will assist the user having difficulty with the program.

In the method described above, the flapping motion determined is about a flapping hinge offset, and with the elimination of all assumptions that the flapping angles are small, the rotor control axis (axis of no feathering) and the tip path plane axis (axis of no first harmonic flapping) are no longer considered convenient for reference in the analysis of rotor blade motion. Therefore, the axis selected for use in the analysis is the rotor shaft axis system. All forces, moments and angles are referred to the shaft axis system with the exception of some of the final output forces which are referred to the relative wind and control axis systems.

With the use of the computer, the GRP program eliminated many of the simplifying assumptions of the earlier classical theory originated by Wheatley and Bailey in Ref. 1 and 2. The assumptions of the classical theory did not impose serious limitations in low speed flight, but as helicopter speeds increase, the inaccuracies inherent in the theory seriously limit the usefulness of this method. The assumptions of the Wheatley-Bailey theory which are not present in the GRP program include the following.

1. The flapping and inflow angles are assumed small.
2. The lift and drag coefficients are approximated by a linear and a quadratic variation, respectively, with angle of attack.
3. The effects of Mach number on CL and CD are not considered.
4. Sectional characteristics in the reverse flow region are the same as those in the conventional flow.
5. The sectional characteristics of blade twist, tip sweep, flapping hinge offset and root cut out are ignored.

While the GRP program represents a refined approach to the classical theory, there are still some basic assumptions which make the GRP subject to error. These are:

1. Steady state two-dimensional airfoil data are used.
2. Quasi-static blade analysis is used.
3. The rotational speed about the shaft axis is constant. There is no lead or lag motion in the program.
4. The rotor blade is assumed rigid in bending and torsion.

5. The rotor inflow is assumed uniform unless varied by the user.
6. Spanwise flow is incorporated into the calculation of blade angle of attack; however, it is assumed that the flow at one segment does not affect the flow at any other segment.

It is felt that the errors induced by the above assumptions are relatively small in the normal cruise speed region of a modern helicopter. This is the region from just below the minimum power airspeed to the maximum allowable cruise speed. The program can not calculate rotor hover power. This is because one of the factors in the denominator in the main routine which estimates new flapping routine reentry parameters is the advance ratio. Since the advance ratio is zero in a hover, the computer would attempt to divide here by the number zero. Highly accurate results are not available in the airspeed region from hover to just below the minimum power airspeed while using the normal uniform inflow assumption. This is a region of highly non-uniform flow. Variable inflow may be input by the user. However, at this time, no information is available on how successful this technique is in accurately estimating the required rotor system horsepower. While the program's required technique for inducing harmonic variable flow is cumbersome, Bramwell in Chapter Four of Ref. 6 describes several methods which could be incorporated into the program.

The quasi-static blade analysis assumption is valid except in the very high speed region where a large percentage of the retreating blade is in a stalled condition. This is an area of aerodynamic hysteresis that is influenced by unsteady aerodynamics. While encountering lift hysteresis, the amount of lift change above the steady state CL is about the same as below. However, the lift distribution on the rotor disc will change. Stall is delayed and occurs at a slightly later azimuthal station

then predicted by quasi-static analysis. While difficult, complicated and computer-time-consuming procedures can be taken to reduce these assumptions there is no guarantee that the accuracy of the solution will improve. It is felt that the present program produces highly accurate results in the flight range of interest in a modern helicopter.

## II. METHOD OF ANALYSIS

### A. GENERAL COMMENTS

The GRP uses a combined blade element/momentum strip theory in its calculations. The blade radius is divided into a maximum of 15 segments or strips. Figure 1 illustrates a typical blade element. In order to obtain a steady state flapping solution the program must calculate the time history of the flapping motion. This necessitates a complete knowledge of the flapping angles, rates and accelerations. The time history of this motion must be found by solving the highly non-linear equation for the summation of moments about the flapping hinge. Figure 2 illustrates the forces which produce moments on the rotor system. The blade has aerodynamic forces acting upwards, blade weight acting downwards, centrifugal force acting outwards, an optional elastic hinge restraint acting to return the blade to a zero flapping angle and an inertia force resisting any change in blade flapping. The moment summation equation about the flapping hinge may be written as

$$(1) \quad M_{AERO} + M_W + M_I + M_{CF} + M_{EHR} = 0.$$

The moment due to inertia force can be expressed as  $I_b \ddot{\beta}$ , where  $I_b$  is the blade moment of inertia about the flapping hinge. Substituting this into equation 1 and solving for  $\ddot{\beta}$ , the following governing equation is obtained.

$$(2) \quad \ddot{\beta} = \frac{M_{AERO} + M_W + M_{CF} + M_{EHR}}{I_b}$$

If the angle of attack and local Mach number at each blade segment were known, the CL and CD could be obtained







Figure 1 Blade Element Diagram




Figure 2 Rotor Blade Moment Diagram

from the inputted airfoil information. The local aerodynamic forces and moments can be calculated and the flapping acceleration determined. Equation 2 can be rewritten as

$$(3) \quad \ddot{\beta}_n = \sum_{i=1}^{K \text{ segments}} \frac{(dM_{AERO_i} + dM_{WI_i} + dM_{CF_i} + dM_{ENR_i})}{I_b}$$

The flapping angle and rate at the  $(N + 1)$  azimuthal position could be obtained from the following expressions.

$$(4) \quad \dot{\beta}_{n+1} = \dot{\beta}_n + \ddot{\beta}_n \Delta t$$

$$(5) \quad \beta_{n+1} = \beta_n + \dot{\beta}_n \Delta t + \ddot{\beta}_n \frac{\Delta t^2}{2}$$

However, since the flapping is periodic in nature and has a direct relationship to the azimuthal angle,  $\Psi$ , the values for flapping are solved with respects to  $\Psi$ , vice time. The values of  $\Omega$ ,  $\psi$  and time are related by the equation  $\Delta \Psi = \Omega \Delta t$ . Therefore

$$(6) \quad \dot{\beta} = \frac{d\beta}{dt} = \Omega \frac{d\beta}{d\Psi} = \Omega^* \dot{\beta}^*$$

$$(7) \quad \ddot{\beta} = \frac{d^2\beta}{dt^2} = \Omega^2 \frac{d^2\beta}{d\Psi^2} = \Omega^{2*} \ddot{\beta}^*$$

The governing equation for the flapping motion now becomes

$$(8) \quad \ddot{\beta}^* = \frac{M_{AERO} + M_{WI} + M_{CF} + M_{ENR}}{I_b \Omega^{2*}}$$

The flapping solution is based on the assumption that the angle of attack is known. However, it is not and the program must proceed through an iterative process in order to determine the inflow ratio, collective pitch and cyclic input angles required to generate the desired forces.

## B. ANGLE OF ATTACK CALCULATIONS

A very important and basic part of this program is the procedure by which the local angles of attack are calculated. While the program will calculate angle of attack with any angular velocity applied either to the rotor system or the helicopter, the development here will describe level flight only. The classical approach ignores radial flow,  $U_R$ , and the angle of attack would be obtained as shown in Figure 1. However, as the blade rotates about the shaft, it will encounter a large variation in radial flow. The program attempts to compensate for this radial flow in the following manner. Instead of the inflow angle  $\Phi$  equalling the arctangent of  $U_P/U_T$ , it is set equal to  $U_P/UTUR$  where  $UTUR$  is the resultant velocity in the tangential and radial direction. This is illustrated in Figure 3. The pitch angle is also reduced by the cosine of the sweep angle. The angle of attack is now calculated in the sweep plane. This three-dimensional angle of attack is lower than the classical two-dimensional angle.

The program enters the  $CL$ ,  $CD$  tables with this sweep plane angle of attack and the sweep plane resultant Mach number. The program computes the forces using the velocities in the sweep plane,  $U_P$  and  $UTUR$ , and the blade chord geometry in the normal plane. Once the forces are computed in the sweep plane they are resolved into their respective directional forces.

This three-dimensional angle of attack, due to sweep, will delay stall on the rotor by reducing the angle of attack. This describes what actually occurs on the blade. However, it is felt by previous personnel using the program that there is a point where the sweep becomes so large that it tends to wash out the lift being produced. The program has been modified to reduce  $CL$  by one half for sweep angles between 60 to 72.5 degrees and reduce  $CL$  to zero for sweep angles between 72.5 and 90 degrees. These high sweep angles occur normally only on the inboard blade segments of the




Figure 3 Spanwise Flow Diagram

retreating blade in and near the reverse flow region.

UP, UT, UR and pitch angle for level flight are shown in Figures 4 and 5. They are calculated in the following manner. The radial velocity, UR, is calculated as

$$(9) \quad UR = (V \cos \alpha_s) \cos \psi \cos \beta$$

The tangential velocity, UT, has two components. The first is the local rotational velocity,  $\Omega r$ , the second is a sinusoidal component of the forward flight velocity. The general expression for UT is

$$(10) \quad UT = \Omega r + (V \cos \alpha_s) \sin \psi$$

This expression contains a small angle assumption in the term  $\Omega r$  for blade flapping angle. The program accounts for the fact that the flapping angle does reduce the true radius slightly by using the following formula

$$(11) \quad UT = (E/R + (r - E/R) \cos \beta) \Omega + (V \cos \alpha_s) \sin \psi$$



The perpendicular velocity, UP, consists of three terms, the inflow ratio, a flapping velocity and a small component of forward velocity. The inflow ratio is defined as

$$(12) \quad \lambda = \frac{V \sin \alpha_s - v}{R}$$

The second component is a vertical flapping velocity which is a function of flapping rate and radius. This is computed as

$$(13) \quad UP(2) = (r - E/R) \dot{\beta}$$

The third component is due to the fact that there is a small component of the radial flow which acts in the UP direction due to blade flap angle. This is equal to



$$UT = (E/R + (R - E/R) \cos \theta) \Omega + (V \cos \alpha_s) \sin \psi$$

Figure 4 UT Diagram

$$U_P = \lambda \Omega R \cos \theta + (r - E/R) \dot{\theta} + (V \cos \alpha_s) \cos \psi \sin \theta$$

$$U_R = (V \cos \alpha_s) \cos \psi \cos \theta$$




Figure 5 UP and UR Diagram

$$(14) \quad UP(3) = (V \cos \alpha_s) \cos \Psi \sin \theta$$

The total formula for UP is

$$(15) \quad UP = \lambda \Omega R \cos \theta + (r - E/R) \dot{\theta} + (V \cos \alpha_s) \cos \Psi \sin \theta$$

The pitch angle ( $\theta$ ) is expressed in equation 16.  $\theta_{.75}$  is the pitch angle at the 75 percent radius position,  $\theta'$  is the twist depending on the relationship of the location of the blade segment to the  $r = .75R$  location. The next four terms are the first and second harmonics of cyclic pitch and  $(\tan \delta_3) \beta$  is the coupled effect of the flapping angle on the pitch angle.

$$(16) \quad \theta = (\theta_{.75} + \theta' - A1S \cos \Psi - B1S \sin \Psi - A2S \cos 2\Psi - B2S \sin 2\Psi - \tan(\delta_3) \beta) \cos \Lambda_{\text{sweep}}$$

The local Mach number is calculated as  $U/a$  where  $a$  is the speed of sound and  $U$  is given in equation 17.

$$(17) \quad U = (UP^2 + UT^2 + UR^2)^{1/2}$$

The angle of attack can now be calculated. Figure 1 illustrates that  $\alpha = \theta - \phi$ . Initially, the program requires estimated values for the inflow ratio, collective pitch at the PSI equal zero position, harmonic cyclic inputs, blade twist and initial flapping angle and rate. The user can either input these values or accept the program's automatic default values of -.02, 5, -1.2, 7.53, 0, 0 and 0 respectively. Using these assumed values, the initial angle of attack can be determined as follows.

$$UP = \lambda \Omega R \cos \theta + (r - E/R) \dot{\theta} + (V \cos \alpha_s) \cos \Psi \sin \theta$$

reduces to

$$UP = \lambda \Omega R$$



$$U_T = (E/R + (r - E/R) \cos \beta) \Omega + (V \cos \alpha_3) \sin \psi$$
  
 reduces to

$$U_T = (E/R + (r - E/R)) \Omega$$

$$U_R = (V \cos \alpha_3) \cos \psi \cos \beta$$
  
 reduces to

$$U_R = V \cos \alpha_3$$

In the program  $V \cos \alpha_3$  is replaced by the term  $\mu \Omega R$  where  $\mu$  is the advance ratio in the shaft axis system. Since the local pitch distribution and inflow ratio are estimated, the local angles of attack can be determined. The next section describes the method used for calculating flapping angle and rates at the  $N + 1$  azimuthal position.

### C. METHOD OF SOLUTION FOR THE FLAPPING EQUATION

In the preceding section, equation 8 was developed in order to calculate the time history of the flapping motion.

$$(8) \quad \ddot{\beta} = \frac{M_{AERO} + M_W + M_{CF} + M_{EHR}}{I_b \Omega^2}$$

The relation involves a complicated second order differential equation for establishing the flapping angle as a function of  $\psi$ . The numerical solution is accomplished by use of a finite difference equation and a step-by-step procedure. An important characteristic of the solution is that it is periodic in nature. The function which represents a steady state flapping solution has the property  $\beta(\psi) = \beta(\psi + 2\pi)$ . Using this fact, a Fourier harmonic series can be written to describe the blade flapping motion.

$$(18) \quad \beta = A_0 - A_1 \cos \psi - B_1 \sin \psi - A_2 \cos 2\psi - B_2 \sin 2\psi - A_3 \cos 3\psi - B_3 \sin 3\psi \dots$$

By assuming that the first harmonic flapping is much larger

than the other higher harmonics, the series can be reduced to

$$(19) \quad \beta = A_0 - A_1 \cos \psi - B_1 \sin \psi$$

This equation can be differentiated with respect to  $\psi$  to obtain

$$(20) \quad \dot{\beta} = A_1 \sin \psi - B_1 \cos \psi$$

$$(21) \quad \ddot{\beta} = A_1 \cos \psi - B_1 \sin \psi$$

Assuming that the values of  $\beta$ ,  $\dot{\beta}$  and  $\ddot{\beta}$  are known at some azimuthal position, the following equations must hold

$$(22) \quad \beta_n = A_0 - A_1 \cos \psi - B_1 \sin \psi$$

$$(23) \quad \dot{\beta}_n = A_1 \sin \psi - B_1 \cos \psi$$

$$(24) \quad \ddot{\beta}_n = A_1 \cos \psi + B_1 \sin \psi$$

These equations can be solved for the  $N + 1$  azimuthal position by substituting  $\psi_{n+1} = \psi_n + \Delta \psi$  into the above formulas. The flapping angle equation becomes

$$(25) \quad \beta_{n+1} = A_0 - A_1 \cos(\psi_n + \Delta \psi) - B_1 \sin(\psi_n + \Delta \psi)$$

By using the following two identities equation (25) can be rewritten as equation (28).

$$(26) \quad \cos(\psi_n + \Delta \psi) = \cos \psi_n \cos \Delta \psi - \sin \psi_n \sin \Delta \psi$$

$$(27) \quad \sin(\psi_n + \Delta \psi) = \sin \psi_n \cos \Delta \psi + \cos \psi_n \sin \Delta \psi$$

$$(28) \quad \beta_{n+1} = A_0 - A_1(\cos \psi_n \cos \Delta \psi - \sin \psi_n \sin \Delta \psi) - B_1(\sin \psi_n \cos \Delta \psi + \cos \psi_n \sin \Delta \psi)$$

The terms can be rearranged into equation 29. The same procedure can be used to develop equation 30 for  $\dot{\beta}$ .

$$(29) \quad \beta_{n+1} = A_0 - \cos \Delta \psi (A_1 \cos \psi_n + B_1 \sin \psi_n) + \sin \Delta \psi (A_1 \sin \psi_n - B_1 \cos \psi_n)$$

$$(30) \quad \dot{\beta}_{n+1} = \cos \Delta \psi (A_1 \sin \psi_n - B_1 \cos \psi_n) + \sin \Delta \psi (A_1 \cos \psi_n + B_1 \sin \psi_n)$$

Substitution into equations 22, 23 and 24 reduces these two

expressions to the flapping equations used in the program. The user can either enter the value for  $\Delta\psi$  or accept the programs automatic default value of 15 degrees.

$$(31) \quad \beta_{n+1}^* = \beta_n^* \cos \Delta\psi + \beta_n^{**} \sin \Delta\psi$$

$$(32) \quad \beta_{n+1} = \beta_n + \beta_n^* \sin \Delta\psi + (1 - \cos \Delta\psi) \beta_n^{**}$$

While this integration scheme is not one of the standard methods used, it is very useful in obtaining periodic solutions for differential equations similar to the one used here. Notice that for small values of  $\Delta\psi$  the trigonometric expression can be reduced to an ordinary Taylor series. By assuming  $\sin \Delta\psi$  equals  $\Delta\psi$  and  $\cos \Delta\psi$  equals one equation 29 reduces to

$$(33) \quad \beta_{n+1}^* = \beta_n^* + \Delta\psi \beta_n^{**}$$

By assuming  $\sin \Delta\psi$  equals  $\Delta\psi$  and  $\cos \Delta\psi$  equals the first two terms of the cosine series  $1 - \frac{\Delta\psi^2}{2}$  equation 32 can be reduced to

$$(34) \quad \beta_{n+1} = \beta_n + \Delta\psi \beta_n^* + \frac{1}{2} (\Delta\psi)^2 \beta_n^{**}$$

#### D. FORCES, MOMENTS AND RADIAL INTEGRATION

The forces acting on a rotor blade may be found by the summation of the elementary forces along the span at any azimuthal position. The forces considered by the program are the resulting aerodynamic forces only, and are initially summed in the shaft reference axis system. The program computes forces in three axis systems. They are the (1) shaft, (2) control and (3) relative wind axis systems.

The program radially integrates differently for lift and drag calculations. The drag is calculated from the hinge offset,  $E/R$ , to the rotor tip. The lift is calculated from

the hinge offset to the next to last rotor blade segment. The last segment is considered a blade "Tip Loss Factor" segment. It is assumed that the tip trailing edge vortices cause no lift to be produced in this segment. The normal procedure is to define this segment as the last three percent of the rotor blade radius.

The first of the maximum 15 blade segments is considered the spar or cut out segment. This is defined as the area between the hinge offset and the point where the airfoil actually begins. If no spar data are entered, it is assumed that this first segment produces no lift and drag is obtained by using the CD verse Alpha Tables for the first blade airfoil data deck entered. If spar data are entered, the first segment and all other segments designated spar segments will have the lift and drag characteristics of the entered spar data.

#### E. AZIMUTHAL INTEGRATION METHOD

Once the integration of the rotor forces and moments along the blade is complete, an integration around the azimuth must be performed in order to obtain the average forces and moments. Since the solution of the flapping equation is obtained by a step-by-step method, the integrands of the integrals over  $\Psi$  are known only at a certain number of equally spaced points around the azimuth. For equilibrium flapping the integral is a periodic function of  $\Psi$ , and for this case integration can be shown to be equivalent to an averaging process. This result makes the azimuthal integration simple. The following method is used where  $N$  is the number of azimuthal positions used in the calculations and  $b$  is the number of blades.

$$(35) \quad \frac{b}{2\pi} \int_0^{2\pi} \int_0^R F(x, \Psi) dx d\Psi = \frac{b}{N} \sum_{i=1}^N \sum_{j=1}^K dF(\Psi_{ij})$$

## F. MAJOR ITERATION

Once the program has calculated a steady state flapping solution and has determined the resulting forces and moments, a question remains to be answered. Is this the desired solution and, if not, what must be done to obtain this solution? In order to solve the flapping equations certain known or assumed values were used, including inflow ratio ( $\lambda$ ), collective pitch ( $\theta.75$ ) and the cyclic pitch ( $A1S$ ,  $B1S$ ,  $A2S$  and  $B2S$ ). One method, first described in Ref. 3, is to iterate on the required lift and drag through modification of  $\lambda$  and  $\theta.75$ , where  $\theta.75$  is the pitch angle at the 75 percent radius station at the PSI equal zero azimuthal position. The modified values are then reentered into the flapping routine and the calculation is repeated until it converges to within a specified tolerance on the required lift and drag. Drag is used here in the sense of negative rotor propulsive force. The program procedure is outlined below.

The required rotor lift and propulsive force are expressed in terms of the magnitude and direction of the resultant force in the longitudinal plane. These are shown in Figure 6 where it can be seen that

$$(36) \quad a'' = \alpha_s + a'$$

$$(37) \quad R_R = ( (F_{e_s})^2 + (F_{x_s})^2 )^{1/2}$$

$$(38) \quad L = R_R \cos(a'') \quad D = R_R \sin(a'')$$

The required lift and propulsive force and their resultant are shown in Figure 7. In a similar way,

$$(39) \quad R = ( L_R^2 + D_R^2 )^{1/2}$$

$$(40) \quad a'' = \arctan (D_R/L_R)$$

The differences between the required and the computed  $R_L$  and  $a''$  values are defined as

$$(41) \quad \Delta R_L = R_{LR} - R_L$$

$$(42) \quad \Delta a'' = a''_R - a''$$

In order to correct  $\lambda$  and  $\theta.75$  to compensate for the difference between  $(R_{LR}, a''_R)$  and  $(R_L, a'')$ , the required values are expanded in a Taylor series with  $\lambda$  and  $\theta.75$  as variables. The first order equations are:

$$(43) \quad R_{LR} = R_L + \frac{\partial R_L}{\partial \lambda} \Delta \lambda + \frac{\partial R_L}{\partial \theta.75} \Delta \theta.75$$

$$(44) \quad a''_R = a'' + \frac{\partial a''}{\partial \lambda} \Delta \lambda + \frac{\partial a''}{\partial \theta.75} \Delta \theta.75$$

Solving the equations for the iteration on  $\lambda$  and  $\theta.75$  yields



$$(45) \quad \Delta \lambda = \frac{\frac{\partial a''}{\partial \theta.75} \Delta R_L - \frac{\partial R_L}{\partial \theta.75} \Delta a''}{\frac{\partial R_L}{\partial \lambda} \frac{\partial a''}{\partial \theta.75} - \frac{\partial R_L}{\partial \theta.75} \frac{\partial a''}{\partial \lambda}}$$

$$(46) \quad \Delta \theta.75 = \frac{\frac{\partial R_L}{\partial \lambda} \Delta a'' - \frac{\partial a''}{\partial \lambda} \Delta R_L}{\frac{\partial R_L}{\partial \lambda} \frac{\partial a''}{\partial \theta.75} - \frac{\partial R_L}{\partial \theta.75} \frac{\partial a''}{\partial \lambda}}$$

Now that  $R_{LR}$ ,  $R_L$  and  $a''_R$  and  $a''$  are known, the corrected values of  $\lambda$  and  $\theta.75$  can be approximated by:

$$(47) \quad \lambda_N = \lambda + \Delta \lambda \quad \theta.75_N = \theta.75 + \Delta \theta.75$$

In order to solve equations 45 and 46, the values of the partial derivatives in these equations must be found. The



procedure used in based on the Wheatley-Bailey method and the formulas can be found on pages 186 and 207 of Ref. 4. Reference 5 outlines the derivation and a complete derivation was performed and verified in conjunction with this thesis.

#### G. FLOW CHART

The flow chart in Figure 8 is a block diagram showing the relationship between the various parts of the GRP program.



# GRP FLOW CHART




Figure 8

### III. GRP USERS' MANUAL

The GRP currently has the capability to enter over 200 individual case variables and option selectors. Presently, 170 are available to the users. This manual explains the input and output format of this GRP program. Examples of both input and output are given in order to make the use of this program easier. This manual is divided into the following areas of discussion.

- A. Main Iteration Options
- B. GRP Data Deck Order
- C. Airfoil Data Deck Requirements
- D. Spar Data Deck Requirements
- E. Sample Data Input Format
- F. Case Input Listings
- G. Case Input Default Values
- H. Case Input Data
- I. Case Input Format
- J. Case Optional Output Indicators
- K. IBM 360 Execution Control Cards
- L. Sample Program Output

It is recommended that the user examine the GRP Case Input listing carefully, since a few options require certain variables to be inputted which are not necessarily located in the same general area of the input listings. An attempt has been made to list all input variables concerned with the different options in the discussion of each option and input variable.

#### A. MAIN ITERATION OPTIONS

The GRP offers the user six different options for determining a solution. They are as follows.

### 1. Normal Routine

In the normal solution to the problem the computer will vary the inflow ratio, LAMBDA, and the pitch angle,  $\theta.75$ , in order to produce the required lift and drag. The cyclic inputs, A1S and B1S, are considered constants. Uniform inflow is assumed unless the user induces a non-uniform inflow by the use of variables 117 and 118, LAML and UVL. The program will calculate the required shaft axis angle and position of the control axis from the fixed value of B1S. In all of the options, the user has a choice of using either a program calculated first estimate of flapping angle, velocity and acceleration or an initial value of zero for all of the above. Either method usually requires the same approximate amount of computer time. The variable PCNV, item 97, determines the method to be used.

### 2. Desired Flapping Angles

This option allows the user to specify the desired longitudinal and lateral flapping angles with respect to the rotor shaft axis. The program at each intermediate force iteration will vary A1S, B1S, inflow ratio and pitch angle. Variables 100 and 112, 113 and 114 control the use of this option.

### 3. Short Iteration Scheme

This option follows the normal routine with one major exception. The program will make only one pass through the flapping routine on each major iteration. The program may or may not arrive at a steady state solution for flapping in the first few iterations. It is assumed that the first few iterations in the normal routine are only rough estimates of the way the variables should be changed and that an exact flapping solution is not actually required if the user is only interested in transient flapping

behavior. In order to use this routine, the user must input a negative number for the variable XITLIM, item 73. The absolute value of XITLIM will still determine the maximum allowable number of times the program will enter the major iteration routine.

#### 4. Trimmed Moments

This option will follow the Normal method described in paragraph one. The Normal method will only converge on lift and drag and will not consider the moments produced. If the variable TRIM, item 160, were assigned a non-zero value, the program would attempt to trim out the pitching and rolling moments about the rotor shaft. It is suggested that this be done in a two case run. The first case should be a normal run, with the desired printout. Then, for the second case, input the variable TRIM. This will do two things. First, it will provide a converged solution without consideration of moments. Secondly, it will allow the full number of iterations to be used to reduce the moments. The program does this by a short routine varying A1S and B1S. During this process, the whole flapping and force iterations must be repeated, but it will at least start by using a converged solution. The variable PCNV, item 97, should be non-zero to allow the flapping solution from the previous case to be used as a first estimate in this case. Setting the variable SKIPIN, item 91, equal to zero will allow a force and moment summation to be outputted for each major iteration. This will allow the user to see exactly how the program is proceeding.

#### 5. TOP Option

In this option, the program iterates upon the required lift but ignores any values inputted for required drag. This option can be used to simulate a wind-tunnel test. The user must input the shaft angle, item 111, and

the pitch angle, item 87. These two inputs will be held constant. The program will iterate on the inflow ratio, LAMBDA, in order to obtain a solution. The variable TOP, item 96, controls the use of this option.

#### 6. ALOFT Option

This option, like TOP, is a wind tunnel option. It also iterates on required lift only. However, here the shaft angle, item 111, and the inflow ratio, item 88, are required inputs and are held as constants. The program will iterate on the pitch angle, item 87, in order to determine a solution. The variable ALOPT, item 110, controls the use of this option.

#### B. GRP DATA DECK ORDER

Data is entered into this program in the following order.

1. Airfoil Lift Coefficient Table
  2. Airfoil Drag Coefficient Table  
(Repeat steps one and two as necessary.)
  3. Case Input Data
  4. Harmonics of the Inflow Ratio \*\*
  5. Spar Lift Coefficient Table \*\*
  6. Spar Drag Coefficient Table \*\*
- \*\* Optional Data

#### C. AIRFOIL BLADE DECK REQUIREMENTS

The GRP program requires that all CL and CD information be entered into the program in tabular form. Tables for up to 15 different Mach numbers and five different airfoils can be entered. The program currently does not use or require values for the Coefficient of Moment, CM. Since certain segments of the retreating blade are in the reverse flow region, angle of attack tables are required to include

valued from -180 degrees to +180 degrees. If they are not included, an error message will be printed when the program can not locate a value for CL and CD at these large positive and negative angles of attack. If complete angle of attack information is not available for a particular airfoil, the user can use the values provided in Section E. It is realized that available data on airfoil behavior at large angles of attack are very limited, but so is the region on the rotor disc where the blade operates at these high angles. Since this occurs only immediately around and within the reverse flow region where dynamic pressure is low, little precision is lost in performance calculation by using one common representation for most airfoil behavior.

As a minimum, two values for CL and CD at two different angles of attack and Mach numbers must be supplied. As a maximum, 15 different values of Mach number may be entered. Each Mach number may contain up to 48 different values of CL and 48 different values of CD and their associated angles of attack.

The first Mach number must be equal to zero. This table can be an exact duplicate of the lowest Mach number table the user has available. The highest Mach number table should be high enough in order to prevent the program from stopping because of a local Mach number higher than that in the table. A quick check can be obtained by adding together the rotor tip velocity and the forward flight speed. This combined velocity, divided by the local speed of sound, must be less than the maximum Mach number entered into the program. The program linearly interpolates between Mach numbers and angles of attack in order to determine the value of CL and CD. The subroutine BLIN4 does the interpolation.

Several options are available to help reduce the number of data points that must be entered. If the airfoil is symmetrical, the user only needs to enter values for positive angles of attack. The program will assign the

appropriate sign to the value of CL and CD according to the sign of the angle of attack. This is accomplished by case input variable 107, SYM. This option can also be used for a cambered airfoil where values of CL and CD at negative angles of attack are unknown.

Values for large angles of attack need not be entered for each Mach number by making use of the program's input variables 156 and 157, or their automatic default values. Values for large positive and negative angles of attack need only be entered for the two lowest Mach number tables. The lowest Mach number table must be at a Mach number equal to zero. If an angle of attack is greater than variable 156 (HIALFA) or lower than variable 157 (LOALFA), or the programs default values of plus and minus 30 degrees, the Mach number is set equal to zero. This ensures that only the first two Mach numbers have to carry the whole range of angles of attack from -180 to +180 degrees for a cambered airfoil or from zero to +180 degrees for a symmetrical airfoil.

The format of the table input will now be described. The first data card contains the variable WBLADE. This controls whether or not the user receives an echo printout of the Blade Airfoil Data being entered. If the value of WBLADE is equal to zero, the user will not receive an echo printout of the Blade Data. If WBLADE is a non-zero number, the user will receive the echo printcut. The read format for WBLADE is F10.0. WBLADE is the only item on the first data card.

The next card also contains only one piece of data, NBLADE. NBLADE is the number of different airfoil data sets to be used and appears on this card in an I2 format. This program will accept up to five different blade airfoil data sets. It will also accept one blade spar data set. If the rotor blade being analyzed were composed of three different types of airfoils, NBLADE would equal three. However, if

the blade consisted of three sections, of which the first and third section were the same, NBLADE would equal two. It is explained later how the blade segments are assigned their respective airfoil type. This arrangement provides the user with the ability to vary the make-up of the blade while only having to enter into the program once a particular set of airfoil data.

The above two variables, WBLADE and NBLADE, are only entered once for each complete computer run which uses the same set of airfoil data. The following information will be entered twice for each type of airfoil used. It will be entered first for CL and secondly for CD for each type airfoil. The overall format is summarized below.

Card 1      WBLADE  
Card 2      NBLADE  
Card 3-     CL's for airfoil number one  
             CD's for airfoil number one  
             CL's for airfcil number two  
             CD's for airfcil number two  
             Repeat as necessary.

Card number three contains the variable NZ, which is the number of Mach numbers for which CL's will be entered for the first airfoil. This number must be right justified in I2 format. The maximum number of Mach numbers for each CL and CD for one airfoil is 15. This is the only number entered on this card.

Card number four begins the actual Mach number, CL versus angle of attack tables. The format in this paragraph must be repeated for each Mach number. This first card is divided into 11 fields (I2, 10F7.0). The first field is a two-digit, right-justified integer in I2 format. It is equal to twice the number of data pairs for this Mach number plus two. This tells the computer how many numbers are required to be entered for this particular Mach number. A data pair consist of one angle of attack and its associated



CL or CD. The remaining ten fields are each seven columns long in floating point or F7.0 format. These fields begin in columns 3, 10, 17, 24, 31, 38, 45, 52, 59, and 66. On this first card, the field that starts in column three contains the number of data pairs at this Mach number. The field that begins in columns 10 is the actual Mach number. The remaining eight fields on this card are for the first four data pairs starting with the lowest angle of attack and increasing towards the highest angle of attack. If a symmetrical airfoil option is used, the lowest angle of attack is zero. If a non-symmetrical airfoil is used, the lowest value for the first two Mach numbers should be -180 degrees and for all the remaining Mach numbers the value of LOMACH entered or -30 degrees.

All the remaining cards for this particular Mach number will contain the data pairs. These cards contain ten fields each, the first field consisting of nine columns and the remaining nine fields consist of seven columns beginning in column ten and following the same format as the first card. The format is (F9.0, 9F7.0). This card is repeated as often as needed. Columns 73-80 are not read and may be used for comments.

This procedure is repeated until all the CL's are entered. Once completed the program is ready to enter the values for CD. The whole procedure is repeated again, starting with the value for NZ representing the number of Mach numbers for which CD's will be entered. If more than one airfoil data deck is to be used, the above procedure will start over again by reading in the value of NZ for the number of Mach numbers to be entered for values of CL for the second airfoil. The number of data pairs for each Mach number must be between 2 and 48. The number of "twice the data pairs plus two" must be between 6 and 98.

Prior to entering the airfoil data, the user should review the following input variables.

1. SYM (107) - Symmetrical and nonsymmetrical airfoil data input control.
2. HIALFA (156) - The highest angle of attack for which values of CL and CD will be found at all Mach numbers.
3. LOAFLA (157) - The lowest angle of attack for which values of CL and CD will be found at all Mach numbers.
4. SPAR (103) - Number of segments using spar airfoil data.
5. TIPSWP (158) - Amount of tip sweep in degrees.
6. TPSWST (159) - Blade segment number at which the tip sweep begins.
7. BSPL (120) - Input control variable for spar data.
8. RB(I) (161-175) - Controls the blade segment airfoil data assignment.

#### D. SPAR DATA DECK REQUIREMENTS

The format for spar data are similar to that of the airfoil data with the exception that only one set of spar data can be entered into the program. Before the program will read spar data, input variable number 120, BSPL, must have a non-zero value. In addition, variable 103, SPAR, must indicate the number of blade segments which are using the spar data. The program automatically assumes that the first segment is a spar segment. This is further explained in the Case Input section. The spar data are the last to be entered into the program. This is an optional input and is not required. If spar data are not inputted, the program will assume that the one automatic spar section creates no lift and has the drag characteristics of the first airfoil section entered.

The format for inputting spar data are as follows. The first card contains the variable WRSPAR in F10 0 format. A non-zero value of WRSPAR causes an echo printout of spar data to occur. The remaining spar data are handled the exact same way as the airfoil section data, starting with the variable NZ. There is no input similar to that of the airfoil section stating how many different spar data decks are being entered since only one is allowed. As before, a minimum of two Mach numbers are required to be entered. The blade segment printout indicates spar segments by the use of a "0" for that segment.

Input variables associated with SPAR data are as follows.

1. SPAR (103) - The number of blade segments using spar data.
2. BSPL (120) - Input variable which controls the input and use of spar data.

#### E. SAMPLE BLADE INPUT

The next several pages illustrates the sample format for a blade which has the following characteristics: (1) an echo printout is not required, (2) there are two airfoil decks to be read in and (3) the first airfoil deck has nine values of Mach numbers for which CL's are to be entered.





6 16. 23.	061	126	10.	162	12.	238	14.	.284
48 -14.	.329	.372	20.	.415	22.	.458	-16.	.3655
-4.	.03278	.479	-10.	.225	-8.	.403	4.	.09
6 16. 23.	.065	.028	0.	.017	22.	.16	14.	.328
48 -14.	.1285	.17	10.	.225	22.	.285	-16.	.397
-4.	.3655	.403	20.	.415	-8.	.479	4.	.149
6 16. 23.	0 363	.437	-10.	.463	22.	.43	14.	.12
48 -14.	.115	.336	0.	.262	22.	.203	-16.	.357
-4.	.167	.066	10.	.052	22.	.08	4.	.397
6 16. 23.	.391	.21	20.	.262	22.	.3225	-16.	.202
48 -14.	1 399	.43	-10.	.463	-8.	.497	4.	.1525
-4.	.1523	.514	0.	.297	22.	.457	14.	.393
6 16. 23.	.203	.117	10.	.09	22.	.2485	-16.	.428
48 -14.	.42	.249	20.	.286	22.	.514	4.	.202
9 48.	0 68	0	-172.	166.	-130.	8	-160.	.66
98 -158.	.1 099	1 0 09	-30.	130.	-12.	1 098	-60.	-1 0975
-18.	.63	.403	-14.	12.	-2.	.242	-10.	-.72
-8.	.378	.59	-4.	8.	8.	.07	0.	.15
2 12.	1 032	1 01	16.	18.	18.	1 032	10.	1 25
22 132.	1 66	1 06	40.	50.	50.	1 09	20.	1 04
160 48.	0 3	.8	172.	180.	180.	1 09	60.	1 0
98 -158.	.68 09	0	-172.	166.	-130.	0	158.	-.68
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-160.	.66
-18.	.63	.403	-14.	12.	-2.	.242	-60.	-1 0975
-8.	.378	.59	-4.	8.	8.	.07	-10.	-.72
2 12.	1 032	1 01	16.	18.	18.	1 032	0.	.15
22 132.	1 66	1 06	40.	50.	50.	1 09	10.	1 25
160 48.	0 3	.8	172.	180.	180.	1 09	20.	1 04
98 -158.	.68 09	0	-172.	166.	-130.	0	60.	1 0
-50.	.689	1 0 09	-30.	130.	-12.	1 098	158.	-.68
-18.	.63	.403	-14.	12.	-2.	.242	-160.	.66
-8.	.378	.59	-4.	8.	8.	.07	-60.	-1 0975
2 12.	1 032	1 01	16.	18.	18.	1 032	-20.	-.72
22 132.	1 66	1 06	40.	50.	50.	1 09	0.	.15
160 48.	0 3	.8	172.	180.	180.	1 09	10.	1 25
98 -158.	.68 09	0	-172.	166.	-130.	0	20.	1 04
-50.	.689	1 0 09	-30.	130.	-12.	1 098	60.	1 0
-18.	.63	.403	-14.	12.	-2.	.242	158.	-.68
-8.	.378	.59	-4.	8.	8.	.07	-160.	.66
2 12.	1 032	1 01	16.	18.	18.	1 032	-60.	-1 0975
22 132.	1 66	1 06	40.	50.	50.	1 09	-20.	-.72
160 48.	0 3	.8	172.	180.	180.	1 09	0.	.15
98 -158.	.68 09	0	-172.	166.	-130.	0	10.	1 25
-50.	.689	1 0 09	-30.	130.	-12.	1 098	20.	1 04
-18.	.63	.403	-14.	12.	-2.	.242	60.	1 0
-8.	.378	.59	-4.	8.	8.	.07	158.	-.68
2 12.	1 032	1 01	16.	18.	18.	1 032	-160.	.66
22 132.	1 66	1 06	40.	50.	50.	1 09	-60.	-1 0975
160 48.	0 3	.8	172.	180.	180.	1 09	-20.	-.72
98 -158.	.68 09	0	-172.	166.	-130.	0	0.	.15
-50.	.689	1 0 09	-30.	130.	-12.	1 098	10.	1 25
-18.	.63	.403	-14.	12.	-2.	.242	20.	1 04
-8.	.378	.59	-4.	8.	8.	.07	60.	1 0
2 12.	1 032	1 01	16.	18.	18.	1 032	158.	-.68
22 132.	1 66	1 06	40.	50.	50.	1 09	-160.	.66
160 48.	0 3	.8	172.	180.	180.	1 09	-60.	-1 0975
98 -158.	.68 09	0	-172.	166.	-130.	0	-20.	-.72
-50.	.689	1 0 09	-30.	130.	-12.	1 098	0.	.15
-18.	.63	.403	-14.	12.	-2.	.242	10.	1 25
-8.	.378	.59	-4.	8.	8.	.07	20.	1 04
2 12.	1 032	1 01	16.	18.	18.	1 032	60.	1 0
22 132.	1 66	1 06	40.	50.	50.	1 09	158.	-.68
160 48.	0 3	.8	172.	180.	180.	1 09	-160.	.66
98 -158.	.68 09	0	-172.	166.	-130.	0	-60.	-1 0975
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-20.	-.72
-18.	.63	.403	-14.	12.	-2.	.242	0.	.15
-8.	.378	.59	-4.	8.	8.	.07	10.	1 25
2 12.	1 032	1 01	16.	18.	18.	1 032	20.	1 04
22 132.	1 66	1 06	40.	50.	50.	1 09	60.	1 0
160 48.	0 3	.8	172.	180.	180.	1 09	158.	-.68
98 -158.	.68 09	0	-172.	166.	-130.	0	-160.	.66
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-60.	-1 0975
-18.	.63	.403	-14.	12.	-2.	.242	-20.	-.72
-8.	.378	.59	-4.	8.	8.	.07	0.	.15
2 12.	1 032	1 01	16.	18.	18.	1 032	10.	1 25
22 132.	1 66	1 06	40.	50.	50.	1 09	20.	1 04
160 48.	0 3	.8	172.	180.	180.	1 09	60.	1 0
98 -158.	.68 09	0	-172.	166.	-130.	0	158.	-.68
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-160.	.66
-18.	.63	.403	-14.	12.	-2.	.242	-60.	-1 0975
-8.	.378	.59	-4.	8.	8.	.07	-20.	-.72
2 12.	1 032	1 01	16.	18.	18.	1 032	0.	.15
22 132.	1 66	1 06	40.	50.	50.	1 09	10.	1 25
160 48.	0 3	.8	172.	180.	180.	1 09	20.	1 04
98 -158.	.68 09	0	-172.	166.	-130.	0	60.	1 0
-50.	.689	1 0 09	-30.	130.	-12.	1 098	158.	-.68
-18.	.63	.403	-14.	12.	-2.	.242	-160.	.66
-8.	.378	.59	-4.	8.	8.	.07	-60.	-1 0975
2 12.	1 032	1 01	16.	18.	18.	1 032	-20.	-.72
22 132.	1 66	1 06	40.	50.	50.	1 09	0.	.15
160 48.	0 3	.8	172.	180.	180.	1 09	10.	1 25
98 -158.	.68 09	0	-172.	166.	-130.	0	20.	1 04
-50.	.689	1 0 09	-30.	130.	-12.	1 098	60.	1 0
-18.	.63	.403	-14.	12.	-2.	.242	158.	-.68
-8.	.378	.59	-4.	8.	8.	.07	-160.	.66
2 12.	1 032	1 01	16.	18.	18.	1 032	-60.	-1 0975
22 132.	1 66	1 06	40.	50.	50.	1 09	-20.	-.72
160 48.	0 3	.8	172.	180.	180.	1 09	0.	.15
98 -158.	.68 09	0	-172.	166.	-130.	0	10.	1 25
-50.	.689	1 0 09	-30.	130.	-12.	1 098	20.	1 04
-18.	.63	.403	-14.	12.	-2.	.242	60.	1 0
-8.	.378	.59	-4.	8.	8.	.07	158.	-.68
2 12.	1 032	1 01	16.	18.	18.	1 032	-160.	.66
22 132.	1 66	1 06	40.	50.	50.	1 09	-60.	-1 0975
160 48.	0 3	.8	172.	180.	180.	1 09	-20.	-.72
98 -158.	.68 09	0	-172.	166.	-130.	0	0.	.15
-50.	.689	1 0 09	-30.	130.	-12.	1 098	10.	1 25
-18.	.63	.403	-14.	12.	-2.	.242	20.	1 04
-8.	.378	.59	-4.	8.	8.	.07	60.	1 0
2 12.	1 032	1 01	16.	18.	18.	1 032	158.	-.68
22 132.	1 66	1 06	40.	50.	50.	1 09	-160.	.66
160 48.	0 3	.8	172.	180.	180.	1 09	-60.	-1 0975
98 -158.	.68 09	0	-172.	166.	-130.	0	-20.	-.72
-50.	.689	1 0 09	-30.	130.	-12.	1 098	0.	.15
-18.	.63	.403	-14.	12.	-2.	.242	10.	1 25
-8.	.378	.59	-4.	8.	8.	.07	20.	1 04
2 12.	1 032	1 01	16.	18.	18.	1 032	60.	1 0
22 132.	1 66	1 06	40.	50.	50.	1 09	158.	-.68
160 48.	0 3	.8	172.	180.	180.	1 09	-160.	.66
98 -158.	.68 09	0	-172.	166.	-130.	0	-60.	-1 0975
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-20.	-.72
-18.	.63	.403	-14.	12.	-2.	.242	0.	.15
-8.	.378	.59	-4.	8.	8.	.07	10.	1 25
2 12.	1 032	1 01	16.	18.	18.	1 032	20.	1 04
22 132.	1 66	1 06	40.	50.	50.	1 09	60.	1 0
160 48.	0 3	.8	172.	180.	180.	1 09	158.	-.68
98 -158.	.68 09	0	-172.	166.	-130.	0	-160.	.66
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-60.	-1 0975
-18.	.63	.403	-14.	12.	-2.	.242	-20.	-.72
-8.	.378	.59	-4.	8.	8.	.07	0.	.15
2 12.	1 032	1 01	16.	18.	18.	1 032	10.	1 25
22 132.	1 66	1 06	40.	50.	50.	1 09	20.	1 04
160 48.	0 3	.8	172.	180.	180.	1 09	60.	1 0
98 -158.	.68 09	0	-172.	166.	-130.	0	158.	-.68
-50.	.689	1 0 09	-30.	130.	-12.	1 098	-160.	.66
-18.	.63	.403	-14.	12.	-2.	.242	-60.	-1 0975
-8.	.378	.59	-4.	8.	8.	.07	-20.	-.72
2 12.	1 032	1 01	16.	18.	18.	1 032	0.	.15
22 132.	1 66	1 06	40.	50.	50.	1 09	10.	1 25
160 48.	0 3	.8	172.	180.	180.	1 09	20.	1 04
98 -158.	.68 09	0	-172.	166.	-130.	0	60.	1 0
-50.	.689	1 0 09	-30.	130.	-12.	1 098	158.	-.68
-18.	.63	.40						



16.23.	225	24	20.20.	268	22.18.	295	233	28
48-14.	0.2315	43	-10.	15	-8.	397	097	.051
6.16.23.	0.0137	193	0.10.	071	2.2.	128	008	.009
48-14.	0.2666	31	20.20.	363	22.18.	4167	128	.2033
6.16.23.	0.0282	4143	-10.	1533	-8.	322	322	-284
48-14.	0.0427	1973	0.10.	088	2.2.	102	102	.0577
6.16.23.	0.2776	083	20.20.	1325	22.18.	189	189	.238
48-14.	0.2876	368	-10.	385	-8.	434	434	.329
6.16.23.	0.0425	2411	0.10.	415	2.2.	372	372	.076
48-14.	0.0925	1368	20.20.	1813	-8.	117	117	.053
6.16.23.	0.32878	368	-10.	412	2.2.	238	238	.2816
48-14.	0.07582	479	0.10.	441	22.18.	403	403	.3655
6.16.23.	0.362	2282	20.20.	225	-8.	17	17	.122
48-14.	0.3697	182	0.10.	439	2.2.	285	285	.108
6.16.23.	0.367	533	20.20.	4672	22.18.	433	433	.323
48-14.	0.11527	366	-10.	262	-8.	21	21	.4
6.16.23.	0.1897	225	0.10.	262	2.2.	1225	1225	.163
48-14.	1.399	5145	20.20.	4855	22.18.	493	493	.138
6.16.23.	1.522	3717	-10.	297	-8.	457	457	.357
48-14.	2.152	117	0.10.	1	2.2.	248	248	.428
6.16.	422	2552	20.	298	2.2.	136	136	.202
		452		4815	22.	363	363	.17
				4815	22.	511	511	.3925



# F. INPUT CASE LISTING

## GRP CASE INPUTS

ITEM NO.	DESCRIPTION	PROGRAM VARIABLE	DIMENSION	REQUIRED
1	Tip Speed	OMEGAR	FPS	YES
2	Radius	R	FT	YES
3	Speed of Sound	SPSD	FPS	YES
4	Air Density	RHO	SLG/CUFT	YES
5	No. of Blades	XNB	-	YES
6	Forward Speed	VEL	KTS	89, 90
7	Offset Ratio of Flap Hinge (e/R)	ER	-	YES
8-22	Delta X	DX(15)	-	YES
23-37	Local Twist	TW(15)	DEG	92
38-52	Local Mass Density	XMASS(15)	SLG/FT	78, 79
53-67	Local Chord	C	FT	YES
68	Delta PSI	DPSI	DEG	**
69	Flap Iteration Limit	FTRL	-	**
70	Initial Beta	BIN	RAD	**
71	Initial Beta *	BPIN	RAD/SEC	**
72	Initial Beta **	BPPIN	RAD/SEC**2	**
73	Lift and Drag Iteration Limit	XITLIM	-	**
74	Required Lift	RL	LB	YES
75	Required Drag	RD	LB	95
76	Lift Tolerance	XLTOL	LB	**
77	Drag Tolerance	XDTOL	LB	**
78	First Moment about Flap Hinge (M)B	FMOM	SLG-FT	38-52
79	Second Moment about	SMOM	SLG-SQFT	38-52
80-82	Shaft Orientation	AG, BGL, CG	DEG	**
83	Pitch-Flap Coupling Angle (Delta 3)	TD3L	DEG	-
84	Drag Increment	DELD	-	-
85	Lat. Cyclic Pitch	A1S	DEG	**

86	Long. Cyclic Pitch	B1S	DEG	**
87	Collective Pitch	T75	DEG	**
88	Inflow Ratio	LAMBDA	-	**
89	Advance Ratio	MUL	-	6, 90
90	VEL Control	UIN	-	6, 89
91	Iteration Output	SKIPIN	-	**
92	Linear Twist	TWIST	DEG	23-37
93	No. of Blade Segments	XNSEG	-	**
94	Climb Rate	RCFPM	FPM	-
95	Flat Plate Area	FPAREA	FT**2	75
96	Thrust Option	TOP	-	-
97	Flapping Re-Use Indicator	PCNV	-	**
100	MU Iteration Tolerance	ABIT	-	-
101	Beta Tolerance	BTOL	-	**
102	Beta* Tolerance	BPTOL	-	**
103	Spar Segments	SPAR	-	-
104-105	Second Harmonic Control Inputs	A2S, B2S	DEG	-
106	Solidity	RSL	-	-
107	Symmetric Airfoil	SYM	-	-
108	Spring Constant	SPH	FT-LB/RAD	-
109	Damping Constant	FDMP	FT-LB/ RAD/SEC	-
110	Lift Only Option	ALOFT	-	-
111	Shaft Angle	ALL	DEG	-
112-113	Desired A1 and B1 Flapping	RA1S RB1S	DEG	-
114	A1, B1 Tolerance	TOLAB	DEG	**
115	Tangent Delta 3	TD3B	-	-
116	Phase Angle for Delta 3	PHD3B	DEG	-
117	Induced Velocities	LAML	-	-
118	Induced Velocities	UVL	-	-
119	Not Used			
120	Input Spar Data	BSPL	-	-

121	Azimuthal Printout Indicator	PPSI	DEG	**
122	Minimum Lift Curve Slope	ATEST	-	-
123	Iteration Gain Factor	IGC	-	**
124-125	Not Used			
126	Pre-Coning Angle	PCR	RAD	-
127-137	Not Used			
138	Hub Moment Inplane Aero Forces	INPL	-	-
139-141	Aircraft Yaw, Roll and Pitch Angular Velocities	PSIS, PHIS THFS	RAD/SEC	-
142	CG Station	FSCG	INCHES	-
143	Rotor Center Station	FSMR	INCHES	-
144	CG Waterline	WLCG	INCHES	-
145	Rotor Waterline	WLMR	INCHES	-
146	Aircraft Lateral Velocity	VELY	KT 3	-
147	Spar Symmetry	SYMSPR	-	-
156	Airfoil Tables	HIALFA	DEG	**
157	Airfoil Tables	LOALFA	DEG	**
158	Tip Sweep	TIPSWP	DEG	**
159	Sweep Station	TPSWST	-	**
160	Rotor Moments	TRIM	-	-
161-175	Rotor Blade Airfoil Data Assignments	RD	-	**

\*\* Program has automatic default value.

# G. GRP INPUT DEFAULT VALUES

ITEM NO	PROGRAM VARIABLE	DEFAULT VALUE
68	DPSI	15.0
69	FTRL	15.0
73	XITLIM	15.0
76	XLTOL	100.
77	XDTOL	50.0
81	BGL	90.0
85	A1S	-1.2 *
86	B1S	7.53 *
87	T75	5.0
88	LAMBDA	- .02
91	SKIPIN	1.0
93	XNSEG	15.0
97	PCNV	1.0
101	BTOL	.001
102	BPTOL	.001
114	TOLAB	0.25
121	PPSI	DPSI
122	ATEST	5.0 **
123	IGC	1.0
156	HIALFA	30.
157	LOALFA	-30.
159	TPSWST	16.
161-175	RB	1.0

\* 0. if ABIT, item 100, is non-zero

\*\* -50 is TOP, item 96, is non-zero

## H. CASE INPUT DATA

Many of the case inputs are self-explanatory by their name listing alone, however, many are not. This section will explain the input variables and case options available to the user.

The program enters all the variables into a 200 element array called V(I). Prior to entering case data, the program will automatically do two things. It will initialize the array V(I) to a value of zero. It will assign the default values listed in the previous section to those particular variables.

The V(I) array is associated with the variable names by equivalent statements. The user needs only to enter values for the variables that are different from the default or initialized values. In a multiple case computer run, the user need only enter variables that are different from the preceeding case. If no new value is enter for a variable, the value from the previous case is carried over.

### 1. Item 6 - Velocity - VEL

The computer program will accept forward velocity in one of two ways. The user will input either VEL, item 6, in knots or advance ratio MUY, item 89. The value of UIN, item 90, determines which variable will be used. If UIN is zero, VEL will be used. If UIN is non-zero, MUL will be used. If VEL is used, the program calculates the advance ratio by the following expression.

$$\mu = \left[ (V / \Omega R^2) - \lambda^2 \right]^{1/2}$$

If MUL is used, the program will calculate the flight velocity by the following expression.

$$V = [(\mu^2 + \lambda^2) \Omega R^2]^{1/2}$$

## 2. Item 7 - Hinge Offset - ER

The offset ratio of the flap hinge, E/R, is the distance from the center of the rotor shaft to the vertical flapping hinge, normalized by the rotor radius, item 2.

## 3. Items 8-22 - Delta X - DX

Delta X is the non-dimensionalized width of each individual blade segment starting with segment number one. There may be up to 15 segments entered. The number of widths entered here must equal the value of Item 93, XNSEG. XNSEG is the number of segments into which the blade is divided. This can range from two to fifteen. It is recommended that a value of ten or more be used for XNSEG. If XNSEG were equal to 12, values of Delta X would be entered for items 8 to 19 and no values would be entered for items 20 to 22. The sum of ER plus the summation of the Delta X's must equal one. ER is the non-dimensional width between the rotor shaft and the flapping hinge offset. Item number 8, which is the first segment width, represents the width between the flapping hinge offset and the point where the actual rotor blade airfoil begins. This area is known as the spar or cut out segment if no spar data were entered. If item 103, SPAR, is zero, the program will assume that this first section creates no lift and has the drag characteristics of the first inputted airfoil data section. Since this area experiences relatively low dynamic pressure, the calculations in this segment do not have an appreciable effect on the outcome of the program. The area between the shaft and the hinge offset, ER, produces neither lift nor drag in the program's calculations. The last segment is

considered a tip loss factor segment. The lift is assumed to be zero, but drag is calculated in the normal manner. In previous runs, the width of this section has been set equal to three percent of the rotor radius, or Delta X equal to .03.

#### 4. Items 23-37 - Twist - TW

The program has two options for entering geometric twist into the calculations. If the blade has linear twist, item 92, TWIST, can be used. If the twist is non-linear, the twist can be entered in items 23-37, TW. If a number is entered for item 92, the program will assume linear twist and ignore all values entered for TW. The local twist at the center of each segment can be entered starting with item 23. If the blade contains ten segments, items 23-32 would be entered and no values for items 33-37 would be entered.

A word of caution is necessary regarding the linear twist option, item 92. The twist is considered to be zero at the 75 percent chord point. The twist is calculated assuming that the twist starts at the rotor shaft and varies linearly out to the rotor tip. If the actual rotor blade airfoil started at the 25 percent radius point with a twist value of -9 degrees, a value of linear twist equal to -12 degrees would have to be entered in order for the correct twist distribution to be calculated by the program.

#### 5. Items 38-52 - XMASS

The program provides two methods for entering the local mass density or the moment of inertia information. The individual mass density for each section can be entered in items 38-52, or the First and Second Moment, FMOM and SMOM, about the Flapping Hinge, can be entered in items 78 and 79. If data are entered for item 79, the Second Moment about the Flapping Hinge, the program will use the information provided by items 78 and 79. If variable 79 is

equal to zero, the program will calculate the First and Second Moments for items 38-52 and ignore any value entered for items 78 and 79.

#### 6. Items 53-57 - Chord

The program has two methods for entering local chord data. The local chord at each segment can be entered starting with segment number one. If the chord is a constant chord, the amount of data to be entered can be reduced to only items 53 and 54. If items 53 and 54 are equal, the program assumes that the chord is constant throughout the radius and will ignore any information entered in items 55-67. Therefore, for constant chord, only enter values for items 53 and 54. If the rotor solidity is not inputted in item 106, the program will compute solidity as follows.

$$\sigma = \frac{b c .15}{\pi R}$$

#### 7. Item 68 - DPSI

DPSI, or Delta PSI, is the incremental azimuthal value by which the program advances in its blade flapping and force summation routine. This number must divide evenly into 360 degrees. A minimum value of five degrees is permitted. It has been found that for most cases decreasing the value of DPSI below 15 degrees does not improve the accuracy but does increase the computational time. As an example, the rotor horsepower required for one particular run was 1096 RHP for DPSI equal to 15 degrees, 1095 RHP for DPSI equal to 10 degrees and 1097 RHP for DPSI equal to 5 degrees. DPSI has a default value of 15 degrees.



#### 8. Item 69 - FTRL

FTRL is the maximum limit on the number of times that the program will enter the flapping iteration routine in search of a steady state flapping solution. The program has an automatic default value of 15 iterations. The program usually arrives at a steady state flapping solution within three to four iterations. The only method by which the user can actually determine the number of flapping iterations required would be to use one of the debug output options. However, these options will create a huge amount of output and the user is cautioned about their use.

#### 9. Items 70-72 BIN-BPPIN

The program has three options on how to assign the values for the initial flapping angle, velocity, and acceleration at the PSI equal zero position. The user may (1) input the values, (2) have the program itself calculate initial values, or (3) accept the default values of zero. Option three is the most used option. It has been discovered that there is little or no difference in solution time between option two and three. Variable number 97, PCNV, controls which option is to be used. If PCNV is non-zero, the program will use either option one or three. The program initially assigns values of zero to BIN, BFIN, and BPPIN before the initial case data are entered. PCNV is assigned the default value of one. Therefore, with no values entered by the user for items 70-72 and 97, the program will start with an initial value for flapping angle, velocity and acceleration at the PSI equal zero position of zero.

If the user sets PCNV equal to zero, the following formulas are used for determining the initial values. These formulas are derived from page 194 of Ref. 4.

$$\beta = \frac{\gamma}{2} \left[ \frac{\sigma}{4}(1 + \mu^2) + \frac{\lambda}{3} \right] - \frac{\mu \left[ \frac{\sigma}{3} - 2\lambda \right]}{1 - \frac{\mu^2}{2}}$$

$$\dot{\beta} = \frac{-\frac{1}{3}\mu \frac{\gamma}{2} \left[ \frac{\sigma}{4}(1 + \mu^2) + \frac{\lambda}{3} \right]}{1 + \frac{\mu^2}{2}}$$

$$\ddot{\beta} = \frac{\mu \left[ \frac{\sigma}{3} - 2\lambda \right]}{1 - \frac{\mu^2}{2}}$$

The term  $\gamma$  is referred to as the Lock number where

$$\gamma = \frac{C_{ns} \rho a R^4}{I_b}$$

In a run where more than one case is executed at a time, a non-zero value for PCNV allows the previous case values for flapping angle, velocity and acceleration to be used as the initial estimate for these variables in the next case. If PCNV is equal to zero, the initial values will be calculated by the above formulas. Most cases are run by accepting the default value of one for PCNV.

#### 10. Item 73 - XITLIM

After the program calculates a steady state flapping solution for its estimated values of inflow ratio, pitch angle and shaft tilt angle, the program determines the forces and moments generated by this solution. If the forces and, optionally, moments do not meet the required amounts entered by the user, the program will calculate new values to re-enter the flapping routine. XITLIM determines the maximum number of times the program will compare the calculated values to the desired values. The program has a default value of 15 for XITLIM. A majority of the solutions require approximately five iterations to converge. Once the XITLIM limit is exceeded, the program will stop and printout an "Exceeded Limit" statement. The program automatically prints as output the number of Major iterations it uses in calculating the solution.

The sign of XITLIM controls the Short Iteration Option. If XITLIM is a negative number, the program uses this option. A complete description can be found in the section entitled Main Iteration Options.

11. Item 74 - Required Lift

The required lift, RL, should equal the actual weight of the helicopter that the rotor system is supporting.

12. Item 75 - Required Drag

The required drag can be entered in one of two ways. It can be entered directly in item 75 or it can be calculated by the program by entering the aircraft's flat plate area in item 95, FPAREA. The drag is equal to the flight path force that the rotor system must overcome to sustain level flight at a certain velocity. Items 75 and 92 can be entered either as positive or negative numbers and the program will provide the correct forward flight solution by assigning the proper sign value internally. If a value is entered for FPAREA, the program will ignore any value assigned to RD. The drag for FPAREA is calculated as follows.

$$D = \frac{1}{2} \rho V^2 (FPAREA)$$

If item 92 is not entered, the user must supply the value for the required drag by using the above formula. There are certain options for which the program ignores or does not iterate on drag. An example of this would be when the program is used to estimate wind-tunnel test results. If these options are desired, see variables 96, TOP, and 110, ALOPT.

### 13. Items 76-77 - Tolerances

XLTOL and XDTOL are the lift and drag tolerances. The program will iterate until both the lift and drag are within the tolerances given by variables 76 and 77. The program has automatic default values of plus and minus 100 pounds for lift and 50 pounds for drag.

### 14. Items 78-79 - Moments

Information regarding the use of FMOM and SMOM can be located in paragraph five on XMASS.

### 15. Items 80-82 - Shaft Axis

The gravitational or weight vector must be oriented to the shaft axis of the rotor system. Figure 9 shows the positions of these angles. The shaft can be oriented in any desired direction. The program will automatically assign the proper values for normal helicopter flight. The default values for AG, BGL, and CG are 0, 90, and 0 degrees, respectively. This orients the shaft in the vertical direction for normal flight. If any other orientation is desired, the user must enter the appropriate values for items 80 to 82.

### 16. Item 83 - Delta 3

Delta three inputs are controlled by variables 83, 115, and 116. These are TD3L, TD3B, and PHD3D, respectively. If the flapping hinge is connected in such a manner as to cause the blade to change pitch due to flapping, this is referred to as a Delta Three hinge. Item 83 is the pitch-flap coupling angle; 115 is the tangent of the Delta Three Bar; and 116 is the phase angle for the Delta Three Bar. The program reduces the pitch angle at a particular azimuth and segment by the quantity TD3 where





Figure 10 Shaft and Control Axis Diagram

$$TD3 = TD3L + TD3B * \sin(PSI + PHD3D)$$

Normally, variables 83, 115, and 116 are zero.

#### 17. Item 84 - Drag Increment

The drag increment is a value of delta CD that is added to the value of CD obtained from the airfoil input data decks. This is added as a roughness factor that naturally occurs on blades that are used on production aircraft. A value of .002 is normally used. The value is not added to the drag calculations for spar data.

#### 18. Items 85-86 - Cyclic Pitch

The lateral and longitudinal cyclic pitch is controlled by four variables. The program allows the user to enter both first and second harmonics of cyclic input. The variables A1S and B1S, 85 and 86, control the first harmonic inputs. The variables A2S and B2S, 104 and 105, control the second harmonic inputs. The A's correspond to the lateral inputs and the B's correspond to the longitudinal inputs. The program has automatic default values for A1S, B1S, A2S and B2S of -1.2, 7.53, 0 and 0 degrees, respectively. The user may enter different values if desired. Unless other options are indicated, the program will keep these cyclic values constant throughout the run and will vary inflow ratio and pitch angle to obtain a final solution. The program will automatically calculate the position of the shaft axis by the momentum theory and will use the value of B1S to determine the position of the control axis. Figure 10 demonstrates this fact.

There is a different option available which allows the program to seek specific values of longitudinal and lateral flapping. This requires the use of variables 100 and 112 - 114. If this option is taken, the values of A1S and B1S are set equal to zero initially and will be changed by the computer in its iteration of the required flapping

angles. The program also has an option to remove hub rolling and pitching moments. Once a solution is obtained that meets the lift and drag tolerances, the values of A1S and B1S are varied to reduce the moments. This option is controlled by variable 160. Normally, runs are made with the user not inputting values for items 85, 86, 104, 105, 100, 112, 113, 114 and 160.

#### 19. Item 87 - Pitch Angle

Variable 87 is the initial value of the collective pitch at the 75 percent radius station at PSI equal zero azimuthal station. The program has a default value of five degrees. This value is used only to initiate the program. The program, under the normal run option, will vary this value in the process of iterating for a convergent solution. There is an option where the pitch angle remains fixed as in a wind-tunnel test. This is the TOP option, variable 96.

#### 20. Item 88 - Inflow Ratio

The variable LAMBDA controls the initial estimate of an uniform inflow. Since the equations of the program are done in a gyrocopter mode, inflow is negative when air flows down through the rotor. This is the normal forward flight mode. The program has a default value of -.02 for LAMBDA. The program will iterate on LAMBDA in its normal iteration routine. The ALOPT, variable 110, option will hold LAMBDA constant.

#### 21. Items 89-90 - MUL

Information regarding the use of MUL and UIN can be found in paragraph one on Flight Velocity.

#### 22. Item 91 - SKIPIN

Information regarding the use of SKIPIN can be found in the section of Case Optional Output Indicators.

23. Item 92 - Linear Twist

Information regarding twist can be found in paragraph four on local twist.

24. Item 93 - XNSEG

Information regarding XNSEG can be found in paragraph three on Delta X.

25. Item 94 - Rate of Climb

The program can be made to calculate a complete solution for any given rate of climb or descent. Climb or descent rate must be entered in units of feet per minute, with positive values for climbs and negative values for descents. The program assumes a uniform down or up flow across the entire rotor surface equal to the rate of climb or descent. This value is added as an incremental correction into the calculations of UP and will effect PHI and angle of attack.

26. Item 95 - FPAREA

Information regarding the use of FPAREA, flat plate area, can be found in paragraph twelve on Required Drag.

27. Item 96 - TOP

The TOP option is one of the wind-tunnel options. If TOP is a non-zero number, the program iterates to obtain the required lift of variable 74, but will ignore the required drag of variable 75. Item 87, the collective pitch at the 75 percent radius at PSI equal zero, will be held constant. Item 88, the inflow ratio, will be varied in the major iteration routine. A non-zero value of TOP will result in a value of -50 for item 122, ATEST. ATEST is the minimum acceptable value for the lift curve slope when option



96 or 110 is executed. If non-zero values for both TOP and ALOPT are entered, the program will do the TOP option. Shaft angle, item 111, must be inputted by the user.

28. Item 97 - PCNV

Information concerning the use of PCNV, the Flapping Solution Re-Use Indicator, can be found in paragraph nine on Initial Flapping Conditions.

29. Item 98 - PRINT

Information concerning the use of PRINT, the program's main output indicator, can be found in the section entitled Case Optional Output Indicators.

30. Item 99 - XEND

Item 99 is the End of Case signal card. It is the last data variable that will be entered for each case. If XEND is a negative number, the program will stop after it determines a solution for that particular case. However, since an infinite number of cases can be entered for each computer run, XEND also tells the program if there are more cases to go. If XEND is equal to 2.0, the program will assume that the next case will begin by reading in new airfoil data. If XEND is any other positive real number, the program assumes that the next case will use the present airfoil data and will enter only case input data and any of the options which normally follow the case input data. Each time that the variable XEND is entered, be especially careful to follow the format for NNUM for this card. NNUM is the number of inputs per data card. NNUM must be a negative number for this XEND card. It is this negative sign on NNUM which actually keys the computer to stop reading data cards for a particular case.

### 31. Item 100 - ABIT

Information regarding the use of ABIT can be found in paragraph 40.

### 32. Items 101-102 - BTOL

In the blade flapping routine, the program searches for a steady state flapping solution for the given conditions of inflow ratio, pitch angle, and cyclic input. The program compares values of flapping angle and velocity at the PSI equal zero azimuthal position on each revolution. If at this position, the difference between the n-th and the (n - 1)th revolution values for flapping angle and velocity is less than BTOL and BPTOL, respectively, the program assumes that it has determined a steady state solution. BTOL and BPTOL have default values of 0.000001 radians and radians per second, respectively. If other values are desired, the user may enter those values for items 101 and 102.

### 33. Item 103 - SPAR

The number of blade segments using spar data can be inputted in item 103. If no spar data are available, no value for SPAR should be entered. For this case, the program assumes that the first segment is the area between the flapping hinge and the point where the actual airfoil begins on the rotor blade. This area is also referred to as the "cut out" segment. In this case, the program assumes that this cut out area produces zero lift and uses CD information from the first airfoil section for drag calculations. If a non-zero number is entered for SPAR, spar airfoil data must be available. Case input variable 120, BSPL, controls the spar input option. If spar data are to be inputted, BSPL should be assigned a non-zero value. In a multiple case run, where spar data are initially entered,

the variable BSPL is set equal to zero as soon as the spar data are entered. If the program did not do this, the user would have to enter a zero for BSPL for the next case if no new spar data are to be entered. If in a multiple case run, the user decides to enter new spar data, the variable BSPL must be assigned a non-zero value for that particular case.

34. Items 104-105 - A2S B2S

Information regarding the use of the second harmonic control inputs can be found in paragraph 18 on Lateral and Longitudinal Cyclic Inputs.

35. Item 106 - Solidity

Information regarding the use of RSL, rotor solidity, can be found in paragraph six on local chord.

36. Item 107 - SYM

SYM is the non-symmetrical airfoil input control. If the user assigns a non-zero value for SYM, the program will assume that all blade airfoil data are non-symmetrical. The user must enter values for CL and CD for the complete range of angles of attack from -180 to +180 degrees. If the value of SYM is zero, only tabular values from zero to +180 degrees need to be entered. The above holds true also for variable 147, SYMSPR. SYMSPR applies to the spar data exactly in the same manner as SYM applies to the airfoil data.

37. Items 108-109 - SFH FDMP

Values for the spring constant, SFH, and damping constant, FDMP, about the flapping hinge can be entered if known. These variables can be entered to simulate a hingeless rotor system or a system with flapping springs.

### 38. Item 110 - ALOPT

This is one of the wind-tunnel options. If ALOPT is a non-zero input, the program will iterate to obtain the lift required of variable 74 but will ignore the required drag, variable 75. In this option, variable 87, collective pitch, will be varied, but not variable 88, inflow ratio, in the program calculations. This is the opposite of the TOP, variable 96, option.

If a lift curve slope less than ATEST, item 122, is calculated while using this option, the program will stop and produce the following message. "Stall Criterion has been violated -- will go to next case, if any." Item 111, the shaft angle, must be inputted. If non-zero values are entered for both TOP and ALOPT, the program will do the TOP Option.

### 39. Item 111 - Shaft Angle

Item 111, the shaft angle, must be inputted whenever the TOP or ALOPT options are used.

### 40. Items 112-114 - RA1S

If variable 100, ABIT, is non-zero, the program will iterate the blade flapping solution in an attempt to obtain the desired lateral and longitudinal flapping angles indicated by variables RA1S and RB1S, respectively. The program will iterate to the accuracy indicated by TOLAB, item 114. Item 112 is RA1S and item 113 is RB1S.

### 41. Items 115-116 - Delta 3

Items 115 and 116 are the tangent and phase angle of a Delta 3 Bar. Information regarding the use of TD3B and PHD3B can be found in paragraph 16 on the Pitch-Flap Coupling Angle.

#### 42. Items 117-118 - LAML

The program allows the user to induce a velocity of any form onto the rotor system. This is done in a harmonic series of the form  $(A0 + A1*\cos(\text{PSI}) + B1*\sin(\text{PSI}) + A2*\cos(2*\text{PSI}) + B2*\sin(2*\text{PSI}) + \dots)$  for each segment that the blade is divided into. If variable 117, LAML, is a non-zero number, the program will enter the harmonics of the induced velocities. During the Read routine, LAML, will be assigned a value of zero. Therefore, for each case where different values for the harmonics are desired, LAML will have to be set to a non-zero number. Variable 118, UVL, controls the use of the induced velocities. If UVL, is zero, the induced velocities will all be set equal to zero.

A short example will now be given on the use of the control variables in a multiple case run. Assume that no harmonic induced velocities are desired for the first case. The user would make no inputs for LAML and UVL. For the second case, assume that harmonic induced velocities are desired. LAML and UVL would be set equal to a non-zero number. The harmonic variables would follow the case input data for this particular case. For the third case, it is desired that the same induced velocities be used. The user would not enter any values for LAML and UVL since (1) LAML has been automatically set to zero and hence no new harmonic data will be entered and (2) UVL is still equal to a non-zero number. It is desired for case four to use no induced velocities. The user now would enter the value of zero for UVL and program will zero out all the induced velocity variables.

This paragraph will describe how to use the variable induced velocity option. The inputs  $A1, B1, A2, B2, \dots$  are numbers in units of feet per second. If the direction of the velocity is down, a negative sign is associated with the A's and B's. A negative sign will decrease the angle of

attack for an element originally at a positive angle of attack. It will increase the amount of negative angle of attack for a blade element originally at a negative angle of attack. The values of A's and B's do not effect the uniform inflow ratio, LAMBDA, that the program iterates upon. The format for using the variable inflow velocity is as follows.

1. A value for NHARM is entered in I3 format. NHARM is the maximum degree of the harmonics that is to be used. If the maximum degree used is  $A3 \cdot \cos(3 \cdot \text{PSI})$ , then NHARM is three. The next three paragraphs are repeated for each blade segment.
2. The value for A0 is entered in E15.6 format. The IBM 360-67 at the NPS will accept F15.0 format.
3. The values for A1, A2, A3, ..., up to NHARM are entered on the next data cards in format 5E14.6.
4. The values for B1, B2, B3, ..., up to NHARM are entered on the next data cards in format 5E14.6.
5. Three cards are required for each blade segment whether or not the values are equal to zero. If the user has 15 blade segments, a minimum of 45 data cards are required.

43. Item 120 - BSPL

Information concerning the use of BSPL can be found in paragraph 33 entitled Number of Spar Airfoil Data Segments.

44. Item 121 - PPSI

PPSI represents a delta PSI for printout purposes. PPSI has a default value equal to DPSI, variable 68. PPSI shall never be a smaller increment than the incremental DPSI used to calculate the solution.

45. Item 122 - ATEST

ATEST is the minimum acceptable value of the lift curve slope when option TOP or ALOPT is used. If no value is assigned, ATEST has a default value of 5 (1/rad). When the TOP option is used it has a automatic value of -50 (1/rad). The lift curve refers to the increase in rotor lift with the tilting back of the tip path plane. A check on it for a minimum is for convergence purpose only.

46. Item 123 - IGC

IGC is the Iteration Gain Control factor. If the major iteration fails to converge, choosing a fractional value for IGC can greatly speed convergence. This may be especially helpful when parts of the rotor are in stall. The amounts by which the convergence algorithm changes the independent variables is multiplied by IGC. Setting item 91, SKIPIN, equal to zero may help the user decide if this IGC option might be useful.

47. Item 126 - PCR

The pre-coning angle in radians may be entered here.

48. Item 138 - INPL

Input 1.0 for INPL in order to remove hub moment inplane aerodynamic forces from the calculation of aerodynamic pitch and roll moments about the shaft axis.

49. Items 139-141 - PSIS

Variables PSIS, PHIS and THFS represent aircraft angular velocities. The aircraft can be given any angular velocity in yaw (PSIS), pitch (PHIS), and roll (THFS) in radians per second by the use of these variables. They effect the calculations of UP, UT and UR. Paragraph 50 contains additional information.

50. Items 142-145 - CG

If the angular velocities, items 139 - 141 are entered, they are used in the calculations of UP, UT and UR. If no values for items 142 - 145 are entered, the program assumes that the rotor system rotates due to the angular velocities about the center of the shaft. If values are entered for items 142 - 145, the calculations will assume that the entire rotor shaft is rotating about the center of gravity. Variables 142 - 145 are PSCG, PSMK, WLCG and WLMF. PSCG is the longitudinal CG position while PSMK is the longitudinal position of the main rotor. WLCG is the CG waterline station while WLMF is the main rotor's waterline, or vertical position. All of these values must be entered in units of inches.

51. Item 146 - VELV

The aircraft's lateral speed in knots can be entered here.

52. Item 147 - SYM3PR

If the spar data are symmetrical, do not enter a value for SYM3PR. The program will only use values for CL and CD between zero to +180 degrees. If the spar data are non-symmetrical, enter any non-zero value for SYM3PR. The program will require values from -180 to +180 degrees.



53. Items 156-157 - HIALFA

In order for the program to properly calculate the region in and around the reverse flow region, the values of CL and CD are required to be known at high and low angles of attacks approaching 180 degrees. However, in order to save the user from having to enter a whole range of angles of attack for all Mach numbers, the program has an option where for angles above HIALFA, 156, and below LOALFA, 157, the Mach number is set equal to zero for table lookup purposes. The user is only required to enter large angles for the first two Mach number tables. HIALFA and LOALFA have default values of +30 and -30 degrees, respectively.

54. Items 158-159 - Tip Sweep


The GRP program will properly calculate the airflow sweep angle, UT, UR, and pitch angle of a swept tip airfoil. TIPSWP is the amount of sweep of the tip measured in degrees. TPSWST is the blade segment number at which the sweep begins. The program assumes that the remaining outboard segments starting with TPSWST are swept the number of degrees indicated by TIPSWP. UT and UR are modified for these segments as shown in Figure 11.

55. Item 160 - TRIM

If TRIM is a non-zero value, the program will attempt to adjust A1S and B1S in order to reduce the rolling and pitching moments to less than plus or minus 100 pounds. It will first obtain a solution which will satisfy the required lift and drag, then it will adjust A1S and B1S to reduce the moments.

56. Items 161-175 - RB

Variables 161 - 175 assign the proper airfoil data to blade segments one through fifteen. The program will



$$UR = UR \cos \lambda_t + UT \sin \lambda_t$$

$$UT = UT \cos \lambda_t - UR \sin \lambda_t$$

Figure 11. Tip Sweep Calculation Diagram

accept up to five airfoil data decks. The RB array is initialized with the value of one for all 15 segments. If only one blade airfoil deck is used, there is no need to enter any values for RB. Only enter values for the segments which will use airfoil data sets two through five. If no spar data are entered, SPAR equals zero, segment number one is considered the cut out segment and is assigned the value of RB(1) equals one for calculation purposes and the value of RB(1) equals zero for printout identification. In this case, segment one produces only drag but no lift. If SPAR is greater than zero, RB(I), I = 1, SPAR, will be assigned the value of zero for printout identification. These segments will use the spar data entered and will calculate both lift and drag.

#### I. CASE INPUT FORMAT

Below is located the format that is used to input case data to the program. All input data cards are of the format (I2, I4, 5F12.0). The input cards contain seven fields which are called NNUM, NLOC, C(1), C(2), C(3), C(4) and C(5). An example of a data input card is as follow.

```
5  1  700.    26.8    1148.6    .002246    4.0
```

1. NNUM is the number of inputs on this card, where C(N) are the inputs. NNUM must appear in either column one or two. NNUM has a minimum of one and a maximum of five. In the above example NNUM is five.
2. NLOC is the item or variable number of input C(1). This refers to the item numbers that are found in the section on Case Input Listing. NLOC is in I4 format and must be right justified in columns four through six. In the example NLOC refers to item number one, the Rotor Tip Speed.

3. C(1) through C(5) are the values corresponding to the input items NLOC through NLOC + NNUM. Each value must contain a decimal point and be in columns 7 - 18 for C(1), 19 - 30 for C(2), 31 - 42 for C(3), 43 - 54 for C(4) and 55 - 66 for C(5). In this example, values are entered for variables one through five, the Tip Speed, Radius, Speed of Sound, Air Density and Number of Blades.
4. Omission of NNUM will cause program termination with an error explanation statement. NNUM greater than five will cause unknown problems. Omission of NLOC will cause the present card's values of C(N) to be entered into the items indicated by the previous card's NLOC. Failure to right justify NLOC, or NLOC greater than 200, will cause unknown problems. Failure to properly locate correctly any input value within its own field on the card will cause errors in both that input and the number whose field it encroaches on.

#### J. CASE OPTIONAL OUTPUT INDICATORS

The program has two variables that control the output printout, variable 91, SKIPIN, and 98, PRINT. The program will automatically produce a printout of the case input data for each case and a one-page summary of the initial conditions and iteration limitations the user placed upon the program. It will also produce a one-page summary of the resulting forces, moments and calculated rotor horsepower for the final converged solution. The user can also receive an echo printout of the airfoil and spar data decks. If this echo printout is desired, the user will find the correct printout indicators described in sections C and D

entitled Blade and Spar Data Deck Requirements.

The main optional printout variable is variable 98, PRINT. PRINT can be a number from 1 to 1,111,111 depending upon the option desired. If no value is enter for PRINT, the user will receive the printout described above. Below, is listed the PRINT Options. If, for example, PRINT is assigned a value of 111, the user will receive printout options 1, 10 and 100.

#### OPTIONAL OUTPUT INDICATORS

Option 1	Angle of attack, Mach number, section lift and drag coefficients, inflow angle, lift, and sweep angle at each azimuthal position for each radial blade segment. Only for converged flapping solution.
Option 10	Converged flapping angle, rate, and acceleration at each azimuthal position.
Option 100	Converged integrated forces on blade at each azimuthal station.
Option 1000	Harmonic analysis of blade forces for converged case.
Option 10000	Harmonic analysis of air loads for converged case.

#### DEBUGGING OR TRANSIENT OPTIONS

Option 100000	Transient flapping angle, rate, and acceleration at each azimuthal station.
Option 1000000	Option 100000 plus blade velocities, angles, Mach number, section coefficients, and lift for each blade segment at each azimuthal station.

The user is cautioned that the debugging options can give a huge amount of output data.

The second printout option is the variable SKIPIN, number 91. This variable controls the summary force, moment and horsepower output discussed in the first paragraph. If SKIPIN is greater than zero, this summary will be printed only for the final converged solution. If SKIPIN is equal to zero or a negative number, this summary will be printed for each loop through the major iteration (force summation) routine. SKIPIN has a default value of one. If the program is not converging to a solution, the user can see immediately, with very little extra printout, exactly what intermediate solutions the program is producing by setting SKIPIN equal to zero. This may help the user in deciding whether or not to use the Iteration Gain Factor, IGC, variable 123.

#### K. IBM 360 EXECUTION CONTROL CARDS

This section illustrates the control cards required to execute the GRP program using the IBM 360 at the Naval Postgraduate School. The program may be run under OS or CP/CMS. There are two ways of running the program under OS. The first is to run the entire program and data through the computer at the same time. The second way is to store the main program on a disk as a library program and enter only the data through the card reader for each desired case. The second method has the two advantages of (1) not requiring the user to enter the entire 1100 card main program through the card reader for each run and (2) the amount of CPU time required can be reduced since the main program does not have to be recompiled for each run. The program requires approximately one minute and forty seconds of CPU time to compile. The normal run time for each case is approximately

20 CPU seconds. This can vary with the amount of printout data requested. If the program is compiled on the CP/CMS, the user will have to request 344K bytes core size on the login message. The standard 256K bytes core size is not large enough for compiling. However, once the program has been compiled, it can be executed within the 256K normally available.

The following cards are required to execute the entire program through the card reader at one time.

Standard Job Card

// EXEC FORTCLG,REGION.FORT=150K

// REGION.GO=180K

//PORT.SYSIN DD \*

Main GRP Program

/\*

//GO.SYSIN DD \*

Case Input Data

/\*

The following two programs are used to reserve space and load the program onto a disk.

Standard Job Card

// EXEC IGM=IEFBR14

//LOAD DD DSN=S1395.HELO,UNIT=3330,VOL=SER=DISK01

// DISP=(NEW,KEEP),LABEL=RETPD=150,SPACE=(CYL,(1,1,1))

/\*

Standard Job Card

// EXEC FORTCL,REGION.FORT=180K

//PORT.SYSIN DD \*

Main GRP Program

/\*

// LINK.SYSLMOD DD UNIT=3330,VOL=SER=DISK01,

// DSN=S1395.HELO (GRP),DISP=SHR

The S1395 used above and below must be change to S for student or F for faculty with the appropriate user number instead of 1395. The following cards must be used to

execute the program once stored on a disk.

Standard Job Card

//GO EXEC PGM=GRP,REGION=160K

//STEPLIB DD UNIT=3330,VOL=SER=DISK01,DISP=SHR,

// DSN=S1395.HELO

//FT06F001 DD SYSOUT=A,DCB=(RECFM=FBA,LRECL=133,BLKSIZE=3325

//FT05F001 DD \*

Case Input Data

/\*

#### J. Sample Program Output

This section describes in detail the output available from the GRP program. In addition, a sample computer output is included with each description. The program will print up to ten different tables. Seven of these tables are optional and are not automatically printed. The ten tables are as follows.

1. Echo Printout of Rotor Blade and Spar Data
2. Case Input Data Card Listings
3. Summary of Input Data
4. Debugging or Transient Information (Options 100,000 and 1,000,000)
5. Summary of Forces, Moments and Horsepower
6. Converged Flapping Solution (Option 10)
7. Converged Integrated Forces (Option 100)
8. Harmonic Analysis of Z Force (Option 1000)
9. Converged Blade Analysis (option 1)
10. Harmonic Analysis of Air Loads (Option 10,000)

The input variable PRINT, item 98, controls the output of items four and six through ten. Items two, three and five are always outputted. Item one is controlled by the first data card on the rotor blade and spar section input decks.



# 1. Echo Rotor Blade Printout

The next page contains a partial sample Echo Printout of Rotor Blade Input Data. This printout illustrates that (1) the printout was requested (WBLADE = 10.), (2) there are two airfoil decks to be entered, (3) there are nine Mach numbers for which CL's are to be read in and (4) the remaining portion of the printout is the values of Mach numbers, angles of attack and lift coefficients for the first airfoil deck.

[illegible]

## 2. Input Data Card Listing

The next page contains a sample Case Input Data Card Listing. This is one of the automatic printouts. It is an echo printout of the input data cards

1. The first step in the process is to identify the problem or issue that needs to be addressed. This involves gathering information and understanding the context of the problem.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
84

[illegible]

1148-659828125  
C-6573599754  
O-659999927  
C-662001300  
5-660000000  
-1-655995237  
1-659974055  
1-7125553435  
1-7609992218  
1-7229995712  
2-0000000700

[illegible][illegible]

### 3. Summary of Input Data

The next page contains the automatic Summary of Input Data printout. The following information can be seen on this sample output.

a. The blade was divided into 15 segments starting from the hinge offset and proceeding outward.

b. No values were entered for the local mass density, input variables 38 - 52. Instead, values for the First Moment,  $M(M) = 85$ , and the Second Moment,  $MON - INERTIA = 1450$ , about the Flapping Hinge, input items 78 and 79, were entered.

c. The X row indicates the calculated centers of each segment expressed in a percentage of the distance out the rotor blade.

d. The BLADE DECK row indicates that the first blade segment was considered a Spar segment. Segments two through five and twelve through fifteen belong to airfoil data deck number one, while segments six through eleven belong to airfoil data deck number two.

e. The rest of the information, with one exception, is a summary of the case input data. The exception is the term THRUST FACTOR. This is the value used to nondimensionalize all the calculated forces in the program. The THRUST FACTOR equals  $\rho \pi R^2 (\Omega R)^2$ . Moments are nondimensionalized by the THRUST FACTOR times the radius.

f. The program checks to see if all the blade segment lengths, delta X's, plus the distance from the shaft to the hinge offset, E/R, add up to one. If, on the printout,  $SUM(DX) + E/R$  does not equal one, the user has made a mistake somewhere with the delta X's or in the E/R number.

# DATA AIR SYSTEMS COMPANY AIRFLOW ESTIMATION UNIT: 1000 CUBIC FEET PER SECOND (CFM)

STATION		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
WALL SURFACE		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
CEILING		0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074	0.0074
FLOOR		0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093	0.0093
WALL SURFACE		1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
WALL SURFACE		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
WALL SURFACE		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
WALL SURFACE		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
WALL SURFACE		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
WALL SURFACE		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

WALL SURFACE

#### 4. Debugging or Transient Information

The next page illustrates the Debugging or Transient Printout. This is PRINT Option 1,000,000. The information available includes flapping angles, rates and accelerations at each azimuthal position with a radial position display of UP, UT, U, PHI, Angle-of-Attack, Mach Number, CL, CD and Lift Per Inch produced.

This option is generally outputted only when the user is experiencing unknown difficulties with the GRP program. The program will output all of the above information for every revolution and iteration until a converged solution is obtained or the program runs out of allowable computer time. If desired, the variable SKIPIN, item 91, will provide a printout of the Forces, Moments and Horsepower Summary after each major iteration.

PSI = 15 DEGREES REV 1 PETA = 0.00000129 BETA\* = 0.00000122 BETA\*\* = 0.07691514

UP	UT	U	PHI	ALPHA	MACH NC	CL	CC	LC-CL(R/IN)
-0.0200004	0.2497559	0.3745892	-3.0574017	2.4446865	0.2352067	0.0	0.0	0.0
-0.0200008	0.3997558	0.4876213	-2.34942234	3.9032383	0.2306075	0.0	0.0	0.0
-0.0200010	0.5497558	0.6166213	-1.8581762	3.3629398	0.2306075	0.0	0.0	0.0
-0.0200011	0.6747557	0.7204330	-1.5690880	3.42727545	0.2306075	0.0	0.0	0.0
-0.0200012	0.7747557	0.8237011	-1.3913908	2.7472160	0.2306075	0.0	0.0	0.0
-0.0200013	0.8497556	0.9180687	-1.2479219	2.3826094	0.2306075	0.0	0.0	0.0
-0.0200014	0.9497556	1.0391460	-1.15039524	1.32225781	0.2306075	0.0	0.0	0.0
-0.0200014	1.0397556	1.0971460	-1.0691549	1.6028921	0.2306075	0.0	0.0	0.0
-0.0200014	1.0597553	1.0971460	-1.0691549	1.6028921	0.2306075	0.0	0.0	0.0

PSI = 30 DEGREES REV 1 PETA = 0.00262245 BETA\* = 0.01950843 BETA\*\* = -0.01054304

UP	UT	U	PHI	ALPHA	MACH NC	CL	CC	LC-CL(R/IN)
-0.0221490	0.3194170	0.4062405	-3.1246576	2.2959646	0.23543730	0.0	0.0	0.0
-0.0221490	0.4694165	0.5324405	-2.7053546	2.2959646	0.23543730	0.0	0.0	0.0
-0.0221490	0.6194155	0.6855201	-2.4104948	1.7392778	0.23543730	0.0	0.0	0.0
-0.0221490	0.7444151	0.7855201	-2.2412097	1.06152472	0.23543730	0.0	0.0	0.0
-0.0221490	0.8444147	0.8855201	-2.1195560	0.4442472	0.23543730	0.0	0.0	0.0
-0.0221490	0.9444143	0.9855201	-2.0277910	-0.2160130	0.23543730	0.0	0.0	0.0
-0.0221490	1.0444140	1.0855201	-1.9689112	-0.73513329	0.23543730	0.0	0.0	0.0
-0.0221490	1.1044140	1.1355201	-1.9333792	-1.09424280	0.23543730	0.0	0.0	0.0
-0.0221490	1.1294136	1.1574259	-1.8950567	-1.3311462	0.23543730	0.0	0.0	0.0

PSI = 45 DEGREES REV 1 PETA = 0.00740225 BETA\* = 0.01039780 BETA\*\* = -0.08475673

UP	UT	U	PHI	ALPHA	MACH NC	CL	CC	LC-CL(R/IN)
-0.0227411	0.3792349	0.4314013	-3.0217161	1.4916553	0.2705422	0.0	0.0	0.0
-0.0227411	0.5292306	0.5676830	-2.5434405	1.1178379	0.2705422	0.0	0.0	0.0
-0.0227411	0.6792306	0.7059513	-2.2331573	0.71754587	0.2705422	0.0	0.0	0.0
-0.0227411	0.8292306	0.8322306	-1.9506869	0.37946406	0.2705422	0.0	0.0	0.0
-0.0227411	0.9792306	0.9522306	-1.6437622	-0.13222005	0.2705422	0.0	0.0	0.0
-0.0227411	1.1292306	1.0985206	-1.3434205	-0.72108971	0.2705422	0.0	0.0	0.0
-0.0227411	1.1642311	1.1182311	-1.17845185	-2.6108971	0.2705422	0.0	0.0	0.0
-0.0227411	1.1842311	1.1202311	-1.17257614	-3.1643351	0.2705422	0.0	0.0	0.0



## 5. Forces Summary

The next printout illustrates the Summary of Forces, Moments and Horsepower. This page is automatically outputted for the converged solution. A printout of this summary can be obtained for each loop through the major iteration routine by the use of the input variable SKIPIN, item 91. The following information can be observed from this sample printout.

a. The cyclic lateral and longitudinal inputs, A1S, B1S, A2S and B2S are printed at the top of the page. This example indicates that there were no second harmonic inputs for A2S and B2S, which is normal.

b. THETA .75 is the pitch angle of the blade at the 75 percent radius station at the PSI equals zero azimuthal position. In most options the program will iterate upon the values for THETA .75 in its search for a converged solution.

c. LAMBDA refers to the converged value for the uniform inflow ratio. If a rate of climb or descent was used in the case, that rate divided by the tip speed would have to be subtracted from or added to this value of LAMBDA, respectively.

d. MU(X)S and MU(Y)S are the advance ratios in the longitudinal and lateral directions with respect to the shaft axis.

e. CT, CQ, CH, CL and CD are the calculated overall coefficients of Thrust, Torque, H Force, Lift and Drag. All of these items are nondimensionalized by the value of the Thrust Factor.

f. Lift and Drag forces are calculated with respect to the relative wind axis. Thrust and H forces are calculated with respect to the control axis. Z forces are calculated with respect to the shaft axis. X and Y forces are calculated perpendicular to the shaft axis.

g. The Equivalent Drag is the total drag force created by the fuselage, flat plate area times dynamic

pressure, plus the profile drag created by the turning rotor system.

h. The Equivalent P. A., or Equivalent Flat Plate area is obtained by dividing the Equivalent Drag by the dynamic pressure.

i. Alpha(S) is the shaft axis orientation while Alpha(C) is the control axis orientation. The program uses momentum theory to calculate Alpha(S). Alpha(C) is determined from the following relationship,  $\text{Alpha}(S) = \text{Alpha}(C) + \text{DIS}$ .

j. LAT. DIS. and LONG. DIS. are the lift vector offset as a percentage of the rotor radius from the rotor shaft to create the program's rolling and pitching moments.

k. PM and RM are the calculated aerodynamic pitch and roll moments about the shaft axis. The SHEARS Hub Pitch and Roll Moments are calculated from summing the aerodynamic, inertia and elastic hub restraint moments.

A12 -1.20 H12 7.54 A22 0.0 R22 0.0 T1-FTA 275- 8.56 LAMPOL(S) -0.016 PL(V)S 0.0 PL(V)S 0.0  
 CL/SIGMA = 7.806275E-03 CL/SIGMA = 7.806275E-03 CL/SIGMA = 7.806275E-03  
 CC = 3.612313E-04 CC = 3.612313E-04 CC = 3.612313E-04  
 LIFT = 20824.746 POUNDS X FORCE = 1764.641 POUNDS RESULTANT = 20830.715 POUNDS  
 ERAC = -413.158 POUNDS Y FORCE = -275.744 POUNDS ROLL MOM = -2855.685 FT-POUNDS  
 FORCESENDER = 1265.181 POUNDS Z FORCE = -20753.541 POUNDS FITCH MOM = -10650.244 FT-POUNDS  
 ECLIV ERAC = 4482.754 POUNDS EQUIV L/D = 3.212 TRUST = 20807.523 POUNDS ECLIV F.A. = 562.175 SC. FEET  
 ALPHA(S) = 1.123 DEGREES F FORCE = 970.041 POUNDS TORSION = 25846.514 FT-POUNDS  
 REFRACT = -3.807 DEGREES VI ACTUAL = 60.000 KNOTS PROFILE HP = 434.670  
 NAT. DIS. = -0.512 PERCENT SHEARS FOR PITCH MOMENT = -1468.50 FT-LES  
 SHEARS HUE ROLL MOMENT = -1524.55 FT-LES  
 MAJOR ITERATIONS USED = 4  
 \*\*\*\*\*

## 6. Flapping Solution

The next page contains a sample printout of the converged flapping solution. The first items to appear are the flapping values at the PSI equal zero azimuthal position for each revolution prior to the converged revolution on the final iteration. The values for flapping angle and its first two derivatives are expressed in radians.

The second part of this printout is the actual flapping values for the converged revolution. The difference between the flapping angles and rates between the PSI equal zero and 360 degree position must be less than the tolerances entered in variables 101 and 102. The numbers here are also in radians. The last item is a Fourier coefficient series for the flapping angle and it is calculated in degrees. All calculations are done in respects to the shaft axis. This is PRINT Option 10.



## 7. Force Integration

The next table is a sample Force Integration Output. This is PRINT Option 100. The forces are a printout for one blade only at a particular azimuthal position. CQ, CQL and CQD are the Coefficients of Torque, Torque due to Lift and Torque due to Drag. CQ is calculated from  $CQ = CQD - CQL$ . CX, CY and CZ are all related to forces in the shaft axis reference system. CMHS is the Coefficient of Pitching Moment due to aerodynamic, inertia and hub elastic restraint moments about the Shaft Axis and CLHS is the Coefficient of Rolling Moment due to these same forces. In the printout the (B) character is the number of blades, which in this example is four. SIG is the solidity of the rotor system.  $MAX B * CQD / SIGMA$  is a blade stall indicator. It is calculated by determining the first azimuthal station between the PSI equal 180 degree and 360 degree position that has a value of CQD greater than the value of CQD at the PSI equal 180 degrees azimuthal position.



#### 8. Harmonic Analysis of Z Force

The following is a harmonic analysis of the forces in the Z or shaft axis direction. Z force is positive in the downward direction. This is PRINT Option 1000.



HARMONIC ANALYSIS OF DIMENSIONAL CZ  
CZ = A0+A1\*COS(PSI)+B1\*SIN(PSI)+A2\*COS(2\*PSI)+B2\*SIN(2\*PSI) .....

A0	A1	A2	A3	A4	A5	A6
-4.7E 02	-2.3E 02	-2.4E 02	-1.7E 01	8.8E 00	-1.1E 00	3.0E 00
	B1	B2	B3	B4	B5	B6
	-3.8E 02	-5.7E 00	-4.1E 01	-2.7E 00	-3.5E-01	6.5E 00

## 9. Converged Blade Analysis

The next four pages contain the sample overall summary of events occurring on the blade at each azimuthal and radial position. This is PRINT Option 1. Variable 121, PPSI, controls the azimuthal intervals that are printed out. The output items are as follows.

- a. X - Center location of the blade segment
- b. ALPHA - Angle-of-Attack
- c. MACH - Local Mach number
- d. CL - Local Coefficient of Lift
- e. CD - Local Coefficient of Drag
- f. PHI - Local Inflow Angle
- g. L(LB/IN) - Lift produced per inch on segment
- h. Sweep - Sweep Angle of airflow









#### 10. Harmonic of Air Loads

The next printout contains the harmonic analysis of the lift generated per inch on each rotor blade segment. This is PRINT Option 10000. The airloads are computed in two harmonic forms, both containing terms out to and including the tenth harmonic. The forms are

$$\begin{aligned} \text{Lift per Inch} = & A_0 - A_1 \cos \psi - B_1 \sin \psi - A_2 \cos 2\psi - \\ & B_2 \sin 2\psi - A_3 \cos 3\psi - B_3 \sin 3\psi \dots - A_{10} \cos 10\psi - \\ & B_{10} \sin 10\psi \text{ and} \end{aligned}$$

$$\begin{aligned} \text{Lift per Inch} = & A_0 - C_1 \sin(\psi + \phi_1) - C_2 \sin(2\psi + \phi_2) \\ & - C_3 \sin(3\psi + \phi_3) \dots - C_{10} \sin(10\psi + \phi_{10}). \end{aligned}$$

The Ratio column is determined from the coefficients in Column C. From this ratio, one can immediately determine which airload harmonic is dominant and the relative relationship of this to the other harmonic coefficients.

# HARMONICS OF AIR LOADS

STATION 1 A0 = -0.0185388

A	B	C	PHI	RATIO
0.0058114	-0.0290987	0.0296733	168.7057648	1.0000000
-0.0201269	-0.0076506	0.0215319	249.1871948	0.7256326
-0.0075798	0.0102900	0.0127804	-36.3760834	0.4307035
0.0019173	0.0048735	0.0052371	21.4752045	0.1764905
0.0016457	0.0019163	0.0025260	40.6547089	0.0851264
0.0018161	0.0006374	0.0019247	70.6604767	0.0648645
0.0013799	0.0001234	0.0013854	84.8918610	0.0466900
0.0016308	0.0009104	0.0018677	119.1726837	0.0629405
-0.0000526	-0.0014860	0.0014869	182.0275879	0.0501094
-0.0000777	-0.0004794	0.0004857	170.7967834	0.0163678

STATION 2 A0 = 2.1065311

A	B	C	PHI	RATIO
0.4665607	-2.8272552	2.8549228	170.6293030	1.0000000
0.3842223	-0.1021613	0.3575722	75.1100006	0.1387448
0.0412583	-0.1719376	0.1768185	166.5062866	0.0617061
-0.0518297	-0.0356730	0.0629196	235.4613037	0.0219577
-0.0133265	-0.0124577	0.0182426	-46.9297943	0.0063663
-0.0067163	-0.0013983	0.0068603	258.2390137	0.0023941
-0.0137545	0.0124043	0.0185217	-47.9545898	0.0064637
0.0100667	0.0237044	0.0257534	23.0097351	0.0089874
0.0264677	-0.0022998	0.0265674	94.9660645	0.0092715
0.0064641	-0.00225474	0.0234557	164.0029297	0.0081856

STATION 3 A0 = 6.1160278

A	B	C	PHI	RATIO
0.6907077	-5.7561398	5.7974300	173.1574097	1.0000000
0.1150140	-0.1354709	0.1777093	40.3310547	0.0306531
-0.0053393	-0.1083109	0.1084424	182.8220673	0.0187053
-0.0165641	-0.0159713	0.0230098	226.0436707	0.0039690
-0.0029133	0.0028978	0.0041091	-45.1523743	0.0007088
0.0013191	0.0009068	0.0016007	55.4948120	0.0002761
0.0012444	-0.0003366	0.0012450	91.6824951	0.0002147
0.0000843	-0.0003298	0.0012450	165.6586761	0.0005877
-0.0000005	-0.0001539	0.0001539	-0.1882620	0.0000265
-0.0000840	-0.0002034	0.0002201	157.5609741	0.0000380



STATION 4 A0 = 10.8414097

A	B	C	PHI	RATIO
0.6164446	-6.7262754	6.754622	174.7635345	1.0000000
-0.2930883	0.1327320	0.3217429	-65.6354218	0.0476341
-0.0419007	-0.0340860	0.0540141	230.8716888	0.0079968
-0.0247872	-0.0128548	0.0279222	242.5882416	0.0041339
-0.0008707	-0.0201105	0.0201293	182.4791412	0.0029802
0.0141912	0.0010902	0.0142330	85.6067963	0.0021072
0.0009653	0.0089413	0.0089933	-6.1615915	0.0013315
-0.0037353	-0.0011640	0.0039125	252.6913452	0.0005792
-0.0008729	0.0002412	0.0009056	74.5502472	0.0001341
-0.0035800	0.0006888	0.0036457	-79.1098633	0.0005397

STATION 5 A0 = 16.1947784

A	B	C	PHI	RATIO
0.3626862	-7.1265459	7.1357670	177.0865173	1.0000000
-0.3114024	0.1944090	0.3671053	-58.02333765	0.0514458
-0.1032558	-0.0126060	0.1040224	263.0393066	0.0145776
0.0755618	-0.0150281	0.0770417	101.2484741	0.0107966
-0.0024715	0.0103472	0.0106383	-13.4337721	0.0044908
-0.0319176	0.0000382	0.0319176	89.9314423	0.0047299
-0.0014862	0.0059217	0.0061053	-14.0892754	0.0008556
0.0184920	0.0004020	0.0184964	88.7545776	0.0025921
-0.0018298	0.0026334	0.0032068	-34.7934418	0.0004494
-0.0134738	0.0001376	0.0134745	89.4146423	0.0018883

STATION 6 A0 = 23.7709961

A	B	C	PHI	RATIO
0.0274429	-7.6236906	7.6237392	179.7936707	1.0000000
-0.9006391	0.2562434	0.9363821	-74.1181946	0.1228245
-0.1355020	-0.1138743	0.1769975	229.9566040	0.0232166
0.0095282	-0.0167787	0.0192953	150.4087830	0.0025310
0.0000880	-0.0094386	0.0094390	179.4659424	0.0012381
-0.0118955	-0.0018567	0.0120395	261.1286621	0.0015792
-0.0002423	0.0052868	0.0052924	-2.6245661	0.0006942
-0.0065136	-0.0006836	0.0065494	264.0087891	0.0008591
-0.0002131	0.0050558	0.0050603	-2.4134903	0.0006638
0.0033125	-0.0002771	0.0033241	94.7816010	0.0004360

STATION 7 A0 = 26.5055695

A	B	C	PHI	RATIO
-0.3485193	-6.2393513	6.2490759	183.1970215	1.0000000
-1.3400717	-0.3121706	1.3759508	-76.8867188	0.2201847
-0.1670687	-0.1379979	0.2166919	230.4433341	0.0346758
-0.059609	-0.0201869	0.0210486	196.4511414	0.0033683
0.0012575	-0.0021948	0.0025295	150.1383545	0.0004048
0.0116361	-0.0005068	0.0116471	92.4938660	0.0018638
0.0024073	-0.0083405	0.0086809	163.9004822	0.0013891
0.0011396	-0.0004327	0.0012190	110.7918243	0.001951
0.0003120	-0.0029015	0.0029182	173.8625031	0.0004670
0.0004716	-0.0002716	0.0005442	119.93330750	0.0000871

STATION 8 A0 = 29.9147339

A	B	C	PHI	RATIO
-0.8066483	-4.7207584	4.7861788	189.6965790	1.0000000
-1.7467089	-0.3762742	1.7867775	-77.8431091	0.3730864
-0.1978083	-0.1310782	0.2372965	236.4693298	0.0495485
-0.0017244	-0.0276652	0.0277189	183.5665131	0.0057878
0.0084314	-0.0052728	0.0099443	122.0210419	0.0020764
0.0046946	-0.0064113	0.0079463	143.76.5897369	0.0016592
0.0059827	-0.0014264	0.0061504	176.1567535	0.0012842
0.0056898	-0.0016484	0.0059238	106.1567535	0.0012369
0.0054092	-0.0008308	0.0054726	81.2680969	0.0011427
0.0069205	-0.0011486	0.0070152	99.42233398	0.0014648

STATION 9 A0 = 28.9830322

A	B	C	PHI	RATIO
-1.4361496	-1.2663260	1.9147072	228.5956421	0.9784915
-1.9012938	-0.4627401	1.9567947	-73.3211823	1.0000000
-0.2739782	-0.0837021	0.2864787	276.0117035	0.1464020
-0.0536059	-0.0473846	0.0715464	228.5250549	0.0365631
-0.0036424	-0.0342192	0.0344125	-6.0758619	0.0175861
-0.0486374	-0.0091883	0.0494977	259.3017578	0.0252953
-0.0084202	-0.0269197	0.0282058	162.6307220	0.0144143
-0.0112917	-0.0050772	0.0123806	-65.7893524	0.0063270
0.00422988	-0.00254356	0.0257963	170.4072418	0.0131829
0.0137325	-0.0077968	0.0157915	60.4138336	0.0080701

STATION 10 A0 = 34.9860229

A	B	C	PHI	RATIO
-2.2796831	0.2039624	2.2887888	-84.8873291	1.0000000
-2.1698074	0.5970355	2.2504482	-74.513717	0.9832485
-0.3524024	-0.1595188	0.3868251	245.6454926	0.1690086
-0.1728295	-0.0118687	0.1732365	93.9284821	0.0756891
-0.0039592	0.0551648	0.0553067	-4.1050692	0.0241642
0.0780106	0.0224963	0.0811895	73.9137268	0.0354727
0.0065553	0.0280451	0.0288010	13.1561584	0.0125835
0.0357608	0.0012623	0.0357831	87.9783478	0.0156341
-0.0105172	0.0080913	0.0132695	-52.4273529	0.0057976
-0.0129197	-0.0011896	0.0129743	-95.2609558	0.0056686

STATION 11 A0 = 40.3416443

A	B	C	PHI	RATIO
-3.0961714	1.2363281	3.338842	-68.2327118	1.0000000
-2.6404209	0.6432902	2.7176542	-76.3076324	0.8151615
-0.4049954	-0.0475855	0.6036174	222.1401367	0.1810552
0.0306133	-0.0461915	0.0554150	146.4656372	0.0166217
0.1252972	-0.0215824	0.2495590	149.8625793	0.0748553
0.1024029	-0.0225431	0.1055135	103.9468384	0.0316488
0.0641405	-0.0390110	0.0750723	121.3084564	0.0225180
0.0103156	-0.0392041	0.0405385	165.2580566	0.0121595
0.0371099	-0.0429722	0.0567782	139.1867218	0.0170306
-0.0055227	-0.0281254	0.0286625	191.1092834	0.0085973

STATION 12 A0 = 15.1531467

A	B	C	PHI	RATIO
-4.2959366	13.1468153	13.8309002	-18.0956421	1.0000000
-3.9540501	0.7513018	4.0247927	-79.2415466	0.2910000
-0.3706588	-0.0547183	0.6609067	214.1134033	0.0477848
-0.0164340	-0.0444608	0.0474008	200.2836151	0.0034272
-0.0054827	0.0113497	0.0126046	-25.7836758	0.0009113
0.0297508	0.0097892	0.0313200	71.1093483	0.0022645
0.0016600	0.0133093	0.0134125	7.1093483	0.0009697
0.0240062	0.0060478	0.0247563	75.0598328	0.0017899
-0.0023791	-0.0078063	0.0081608	163.0503693	0.0005900
-0.0015144	-0.0044872	0.0047358	198.6434751	0.0003424

STATION 13 A0 = 14.6387329

A	B	C	PHI	RATIO
-3.0683117	12.3609266	12.7360525	-13.9405718	1.0000000
-3.6057901	-0.7387867	3.6806965	258.42208984	0.2889982
-0.1978170	-0.3508309	0.4027578	209.4165344	0.0316234
-0.0111755	-0.0467688	0.0475021	193.6071014	0.0037297
0.0133389	-0.0326380	0.0352586	157.7704163	0.0027684
-0.0020485	-0.0065694	0.0068813	197.3187408	0.0005403
0.0107518	-0.0086541	0.0138020	128.8303528	0.0010837
-0.0046484	-0.0016559	0.0049345	250.3928070	0.0003874
-0.0063981	-0.00050375	0.0081432	128.2147675	0.0006394
-0.0042478	-0.0011064	0.0043895	255.4011841	0.0003447

STATION 14 A0 = 18.6674194

A	B	C	PHI	RATIO
-3.3165741	12.3558550	12.7932320	-15.0252333	1.0000000
-3.7300339	-0.7245855	3.7997599	259.0065918	0.2970133
-0.2268665	-0.3501016	0.4171804	212.9432526	0.0326095
-0.0109534	-0.0573655	0.0584019	190.8098907	0.0045651
0.0089840	-0.0269448	0.0284030	161.5604095	0.0022202
0.008049	-0.0112847	0.0113134	175.9201355	0.0008843
0.0058211	-0.0045196	0.0073696	127.8259888	0.0005761
-0.0016236	-0.0042451	0.0031214	200.9294434	0.0003553
-0.0012039	-0.0028799	0.0031214	157.3127899	0.0002440
-0.0010307	-0.0023727	0.0025869	203.4801636	0.0002022

STATION 15 A0 = -0.0176909

A	B	C	PHI	RATIO
0.0103698	-0.0756623	0.0763695	172.1959381	1.0000000
0.0104975	0.0040839	0.0112639	68.7422333	0.1474917
-0.0003934	0.0010045	0.0010788	-21.3894806	0.0141261
-0.0008102	-0.0004531	0.0009283	240.7874298	0.0121552
0.0001319	-0.0001743	0.0002186	142.8869476	0.0028622
0.0007655	0.0000467	0.0007669	86.5120850	0.0100423
-0.0000028	0.0004759	0.0004759	-0.3370049	0.0062313
0.0001418	-0.0001749	0.0002252	140.9597321	0.0029482
0.0003694	0.0000019	0.0003694	89.7012482	0.0048371
0.0002440	0.0000810	0.0002571	71.6364288	0.0033660

#### IV. GRP SAMPLE ANALYSIS

The GRP program was executed using data representing a relatively new rotor blade. The results were compared with results predicted by the blade's manufacturer. The rotor blade was an unsymmetrical blade. The rotor radius was divided into three sections. Sections one and three were made of the same type airfoil. The blade included a sweep tip design. The blade and helicopter configuration analyzed are typical of a helicopter that could be used by the U.S. Navy in a LAMPS type mission.

For the analysis, the blade was divided into 15 segments. The program used the manufacturer's values for the First and Second Moment of Inertia about the Flapping Hinge, vice local blade mass densities. The GRP assumed uniform inflow for all flight velocities. It used a rigid blade analysis while the actual blade does have live twist. The program was run at five different flight weights, ranging from 16,359 to 20,829 pounds. A flat plate area of 35.8 square feet was used at all speeds. The GRP was run for forward flight speeds of 40 to 160 knots at ten knot increments. The program was executed at sea level, tropical day condition. The manufacturer's predicted rotor horsepower was obtained from his Shaft Horsepower versus True Airspeed curves and was corrected to rotor horsepower by using the manufacturer's Mechanical Efficiency curves.

The results of the analysis are shown in the next several tables. Table VI illustrates a comparison of the GRP required rotor horsepower divided by the manufacturer's required rotor horsepower. The GRP agreed within an average of two percent on the entire range from 40 to 160 knots. The GRP agreed within an average of one percent for the cruise range between 70 and 140 knots. It can be seen that between 40 to 60 knots there is a much larger difference

between the two required horsepower. It is felt that the inflow in this region is not uniform as assumed, but highly mixed and irregular. Also, the GRP results were less than the manufacturer's horsepower in the 150 to 160 knot range. This area represents the region of top speed for the helicopter, and much of the retreating blade is in the stall region. Also, it is expected that there is a change in fuselage attitude at this high speed, which would increase the flat plate area above what was used in the program. The GRP program's maximum endurance velocities agreed exactly with those predicted by the manufacturer.

TABLE I WEIGHT = 16359 LBS

VELOCITY	GRP RHP	MANUFACTURER'S RHP	RATIO (GRP/MAN)
40	1105	1152	.96
50	1006	1041	.97
60	960	973	.99
70	955	958	1.00
80	984	971	1.01
90	1047	1034	1.01
100	1142	1109	1.03
110	1273	1237	1.03
120	1438	1396	1.03
130	1643	1589	1.03
140	1893	1852	1.02
150	2300	2216	1.04
160	2567	2745	.94

TABLE II WEIGHT = 17321 LBS

VELOCITY	GRP RHP	MANUFACTURER'S RHP	RATIO (GRP/MAN)
40	1185	1247	.95
50	1075	1122	.96
60	1018	1038	.98
70	1008	1009	1.00
80	1028	1028	1.00
90	1086	1078	1.01
100	1176	1153	1.02
110	1303	1264	1.03
120	1465	1445	1.01
130	1669	1633	1.02
140	1921	1902	1.01
150	2227	2257	.99
160	2598	2791	.93

TABLE III WEIGHT = 19246 LBS

VELOCITY	GRP RHP	MANUFACTURER'S RHP	RATIO (GRP/MAN)
40	1366	1449	.94
50	1229	1301	.94
60	1148	1186	.97
70	1118	1142	.98
80	1126	1153	.98
90	1172	1199	.98
100	1255	1273	.99
110	1375	1387	.99
120	1530	1557	.98
130	1731	1746	.99
140	1983	2038	.97
150	2290	2440	.94
160	2665	-	-

TABLE IV WEIGHT = 19658 LBS

VELOCITY	GRP RHP	MANUFACTURER'S RHP	RATIO (GRP/MAN)
40	1407	1496	.94
50	1264	1340	.94
60	1178	1231	.96
70	1142	1173	.97
80	1149	1179	.98
90	1193	1221	.98
100	1274	1299	.98
110	1392	1414	.98
120	1546	1566	.99
130	1747	1773	.99
140	1999	2048	.98
150	2305	2477	.93
160	2682	-	-

TABLE V WEIGHT = 20829 LBS

VELOCITY	GRP RHP	MANUFACTURER'S RHP	RATIO (GRP/MAN)
40	1532	1627	.94
50	1370	1457	.94
60	1269	1338	.95
70	1222	1267	.96
80	1219	1258	.97
90	1256	1297	.97
100	1330	1375	.97
110	1445	1477	.98
120	1598	1638	.98
130	1798	1866	.96
140	2045	2157	.95
150	2354	2589	.91
160	2747	-	-



TABLE VI RATIO COMPARISON

VELOCITY	WEIGHT					RATIO AVERAGE
	16359	17321	19246	19658	20829	
40	.96	.95	.94	.94	.94	.95
50	.97	.96	.94	.94	.94	.95
60	.99	.98	.97	.96	.95	.97
70	1.00	1.00	.98	.97	.96	.98
80	1.01	1.00	.98	.97	.97	.99
90	1.01	1.01	.98	.98	.97	.99
100	1.03	1.02	.99	.98	.97	1.00
110	1.03	1.03	.99	.99	.98	1.00
120	1.03	1.01	.98	.99	.98	1.00
130	1.03	1.02	.99	.99	.96	1.00
140	1.02	1.01	.97	.98	.95	.99
150	1.04	.99	.94	.93	.91	.96
160	.94	.93	-	-	-	.94
AVERAGES FOR ENTIRE SPEED RANGE						
AVERAGE	1.00	.99	.97	.97	.96	.98
AVERAGES FOR CRUISE RANGE						
70 - 140 KNOTS						
AVERAGE	1.02	1.01	.98	.98	.97	.99

## V. CONCLUSIONS

The logic and theory used in the GRP program was investigated and found to be sound. However, there were three discrepancies in the Navy's version of the program that did require attention. The calculations in the reverse flow section on the rotor were incorrect, the calculation of the chord at the 75 percent radius position was incorrect and the original Trim Option for reducing moments would not work. All of the above discrepancies were corrected.

Three desirable features were added to the GRP program. First, the ability to analyze a rotor blade composed of more than one airfoil type was added. The program will now accept up to five different airfoil data input decks for use in analyzing a rotor system. Secondly, the program would only calculate performance in level flight. The ability to calculate performance in climbs and descents has been added. Lastly, the program will now calculate the aerodynamics for a swept tip rotor blade design.

The results of the sample analysis described in Section IV indicates that the program does produce highly accurate performance predictions. The averaged GRP rotor horsepower was within two percent of the manufacturer's data. The results were within one percent when compared in the area of normal cruise flight. The GRP, in this analysis, assumed uniform inflow, constant flat plate area and a rigid rotor blade. It is felt that while complicated, computer-time-consuming procedures can be taken to reduce these assumptions, they are not warranted if the GRP is to be used strictly as a helicopter performance prediction program.

# GRP COMPUTER PROGRAM

```

AIR-530132B  UNGER  UG  23541  RM 904
FOR INFO  CALL GEORGE UNGER OR HIS FAITHFUL ORTHODOX COMPANION
STEVEN AT X23544, PROVIDED THEY HAVE NOT BEEN LIFTED, SHIFTED,
RIPTED, OR OTHERWISE FOUND BETTER JOBS....

MODIFIED BY LT. JIM LOISELLE, USN 1977
NAVAL POSTGRADUATE SCHOOL, MONTEREY, CALIF.

EQUIVALENCE
1 (V(4),RHO),
2 (V(6),VEL),
3 (V(23),TWT),
4 (V(69),PTRL),
5 (V(77),XDTOL),
6 (V(81),RGL),
7 (V(85),AIS),
8 (V(89),MUL),
9 (V(97),PCNV),
1 (V(101),BTOL),
2 (V(105),B2S),
3 (V(109),PDMP),
4 (V(113),RBIS),
5 (V(117),LAML),
6 (V(122),ANPL),
7 (V(138),INPL),
8 (V(142),FSCG),
9 (V(146),VELY),
1 (V(154),RCRPM),
2 (V(161),RBI),
3 (V(165),XCO),
4 (V(169),XCY),
5 (V(173),XCF),
6 (V(177),XCH),
7 (V(181),XCM),
8 (V(185),XCN),
9 (V(189),XCL),
1 (V(193),XCT),
2 (V(197),XCU),
3 (V(201),XCV),
4 (V(205),XCH),
5 (V(209),XCM),
6 (V(213),XCN),
7 (V(217),XCL),
8 (V(221),XCT),
9 (V(225),XCU),
1 (V(229),XCV),
2 (V(233),XCH),
3 (V(237),XCM),
4 (V(241),XCN),
5 (V(245),XCL),
6 (V(249),XCT),
7 (V(253),XCU),
8 (V(257),XCV),
9 (V(261),XCH),
1 (V(265),XCM),
2 (V(269),XCN),
3 (V(273),XCL),
4 (V(277),XCT),
5 (V(281),XCU),
6 (V(285),XCV),
7 (V(289),XCH),
8 (V(293),XCM),
9 (V(297),XCN),
1 (V(301),XCL),
2 (V(305),XCT),
3 (V(309),XCU),
4 (V(313),XCV),
5 (V(317),XCH),
6 (V(321),XCM),
7 (V(325),XCN),
8 (V(329),XCL),
9 (V(333),XCT),
1 (V(337),XCU),
2 (V(341),XCV),
3 (V(345),XCH),
4 (V(349),XCM),
5 (V(353),XCN),
6 (V(357),XCL),
7 (V(361),XCT),
8 (V(365),XCU),
9 (V(369),XCV),
1 (V(373),XCH),
2 (V(377),XCM),
3 (V(381),XCN),
4 (V(385),XCL),
5 (V(389),XCT),
6 (V(393),XCU),
7 (V(397),XCV),
8 (V(401),XCH),
9 (V(405),XCM),
1 (V(409),XCN),
2 (V(413),XCL),
3 (V(417),XCT),
4 (V(421),XCU),
5 (V(425),XCV),
6 (V(429),XCH),
7 (V(433),XCM),
8 (V(437),XCN),
9 (V(441),XCL),
1 (V(445),XCT),
2 (V(449),XCU),
3 (V(453),XCV),
4 (V(457),XCH),
5 (V(461),XCM),
6 (V(465),XCN),
7 (V(469),XCL),
8 (V(473),XCT),
9 (V(477),XCU),
1 (V(481),XCV),
2 (V(485),XCH),
3 (V(489),XCM),
4 (V(493),XCN),
5 (V(497),XCL),
6 (V(501),XCT),
7 (V(505),XCU),
8 (V(509),XCV),
9 (V(513),XCH),
1 (V(517),XCM),
2 (V(521),XCN),
3 (V(525),XCL),
4 (V(529),XCT),
5 (V(533),XCU),
6 (V(537),XCV),
7 (V(541),XCH),
8 (V(545),XCM),
9 (V(549),XCN),
1 (V(553),XCL),
2 (V(557),XCT),
3 (V(561),XCU),
4 (V(565),XCV),
5 (V(569),XCH),
6 (V(573),XCM),
7 (V(577),XCN),
8 (V(581),XCL),
9 (V(585),XCT),
1 (V(589),XCU),
2 (V(593),XCV),
3 (V(597),XCH),
4 (V(601),XCM),
5 (V(605),XCN),
6 (V(609),XCL),
7 (V(613),XCT),
8 (V(617),XCU),
9 (V(621),XCV),
1 (V(625),XCH),
2 (V(629),XCM),
3 (V(633),XCN),
4 (V(637),XCL),
5 (V(641),XCT),
6 (V(645),XCU),
7 (V(649),XCV),
8 (V(653),XCH),
9 (V(657),XCM),
1 (V(661),XCN),
2 (V(665),XCL),
3 (V(669),XCT),
4 (V(673),XCU),
5 (V(677),XCV),
6 (V(681),XCH),
7 (V(685),XCM),
8 (V(689),XCN),
9 (V(693),XCL),
1 (V(697),XCT),
2 (V(701),XCU),
3 (V(705),XCV),
4 (V(709),XCH),
5 (V(713),XCM),
6 (V(717),XCN),
7 (V(721),XCL),
8 (V(725),XCT),
9 (V(729),XCU),
1 (V(733),XCV),
2 (V(737),XCH),
3 (V(741),XCM),
4 (V(745),XCN),
5 (V(749),XCL),
6 (V(753),XCT),
7 (V(757),XCU),
8 (V(761),XCV),
9 (V(765),XCH),
1 (V(769),XCM),
2 (V(773),XCN),
3 (V(777),XCL),
4 (V(781),XCT),
5 (V(785),XCU),
6 (V(789),XCV),
7 (V(793),XCH),
8 (V(797),XCM),
9 (V(801),XCN),
1 (V(805),XCL),
2 (V(809),XCT),
3 (V(813),XCU),
4 (V(817),XCV),
5 (V(821),XCH),
6 (V(825),XCM),
7 (V(829),XCN),
8 (V(833),XCL),
9 (V(837),XCT),
1 (V(841),XCU),
2 (V(845),XCV),
3 (V(849),XCH),
4 (V(853),XCM),
5 (V(857),XCN),
6 (V(861),XCL),
7 (V(865),XCT),
8 (V(869),XCU),
9 (V(873),XCV),
1 (V(877),XCH),
2 (V(881),XCM),
3 (V(885),XCN),
4 (V(889),XCL),
5 (V(893),XCT),
6 (V(897),XCU),
7 (V(901),XCV),
8 (V(905),XCH),
9 (V(909),XCM),
1 (V(913),XCN),
2 (V(917),XCL),
3 (V(921),XCT),
4 (V(925),XCU),
5 (V(929),XCV),
6 (V(933),XCH),
7 (V(937),XCM),
8 (V(941),XCN),
9 (V(945),XCL),
1 (V(949),XCT),
2 (V(953),XCU),
3 (V(957),XCV),
4 (V(961),XCH),
5 (V(965),XCM),
6 (V(969),XCN),
7 (V(973),XCL),
8 (V(977),XCT),
9 (V(981),XCU),
1 (V(985),XCV),
2 (V(989),XCH),
3 (V(993),XCM),
4 (V(997),XCN),
5 (V(1001),XCL),
6 (V(1005),XCT),
7 (V(1009),XCU),
8 (V(1013),XCV),
9 (V(1017),XCH),
1 (V(1021),XCM),
2 (V(1025),XCN),
3 (V(1029),XCL),
4 (V(1033),XCT),
5 (V(1037),XCU),
6 (V(1041),XCV),
7 (V(1045),XCH),
8 (V(1049),XCM),
9 (V(1053),XCN),
1 (V(1057),XCL),
2 (V(1061),XCT),
3 (V(1065),XCU),
4 (V(1069),XCV),
5 (V(1073),XCH),
6 (V(1077),XCM),
7 (V(1081),XCN),
8 (V(1085),XCL),
9 (V(1089),XCT),
1 (V(1093),XCU),
2 (V(1097),XCV),
3 (V(1101),XCH),
4 (V(1105),XCM),
5 (V(1109),XCN),
6 (V(1113),XCL),
7 (V(1117),XCT),
8 (V(1121),XCU),
9 (V(1125),XCV),
1 (V(1129),XCH),
2 (V(1133),XCM),
3 (V(1137),XCN),
4 (V(1141),XCL),
5 (V(1145),XCT),
6 (V(1149),XCU),
7 (V(1153),XCV),
8 (V(1157),XCH),
9 (V(1161),XCM),
1 (V(1165),XCN),
2 (V(1169),XCL),
3 (V(1173),XCT),
4 (V(1177),XCU),
5 (V(1181),XCV),
6 (V(1185),XCH),
7 (V(1189),XCM),
8 (V(1193),XCN),
9 (V(1197),XCL),
1 (V(1201),XCT),
2 (V(1205),XCU),
3 (V(1209),XCV),
4 (V(1213),XCH),
5 (V(1217),XCM),
6 (V(1221),XCN),
7 (V(1225),XCL),
8 (V(1229),XCT),
9 (V(1233),XCU),
1 (V(1237),XCV),
2 (V(1241),XCH),
3 (V(1245),XCM),
4 (V(1249),XCN),
5 (V(1253),XCL),
6 (V(1257),XCT),
7 (V(1261),XCU),
8 (V(1265),XCV),
9 (V(1269),XCH),
1 (V(1273),XCM),
2 (V(1277),XCN),
3 (V(1281),XCL),
4 (V(1285),XCT),
5 (V(1289),XCU),
6 (V(1293),XCV),
7 (V(1297),XCH),
8 (V(1301),XCM),
9 (V(1305),XCN),
1 (V(1309),XCL),
2 (V(1313),XCT),
3 (V(1317),XCU),
4 (V(1321),XCV),
5 (V(1325),XCH),
6 (V(1329),XCM),
7 (V(1333),XCN),
8 (V(1337),XCL),
9 (V(1341),XCT),
1 (V(1345),XCU),
2 (V(1349),XCV),
3 (V(1353),XCH),
4 (V(1357),XCM),
5 (V(1361),XCN),
6 (V(1365),XCL),
7 (V(1369),XCT),
8 (V(1373),XCU),
9 (V(1377),XCV),
1 (V(1381),XCH),
2 (V(1385),XCM),
3 (V(1389),XCN),
4 (V(1393),XCL),
5 (V(1397),XCT),
6 (V(1401),XCU),
7 (V(1405),XCV),
8 (V(1409),XCH),
9 (V(1413),XCM),
1 (V(1417),XCN),
2 (V(1421),XCL),
3 (V(1425),XCT),
4 (V(1429),XCU),
5 (V(1433),XCV),
6 (V(1437),XCH),
7 (V(1441),XCM),
8 (V(1445),XCN),
9 (V(1449),XCL),
1 (V(1453),XCT),
2 (V(1457),XCU),
3 (V(1461),XCV),
4 (V(1465),XCH),
5 (V(1469),XCM),
6 (V(1473),XCN),
7 (V(1477),XCL),
8 (V(1481),XCT),
9 (V(1485),XCU),
1 (V(1489),XCV),
2 (V(1493),XCH),
3 (V(1497),XCM),
4 (V(1501),XCN),
5 (V(1505),XCL),
6 (V(1509),XCT),
7 (V(1513),XCU),
8 (V(1517),XCV),
9 (V(1521),XCH),
1 (V(1525),XCM),
2 (V(1529),XCN),
3 (V(1533),XCL),
4 (V(1537),XCT),
5 (V(1541),XCU),
6 (V(1545),XCV),
7 (V(1549),XCH),
8 (V(1553),XCM),
9 (V(1557),XCN),
1 (V(1561),XCL),
2 (V(1565),XCT),
3 (V(1569),XCU),
4 (V(1573),XCV),
5 (V(1577),XCH),
6 (V(1581),XCM),
7 (V(1585),XCN),
8 (V(1589),XCL),
9 (V(1593),XCT),
1 (V(1597),XCU),
2 (V(1601),XCV),
3 (V(1605),XCH),
4 (V(1609),XCM),
5 (V(1613),XCN),
6 (V(1617),XCL),
7 (V(1621),XCT),
8 (V(1625),XCU),
9 (V(1629),XCV),
1 (V(1633),XCH),
2 (V(1637),XCM),
3 (V(1641),XCN),
4 (V(1645),XCL),
5 (V(1649),XCT),
6 (V(1653),XCU),
7 (V(1657),XCV),
8 (V(1661),XCH),
9 (V(1665),XCM),
1 (V(1669),XCN),
2 (V(1673),XCL),
3 (V(1677),XCT),
4 (V(1681),XCU),
5 (V(1685),XCV),
6 (V(1689),XCH),
7 (V(1693),XCM),
8 (V(1697),XCN),
9 (V(1701),XCL),
1 (V(1705),XCT),
2 (V(1709),XCU),
3 (V(1713),XCV),
4 (V(1717),XCH),
5 (V(1721),XCM),
6 (V(1725),XCN),
7 (V(1729),XCL),
8 (V(1733),XCT),
9 (V(1737),XCU),
1 (V(1741),XCV),
2 (V(1745),XCH),
3 (V(1749),XCM),
4 (V(1753),XCN),
5 (V(1757),XCL),
6 (V(1761),XCT),
7 (V(1765),XCU),
8 (V(1769),XCV),
9 (V(1773),XCH),
1 (V(1777),XCM),
2 (V(1781),XCN),
3 (V(1785),XCL),
4 (V(1789),XCT),
5 (V(1793),XCU),
6 (V(1797),XCV),
7 (V(1801),XCH),
8 (V(1805),XCM),
9 (V(1809),XCN),
1 (V(1813),XCL),
2 (V(1817),XCT),
3 (V(1821),XCU),
4 (V(1825),XCV),
5 (V(1829),XCH),
6 (V(1833),XCM),
7 (V(1837),XCN),
8 (V(1841),XCL),
9 (V(1845),XCT),
1 (V(1849),XCU),
2 (V(1853),XCV),
3 (V(1857),XCH),
4 (V(1861),XCM),
5 (V(1865),XCN),
6 (V(1869),XCL),
7 (V(1873),XCT),
8 (V(1877),XCU),
9 (V(1881),XCV),
1 (V(1885),XCH),
2 (V(1889),XCM),
3 (V(1893),XCN),
4 (V(1897),XCL),
5 (V(1901),XCT),
6 (V(1905),XCU),
7 (V(1909),XCV),
8 (V(1913),XCH),
9 (V(1917),XCM),
1 (V(1921),XCN),
2 (V(1925),XCL),
3 (V(1929),XCT),
4 (V(1933),XCU),
5 (V(1937),XCV),
6 (V(1941),XCH),
7 (V(1945),XCM),
8 (V(1949),XCN),
9 (V(1953),XCL),
1 (V(1957),XCT),
2 (V(1961),XCU),
3 (V(1965),XCV),
4 (V(1969),XCH),
5 (V(1973),XCM),
6 (V(1977),XCN),
7 (V(1981),XCL),
8 (V(1985),XCT),
9 (V(1989),XCU),
1 (V(1993),XCV),
2 (V(1997),XCH),
3 (V(2001),XCM),
4 (V(2005),XCN),
5 (V(2009),XCL),
6 (V(2013),XCT),
7 (V(2017),XCU),
8 (V(2021),XCV),
9 (V(2025),XCH),
1 (V(2029),XCM),
2 (V(2033),XCN),
3 (V(2037),XCL),
4 (V(2041),XCT),
5 (V(2045),XCU),
6 (V(2049),XCV),
7 (V(2053),XCH),
8 (V(2057),XCM),
9 (V(2061),XCN),
1 (V(2065),XCL),
2 (V(2069),XCT),
3 (V(2073),XCU),
4 (V(2077),XCV),
5 (V(2081),XCH),
6 (V(2085),XCM),
7 (V(2089),XCN),
8 (V(2093),XCL),
9 (V(2097),XCT),
1 (V(2101),XCU),
2 (V(2105),XCV),
3 (V(2109),XCH),
4 (V(2113),XCM),
5 (V(2117),XCN),
6 (V(2121),XCL),
7 (V(2125),XCT),
8 (V(2129),XCU),
9 (V(2133),XCV),
1 (V(2137),XCH),
2 (V(2141),XCM),
3 (V(2145),XCN),
4 (V(2149),XCL),
5 (V(2153),XCT),
6 (V(2157),XCU),
7 (V(2161),XCV),
8 (V(2165),XCH),
9 (V(2169),XCM),
1 (V(2173),XCN),
2 (V(2177),XCL),
3 (V(2181),XCT),
4 (V(2185),XCU),
5 (V(2189),XCV),
6 (V(2193),XCH),
7 (V(2197),XCM),
8 (V(2201),XCN),
9 (V(2205),XCL),
1 (V(2209),XCT),
2 (V(2213),XCU),
3 (V(2217),XCV),
4 (V(2221),XCH),
5 (V(2225),XCM),
6 (V(2229),XCN),
7 (V(2233),XCL),
8 (V(2237),XCT),
9 (V(2241),XCU),
1 (V(2245),XCV),
2 (V(2249),XCH),
3 (V(2253),XCM),
4 (V(2257),XCN),
5 (V(2261),XCL),
6 (V(2265),XCT),
7 (V(2269),XCU),
8 (V(2273),XCV),
9 (V(2277),XCH),
1 (V(2281),XCM),
2 (V(2285),XCN),
3 (V(2289),XCL),
4 (V(2293),XCT),
5 (V(2297),XCU),
6 (V(2301),XCV),
7 (V(2305),XCH),
8 (V(2309),XCM),
9 (V(2313),XCN),
1 (V(2317),XCL),
2 (V(2321),XCT),
3 (V(2325),XCU),
4 (V(2329),XCV),
5 (V(2333),XCH),
6 (V(2337),XCM),
7 (V(2341),XCN),
8 (V(2345),XCL),
9 (V(2349),XCT),
1 (V(2353),XCU),
2 (V(2357),XCV),
3 (V(2361),XCH),
4 (V(2365),XCM),
5 (V(2369),XCN),
6 (V(2373),XCL),
7 (V(2377),XCT),
8 (V(2381),XCU),
9 (V(2385),XCV),
1 (V(2389),XCH),
2 (V(2393),XCM),
3 (V(2397),XCN),
4 (V(2401),XCL),
5 (V(2405),XCT),
6 (V(2409),XCU),
7 (V(2413),XCV),
8 (V(2417),XCH),
9 (V(2421),XCM),
1 (V(2425),XCN),
2 (V(2429),XCL),
3 (V(2433),XCT),
4 (V(2437),XCU),
5 (V(2441),XCV),
6 (V(2445),XCH),
7 (V(2449),XCM),
8 (V(2453),XCN),
9 (V(2457),XCL),
1 (V(2461),XCT),
2 (V(2465),XCU),
3 (V(2469),XCV),
4 (V(2473),XCH),
5 (V(2477),XCM),
6 (V(2481),XCN),
7 (V(2485),XCL),
8 (V(2489),XCT),
9 (V(2493),XCU),
1 (V(2497),XCV),
2 (V(2501),XCH),
3 (V(2505),XCM),
4 (V(2509),XCN),
5 (V(2513),XCL),
6 (V(2517),XCT),
7 (V(2521),XCU),
8 (V(2525),XCV),
9 (V(2529),XCH),
1 (V(2533),XCM),
2 (V(2537),XCN),
3 (V(2541),XCL),
4 (V(2545),XCT),
5 (V(2549),XCU),
6 (V(2553),XCV),
7 (V(2557),XCH),
8 (V(2561),XCM),
9 (V(2565),XCN),
1 (V(2569),XCL),
2 (V(2573),XCT),
3 (V(2577),XCU),
4 (V(2581),XCV),
5 (V(2585),XCH),
6 (V(2589),XCM),
7 (V(2593),XCN),
8 (V(2597),XCL),
9 (V(2601),XCT),
1 (V(2605),XCU),
2 (V(2609),XCV),
3 (V(2613),XCH),
4 (V(2617),XCM),
5 (V(2621),XCN),
6 (V(2625),XCL),
7 (V(2629),XCT),
8 (V(2633),XCU),
9 (V(2637),XCV),
1 (V(2641),XCH),
2 (V(2645),XCM),
3 (V(2649),XCN),
4 (V(2653),XCL),
5 (V(2657),XCT),
6 (V(2661),XCU),
7 (V(2665),XCV),
8 (V(2669),XCH),
9 (V(2673),XCM),
1 (V(2677),XCN),
2 (V(2681),XCL),
3 (V(2685),XCT),
4 (V(2689),XCU),
5 (V(2693),XCV),
6 (V(2697),XCH),
7 (V(2701),XCM),
8 (V(2705),XCN),
9 (V(2709),XCL),
1 (V(2713),XCT),
2 (V(2717),XCU),
3 (V(2721),XCV),
4 (V(2725),XCH),
5 (V(2729),XCM),
6 (V(2733),XCN),
7 (V(2737),XCL),
8 (V(2741),XCT),
9 (V(2745),XCU),
1 (V(2749),XCV),
2 (V(2753),XCH),
3 (V(2757),XCM),
4 (V(2761),XCN),
5 (V(2765),XCL),
6 (V(2769),XCT),
7 (V(2773),XCU),
8 (V(2777),XCV),
9 (V(2781),XCH),
1 (V(2785),XCM),
2 (V(2789),XCN),
3 (V(2793),XCL),
4 (V(2797),XCT),
5 (V(2801),XCU),
6 (V(2805),XCV),
7 (V(2809),XCH),
8 (V(2813),XCM),
9 (V(2817),XCN),
1 (V(2821),XCL),
2 (V(2825),XCT),
3 (V(2829),XCU),
4 (V(2833),XCV),
5 (V(2837),XCH),
6 (V(2841),XCM),
7 (V(2845),XCN),
8 (V(2849),XCL),
9 (V(2853),XCT),
1 (V(2857),XCU),
2 (V(2861),XCV),
3 (V(2865),XCH),
4 (V(2869),XCM),
5 (V(2873),XCN),
6 (V(2877),XCL),
7 (V(2881),XCT),
8 (V(2885),XCU),
9 (V(2889),XCV),
1 (V(2893),XCH),
2 (V(2897),XCM),
3 (V(2901),XCN),
4 (V(2905),XCL),
5 (V(2909),XCT),
6 (V(2913),XCU),
7 (V(2917),XCV),
8 (V(2921),XCH),
9 (V(2925),XCM),
1 (V(2929),XCN),
2 (V(2933),XCL),
3 (V(2937),XCT),
4 (V(2941),XCU),
5 (V(2945),XCV),
6 (V(2949),XCH),
7 (V(2953),XCM),
8 (V(2957),XCN),
9 (V(2961),XCL),
1 (V(2965),XCT),
2 (V(2969),XCU),
3 (V(2973),XCV),
4 (V(2977),XCH),
5 (V(2981),XCM),
6 (V(2985),XCN),
7 (V(2989),XCL),
8 (V(2993),XCT),
9 (V(2997),XCU),
1 (V(3001),XCV),
2 (V(3005),XCH),
3 (V(3009),XCM),
4 (V(3013),XCN),
5 (V(3017),XCL),
6 (V(3021),XCT),
7 (V(3025),XCU),
8 (V(3029),XCV),
9 (V(3033),XCH),
1 (V(3037),XCM),
2 (V(3041),XCN),
3 (V(3045),XCL),
4 (V(3049),XCT),
5 (V(3053),XCU),
6 (V(3057),XCV),
7 (V(3061),XCH),
8 (V(3065),XCM),
9 (V(3069),XCN),
1 (V(3073),XCL),
2 (V(3077),XCT),
3 (V(3081),XCU),
4 (V(3085),XCV),
5 (V(3089),XCH),
6 (V(3093),XCM),
7 (V(3097),XCN),
8 (V(3101),XCL),
9 (V(3105),XCT),
1 (V(3109),XCU),
2 (V(3113),XCV),
3 (V(3117),XCH),
4 (V(3121),XCM),
5 (V(3125),XCN),
6 (V(3129),XCL),
7 (V(3133),XCT),
8 (V(3137),XCU),
9 (V(3141),XCV),
1 (V(3145),XCH),
2 (V(3149),XCM),
3 (V(3153),XCN),
4 (V(3157),XCL),
5 (V(3161),XCT),
6 (V(3165),XCU),
7 (V(3169),XCV),
8 (V(3173),XCH),
9 (V(3177),XCM),
1 (V(3181),XCN),
2 (V(3185),XCL),
3 (V(3189),XCT),
4 (V(3193),XCU),
5 (V(3197),XCV),
6 (V(3201),XCH),
7 (V(3205),XCM),
8 (V(3209),XCN),
9 (V(3213),XCL),
1 (V(3217),XCT),
2 (V(3221),XCU),
3 (V(3225),XCV),
4 (V(3229),XCH),
5 (V(3233),XCM),
6 (V(3237),XCN),
7 (V(3241),XCL),
8 (V(3245),XCT),
9 (V(3249),XCU),
1 (V(3253),XCV),
2 (V(3257),XCH),
3 (V(3261),XCM),
4 (V(3265),XCN),
5 (V(3269),XCL),
6 (V(3273),XCT),
7 (V(3277),XCU),
8 (V(3281),XCV),
9 (V(3285),XCH),
1 (V(3289),XCM),
2 (V(3293),XCN),
3 (V(3297),XCL),
4 (V(3301),XCT),
5 (V(3305),XCU),
6 (V(3309),XCV),
7 (V(3313),XCH),
8 (V(3317),XCM),
9 (V(3321),XCN),
1 (V(3325),XCL),
2 (V(3329),XCT),
3 (V(3333),XCU),
4 (V(3337),XCV),
5 (V(3341),XCH),
6 (V(3345),XCM),
7 (V(3349),XCN),
8 (V(3353),XCL),
9 (V(3357),XCT),
1 (V(3361),XCU),
2 (V(3365),XCV),
3 (V(3369),XCH),
4 (V(3373),XCM),
5 (V(3377),XCN),
6 (V(3381),XCL),
7 (V(3385),XCT),
8 (V(3389),XCU),
9 (V(3393),XCV),
1 (V(3397),XCH),
2 (V(3401),XCM),
3 (V(3405),XCN),
4 (V(3409),XCL),
5 (V(3413),XCT),
6 (V(3417),XCU),
7 (V(3421),XCV),
8 (V(3425),XCH),
9 (V(3429),XCM),
1 (V(3433),XCN),
2 (V(3437),XCL),
3 (V(3441),XCT),
4 (V(3445),XCU),
5 (V(3449),XCV),
6 (V(3453),XCH),
7 (V(3457),XCM),
8 (V(3461),XCN),
9 (V(3465),XCL),
1 (V(3469),XCT),
2 (V(3473),XCU),
3 (V(3477),XCV),
4 (V(3481),XCH),
5 (V(3485),XCM),
6 (V(3489),XCN),
7 (V(3493),XCL),
8 (V(3497),XCT),
9 (V(3501),XCU),
1 (V(3505),XCV),
2 (V(3509),XCH),
3 (V(3513),XCM),
4 (V(3517),XCN),
5 (V(3521),XCL),
6 (V(3525),XCT),
7 (V(3529),XCU),
8 (V(3533),XCV),
9 (V(3537),XCH),
1 (V(3541),XCM),
2 (V(3545),XCN),
3 (V(3549),XCL),
4 (V(3553),XCT),
5 (V(3557),XCU),
6 (V(3561),XCV),
7 (V(3565),XCH),
8 (V(3569),XCM),
9 (V(3573),XCN),
1 (V(3577),XCL),
2 (V(3581),XCT),
3 (V(3585),XCU),
4 (V(3589),XCV),
5 (V(3593),XCH),
6 (V(3597),XCM),
7 (V(3601),XCN),
8 (V(3605),XCL),
9 (V(3609),XCT),
1 (V(3613),XCU),
2 (V(3617),XCV),
3 (V(3621),XCH),
4 (V(3625),XCM),
5 (V(3629),XCN),
6 (V(3633),XCL),
7 (V(3637),XCT),
8 (V(3641),XCU),
9 (V(3645),XCV),
1 (V(3649),XCH),
2 (V(3653),XCM),
3 (V(3657),XCN),
4 (V(3661),XCL),
5 (V(3665),XCT),
6 (V(3669),XCU),
7 (V(3673),XCV),
8 (V(3677),XCH),
9 (V(3681),XCM),
1 (V(3685),XCN),
2 (V(3689),XCL),
3 (V(3693),XCT),
4 (V(3697),XCU),
5 (V(3701),XCV),
6 (V(3705),XCH),
7 (V(3709),XCM),
8 (V(3713),XCN),
9 (V(3717),XCL),
1 (V(3721),XCT),
2 (V(3725),XCU),
3 (V(3729),XCV),
4 (V(3733),XCH),
5 (V(3737),XCM),
6 (V(3741),XCN),
7 (V(3745),XCL),
8 (V(3749),XCT),
9 (V(3753),XCU),
1 (V(3757),XCV),
2 (V(3761),XCH),
3 (V(3765),XCM),
4 (V(3769),XCN),
5 (V(3773),XCL),
6 (V(3777),XCT),
7 (V(3781),XCU),
8 (V(3785),XCV),
9 (V(3789),XCH),
1 (V(3793),XCM),
2 (V(3797),XCN),
3 (V(3801),XCL),
4 (V(3805),XCT),
5 (V(3809),XCU),
6 (V(3813),XCV),
7 (V(3817),XCH),
8 (V(3821),XCM),
9 (V(3825),XCN),
1 (V(3829),XCL),
2 (V(3833),XCT),
3 (V(3837),XCU),
4 (V(3841),XCV),
5 (V(3845),XCH),
6 (V(3849),XCM),
7 (V(3853),XCN),
8 (V(3857),XCL),
9 (V(3861),XCT),
1 (V(3865),XCU),
2 (V(3869),XCV),
3 (V(3873),XCH),
4 (V(3877),XCM),
5 (V(3881),XCN),
6 (V(3885),XCL),
7 (V(3889),XCT),
8 (V(3893),XCU),
9 (V(3897),XCV),
1 (
```

GRP000460  
GRP000470  
GRP000480  
GRP000490  
GRP000500  
GRP000510  
GRP000520  
GRP000530  
GRP000540  
GRP000550  
GRP000560  
GRP000570  
GRP000580  
GRP000590  
GRP000600  
GRP000610  
GRP000620  
GRP000630  
GRP000640  
GRP000650  
GRP000660  
GRP000670  
GRP000680  
GRP000690  
GRP000700  
GRP000710  
GRP000720  
GRP000730  
GRP000740  
GRP000750  
GRP000760  
GRP000770  
GRP000780  
GRP000790  
GRP000800  
GRP000810  
GRP000820  
GRP000830  
GRP000840  
GRP000850  
GRP000860  
GRP000870  
GRP000880  
GRP000890  
GRP000900  
GRP000910  
GRP000920  
GRP000930  
GRP000940

```

DIMENSION SWPCOS(15), UR(15), UTUR(15), SWEEP(73,15),
DIMENSION XDA(73,15), XLAO(15), XLA(15,18), XLB(15,18), DUM(73)
DIMENSION V(200), TP(9), FC(73,9), YMESS(73)
LOGICAL D3B, CONV, SHIN, MCONV, AIB1, ALFA, PRNT, USVL, TEST
REAL MU, LAMBDA, MUSQ, MUL, LOAD, LAMI, IGC, LRF, LATE, LONGD, INPL
INTEGER CASE
JOY = 0
JEB = 0
C*****READ IN BLADE CURVE DATA *****
2000 READ(5,169) WBLADE
      READ(5,69) NBLDAT
      IF (WBLADE.EQ. 0.) GO TO 10
      WRITE(6,173) NBLDAT
      DO 63 N=1, NBLDAT
        READ(5,69) NZ
        IF (WBLADE.NE. 0.) WRITE(6,79) NZ
        DO 61 I=1, NZ
          READ(5,69) J, (CLT(N,I,K), K=1,J)
          IF (WBLADE.NE. 0.) WRITE(6,79) J, (CLT(N,I,K), K=1,J)
61 CONTINUE
        READ(5,69) NZ
        IF (WBLADE.NE. 0.) WRITE(6,79) NZ
        DO 63 I=1, NZ
          READ(5,69) J, (CDT(N,I,K), K=1,J)
          IF (WBLADE.NE. 0.) WRITE(6,79) J, (CDT(N,I,K), K=1,J)
63 CONTINUE
      ZERO OUT LOADER AREA*****
C*****DO 59 I=1,200 *****
59 V(I)=0.
C SET UP CONSTANTS AND AUTOMATIC IN2UT
      PI = 3.14159265
      TWOPI = 6.28318531
      RC = 57.2957795
      XXXXX = 1.0
      BTOL = .001
      BPTOL = .001
      XLTOL = 100.
      XDTOL = 50.
      TOLAB = .25
      BGL = 90.
      G = 32.2
      IGC = 1.
      FTRL = 15.0
      DPSI = 15.0
      BIN = .000001
      BPIN = .000001
      XITLIM = 15.0

```

```

BPPIN = .000001
XNSEG = 15.0
B1S = 7.53
A1S = -1.2
SKIPIN = 1.0
PCNV = 1.0
CASE=0
DO 9000 I=1,15
  RB(I)=1.0
  HIALPA=30.
  LOALPA=-30.
  TPSWST=16.0
  T75=5.0
  LAMBDA=-.0200
  *****
C ***** READ IN CASE DATA *****
C ***** CALL LOADED(V) *****
1000 CASE=CASE+1
  NTPST=TPSWST
  TIPSU=TIPSU/RC
  I=SPAR
DO 9002 J=1,I
  RB(J)=0.0
  MONITN=0
  RD=-ABS(RD)
  IF (FPAREA.NE.0.) RD=-.5*RHO*(VEL*1.689)**2*ABS(FPAREA)
  IF (ABIT.EQ.0.) GO TO 999
  A1S=0.
  B1S=0.
999 NPRNT = PRINT
  DO 810 II=1,7
    NPRNT = NPRNT - 10**(7 - II)
  IF (NPRNT) = 0.0
    XMESS(II) = 0.0
    NPRNT = PRINT
    GO TO 910
  XMESS(II) = 1.0
  CONTINUE
  SKIP = -1.0
  IF (SKIP.NE.0.) SKIP = 1.0
  IF (JEB.GT.0) GO TO 1600
70 ***** PRINT HEADING BEFORE EACH CASE *****
C ***** WRITE (6,80) *****
C SET UP CONTROL VARIABLES ACCORDING TO INPUT OPTIONS
  TOLAB = ABS(TOLAB)
  SHIN=XITLIN.LT.0.
  A1B1=ABIT.NE.0.
  IF (TOP.NE.0.) ATEST=-50.
  ALPA=XITLIN.NE.0..AND.(ALOPT.NE.0..OR.TOP.NE.0.)

```

```

GRP00950
GRP00960
GRP00970
GRP00980
GRP00990
GRP01000
GRP01010
GRP01020
GRP01030
GRP01040
GRP01050
GRP01060
GRP01070
GRP01080
GRP01090
GRP01100
GRP01110
GRP01120
GRP01130
GRP01140
GRP01150
GRP01160
GRP01170
GRP01180
GRP01190
GRP01200
GRP01210
GRP01220
GRP01230
GRP01240
GRP01250
GRP01260
GRP01270
GRP01280
GRP01290
GRP01300
GRP01310
GRP01320
GRP01330
GRP01340
GRP01350
GRP01360
GRP01370
GRP01380
GRP01390
GRP01400
GRP01410
GRP01420
GRP01430

```

```

PRNT=TRAN.NE.O.
USVL=UVL.NE.O.
D3B=TD3B.NE.O.
IF (PPSI.EQ.O.) PPSI=DPSI
IF (ATEST.EQ.O.) ATEST=5.
NSEG=XNSEG
PC=PCR*RC
XDPSI=DPSI/RC
K=360./DPSI+.1
KP1=K+1
OM=OMEGAR/R
R4 = R**4
R5 = R**5
OMS = OM**2
FAC=2./(RC*OM)
ITLIN=ABS(XITLIN)
ITN=0
NSPAR=ABS(SPAR)
NTRL=PTRL
IF (SHIN) NTRL=1
TEST=.TRUE.
MCONV=.TRUE.
IDPSI=DPSI
IDPSI(1)=0
DO 997 I=2, KP1
997 IP(SI(I))=IP(SI(I-1))+IDPSI
NB=XNB
C*****ZERO OUT LAMBDA'S IF NCT TO BE USED *****
IF (USVL) GO TO 551
DO 550 I=2, KP1
DO 550 J=1, NSEG
550 XDA(I, J)=0.
C*** READ HARMONICS OF LAMBDA IF DESIRED *****
551 IF (LAML.EQ.O.) GO TO 504
LAML=0.
READ(5, 500) NHARM
DO 503 I=1, NSEG
READ(5, 501) XLAO(I)
READ(5, 502) {XLA(I, J), J=1, NHARM}
READ(5, 502) {XLB(I, J), J=1, NHARM}
C*** COMPUTE VARIABLE LAMBDA'S IF TO BE USED *****
503 IF (.NOT.USVL) GO TO 507
504 XI=0.
DO 506 I=2, KP1
XI=XI+XDPSI
DO 506 J=1, NSEG
XDA(I, J) = -XLAO(J)
ARG=0.
DO 506 L=1, NHARM

```

```

GRP01440
GRP01450
GRP01460
GRP01470
GRP01480
GRP01490
GRP01500
GRP01510
GRP01520
GRP01530
GRP01540
GRP01550
GRP01560
GRP01570
GRP01580
GRP01590
GRP01600
GRP01610
GRP01620
GRP01630
GRP01640
GRP01650
GRP01660
GRP01670
GRP01680
GRP01690
GRP01700
GRP01710
GRP01720
GRP01730
GRP01740
GRP01750
GRP01760
GRP01770
GRP01780
GRP01790
GRP01800
GRP01810
GRP01820
GRP01830
GRP01840
GRP01850
GRP01860
GRP01870
GRP01880
GRP01890
GRP01900
GRP01910
GRP01920

```

```

506 XDA(I,J)=XDA(I,J)-XLA(J,L)*COS(ARG)-XLB(J,L)*SIN(ARG)
C*** READ BIVARIANT SPAR DATA IF DESIRED *****
507 IF(BSPL.EQ.0.) GO TO 508
    BSPL=0.169) WRSPAR
    READ(5,6) NZ
    IF (WRSPAR.EQ. 0.0) GOTO 9006
    WRITE(6,74) NZ
    WRITE(6,69) NZ
9006 DO 509 I=1,NZ
    READ(5,69) J, (BSCLT(1,I,KK), KK=1,J)
509 IF (WRSPAR.NE. 0.0) WRITE(6,69) J, (BSCLT(1,I,KK), KK=1,J)
    IF (WRSPAR.NE. 0.0) WRITE(6,69) NZ
    DO 510 I=1,NZ
510 IF (WRSPAR.NE. 0.0) WRITE(6,69) J, (BSCDT(1,I,KK), KK=1,J)
C GRAVITY ANGLE COMPUTATIONS
508 IF(BGL.EQ.90.0) GO TO 301
    AA=CCOS(AG/RC)
    BB=CCOS(BGL/RC)
    CC=CCOS(CG/RC)
    AA2=AA**2
    BB2=BB**2
    CC2=CC**2
    HW=SQRT(1.0+ AA2*BB2*CC2)
    HX=BB*SQRT{CC2*(AA2-1.0)+1.0}
    HY=CC*SQRT{AA2*(BB2-1.0)+1.0}
    HZ=AA*SQRT{BB2*(CC2-1.0)+1.0}
    GO TO 302
301 HW=1.0
    HX=0.0
    HY=0.0
    HZ=1.0
C COMPUTE X*S AND CHORDS
302 D=ER
    X(1)=DX(1)/2.0
    XX(1)=X(1)+ER
    DO 1 I=2,NSEG
    D=D+DX(I-1)+DX(I)/2.0
    X(I)=X(I-1)+ER
    SUM=D+DX(NSEG)
    IF(ABS(C(1)-C(2)).GT..0000001) GO TO 199
    DO 12 I=2,NSEG
12 C(I)=C(I-1)
    DO 86 I=1,NSEG
199 IF(X(I)-.75)86,88,87

```

GRP C1930  
 GRP C1940  
 GRP C1950  
 GRP C1960  
 GRP C1970  
 GRP C1980  
 GRP C1990  
 GRP C2000  
 GRP C2010  
 GRP C2020  
 GRP C2030  
 GRP C2040  
 GRP C2050  
 GRP C2060  
 GRP C2070  
 GRP C2080  
 GRP C2090  
 GRP C2100  
 GRP C2110  
 GRP C2120  
 GRP C2130  
 GRP C2140  
 GRP C2150  
 GRP C2160  
 GRP C2170  
 GRP C2180  
 GRP C2190  
 GRP C2200  
 GRP C2210  
 GRP C2220  
 GRP C2230  
 GRP C2240  
 GRP C2250  
 GRP C2260  
 GRP C2270  
 GRP C2280  
 GRP C2290  
 GRP C2300  
 GRP C2310  
 GRP C2320  
 GRP C2330  
 GRP C2340  
 GRP C2350  
 GRP C2360  
 GRP C2370  
 GRP C2380  
 GRP C2390  
 GRP C2400  
 GRP C2410

```

86 CONTINUE
87 C75=C(I-1)+((.75-X(I-1))/(X(I)-X(I-1))*(C(I)-C(I-1)))
GO TO 89
88 C75=C(I)
89 C752=2.*C75**2
BG=G*R/OMEGAR**2
C PRE-COMPUTATION OF FREQUENTLY USED COMBINATIONS
XLP=RHO*OMEGAR**2/24.
DO 2 I=1,NSEG
CDX(I)=C(I)**2*DX(I)
CR(I)=C(I)/R
CRDX(I)=CR(I)*DX(I)
2 XLP{I}=XLP*C(I)
C COMPUTE 1ST AND 2ND MOMENTS
RR2=.5*RHO*R**2
RR5=RR2*RR**3
IF(SHOM.NE.0.) GO TO 96
S=XMASS(1)/RR2*X(1)*DX(1)
SR=S*X(1)
DO 3 I=2,NSEG
DXD=XMASS(I)/RR2*X(I)*DX(I)
S=S+DXD
3 SR=SR+DXD*X(I)
SHOM=SR*RR5
S=S/SR
PHOM=S*SHOM/R
GO TO 97
96 SR=SHOM/RR5
S=PHOM*R/SHOM
C COMPUTE SIGMA
97 RS=RSL
IP(RSL.EQ.0.) RS=XNB*C75/(PI*R)
C COMPUTE TWISTS
IF(TWIST.EQ.0.0) GO TO 102
DO 101 I=1,NSEG
TW(I)=(XX(I)-.75)*TWIST
101 HK=TWOPI*RR2*OMEGAR**2
102 IF(D3B) PHD3BR=PHD3B/RC
XSI= SIN(XDPSI)
XCOS= COS(XDPSI)
C****
C COMPUTE MU AND LAMBDA *****
IF(.NOT.ALFA.AND..NOT.USVL) GO TO 777
IF(DVL.LT.0.) GO TO 777
ALLR=ALL/RC
CAL= COS(ALLR)
MU=VEL*CAL/OMEGAR*1.689
MUSQ=MU**2
IF(USVL) GO TO 104
XINBD = MU*SIN(ALLR)/CAL-RL/(HK*2. *MU)
*****

```

GRP02420  
 GRP02430  
 GRP02440  
 GRP02450  
 GRP02460  
 GRP02470  
 GRP02480  
 GRP02490  
 GRP02500  
 GRP02510  
 GRP02520  
 GRP02530  
 GRP02540  
 GRP02550  
 GRP02560  
 GRP02570  
 GRP02580  
 GRP02590  
 GRP02600  
 GRP02610  
 GRP02620  
 GRP02630  
 GRP02640  
 GRP02650  
 GRP02660  
 GRP02670  
 GRP02680  
 GRP02690  
 GRP02700  
 GRP02710  
 GRP02720  
 GRP02730  
 GRP02740  
 GRP02750  
 GRP02760  
 GRP02770  
 GRP02780  
 GRP02790  
 GRP02800  
 GRP02810  
 GRP02820  
 GRP02830  
 GRP02840  
 GRP02850  
 GRP02860  
 GRP02870  
 GRP02880  
 GRP02890  
 GRP02900



```

IF (MU,LT,.1) XLMBD = XLMBD/2.
DO 1603 I=1,100
  LAMBDA = MU*SIN(ALIR)/CAL-RL/(CAL*2.*HK*SQRT (MU**2+XLMBD**2))
  IF (ABS (LAMBDA-XLMBD).LT..0001) GO TO 104
1603 XLMBD = LAMBDA
  WRITE (6,1604) LAMBDA,XLMBD
  GO TO 104
777 IF (UIN.EQ.0.) GO TO 103
  MU = MUL
  MUSQ = MU**2
  VEL = SQRT ((MUSQ+LAMBDA**2)*(OMEGAR*.5921)**2)
  GO TO 104
103 MUSQ = (VEL/(OMEGAR*.5921))**2-LAMBDA**2
  MU = SQRT(MUSQ)
  C*** COMPUTE TIP MACH NO. *****
104 XMTIP = OMEGAR/SPSD
  MUY = VELY/OMEGAR*1.689
  C PRINT INPUT
  DO 198 I=1,NSEG
198 NN(I)=I
  GO TO 1002
1001 WRITE (6,58)
1002 WRITE (6,201) (NN(I), I=1,NSEG)
  WRITE (6,201) (XMASS(I), I=1,NSEG)
  WRITE (6,202) (DX(I), I=1,NSEG)
  WRITE (6,203) (XX(I), I=1,NSEG)
  WRITE (6,204) (C(I), I=1,NSEG)
  WRITE (6,205) (TW(I), I=1,NSEG)
  WRITE (6,206) (RB(I), I=1,NSEG)
  RB(1)=1
  CASE
  WRITE (6,1010) OMEGAR,AG,R,BGL,SPSD,CG,RHO,TD3I
  WRITE (6,207) OMEGAR,AG,R,BGL,SPSD,CG,RHO,TD3I
  WRITE (6,208) GER,NB,DELD,XMTIP,SMON,RS,SUM,FMON,VEL,HK,IDPSI,FDM
  1P,SEH,IGC,PC,TD3B,PHD3B
  WRITE (6,225) PSCG,VVELY
  WRITE (6,226) FSHR,PSIS
  WRITE (6,227) WLCG,PHIS
  WRITE (6,228) WLMR,THPS
  WRITE (6,229) BTOL,BPTOL,NTRL
  WRITE (6,211) ITERATION OPTIONS IF USED *****
  C*** IF (XITLI.EQ.0.) GO TO 1600
  WRITE (6,38) RL,RD,ITLIM,XTOL,XDTOL
  IF (SHIN) WRITE (6,25)
  IF (.NOT.SHIN) WRITE (6,585)
  IF (A1B1) WRITE (6,95) RA1S,RB1S,TOLAB
  IF (ALFA) WRITE (6,39) ALL STARTING VALUES *****
  C*** SET UP CASE AND COMPUTE *****
1600 CONTINUE

```

```

29      LL=0
      AIR=A1S/RC
      B1R=B1S/RC
      CB=COS(B1R)
      SB=SIN(B1R)
      IF(BIN.EQ.0..OR.ITN.NE.0) GO TO 210
      B(1)=BIN
      BP(1)=BPPIN
      BPP(1)=BPPIN
      BIN=0.
      GO TO 114
210      IF(PCNV.NE.0.0) GO TO 113
      GAM=5.73*C75*RHO*R**4/SMOM
      T7R=T75/RC
      HA=GAM/2.*(T7R*((1.0+MUSQ)/4.0)+LAMBDA/3.0)
      BPP(1)=MU*(8./3.*T7R+2.*LAMBDA)/(1.-.5*MUSQ)
      BP(1)=-4./3.*MU*HA/(1.+5*MUSQ)
      B(1)=HA-BPP(1)
      GO TO 114
113      B(1)=B(KP1)
      BP(1)=BP(KP1)
      BPP(1)=BPP(KP1)
114      PSI=0.0
      LL=LL+1
      XMH3 = 0.0
      XMH5 = 0.0
      XLH1 = 0.0
      XLH2 = 0.0
      HMR = (WLMR-WLCG)/(12.*R)
      LHR = (FSCG-FSMR)/(12.*R)
      PSO = PSIS/OM
      PHSO = PHIS/OM
      THFO = THFS/OM
      FHEOR = FMOM*ER/(RHO*PI*R4)
      ERPI = ER/TWOPI
      SUM1 = 0.0
      SUM2 = 0.0
      SUM3 = 0.0
      SUM4 = 0.0
      RCFPS=RCFPM/60.
      C *****
      C BEGIN CASE *****
      DO 30 I=2,KP1
      PSI=PSI+XDP*PSI
      B(I)=B(I-1)+BP(I-1)*XSIN+(1.-XCOS)*BPP(I-1)
      BD(I)=B(I)*RC
      BP(I)=BP(I-1)*XCOS+BPP(I-1)*XSIN
      YSIN=SIN(B(I))
      C *****
      C *****
      GRP03400
      GRP03410
      GRP03420
      GRP03430
      GRP03440
      GRP03450
      GRP03460
      GRP03470
      GRP03480
      GRP03490
      GRP03500
      GRP03510
      GRP03520
      GRP03530
      GRP03540
      GRP03550
      GRP03560
      GRP03570
      GRP03580
      GRP03590
      GRP03600
      GRP03610
      GRP03620
      GRP03630
      GRP03640
      GRP03650
      GRP03660
      GRP03670
      GRP03680
      GRP03690
      GRP03700
      GRP03710
      GRP03720
      GRP03730
      GRP03740
      GRP03750
      GRP03760
      GRP03770
      GRP03780
      GRP03790
      GRP03800
      GRP03810
      GRP03820
      GRP03830
      GRP03840
      GRP03850
      GRP03860
      GRP03870
      GRP03880

```

```

2SIN=SIN(PSI)
XCOS=COS(B(I))
ZCOS=COS(PSI)
CWM=((ZCOS*HX+ZSIN*HY)*YSIN+YCCS*HZ)*BG/HW+ER*YSIN)*S
IF(SMON.NE.0.) CWM=CWM+YSIN*YCCS
AM=0.0
DO 7 IJ=1,7
7 H(IJ)=0.0
PSI2=2.0*PSI
C CALCULATIONS FOR DELTA 3 BAR
TD3=TD3L
IF(D3B) TD3=TD3+TD3B*SIN(PSI+PHD3BR)
C BEGIN SPANWISE INTEGRATION*****
DO 28 N=1,NSEG
NB=RB(N)
UP(N)=(LAMBDA+(ER+X(N)*YCCS)*(PHSO*ZSIN+THFO*ZCOS)-LMR*
1THFO)*YCCS-X(N)*BP(I)-(MU*ZCOS-MUY*ZSIN)*YSIN
IF(USVL) UP(N)=UP(N)-XDA(I,N)*YCCS/OMEGAR+VEL*SIN(ALL/RC)/OMEGAR
IF(RCPM.NE.0.) UP(N)=UP(N)-RCPM*YCCS/OMEGAR
UT(N)=(1.-PSO)*(ER+X(N)*YCCS)+(MU-HMR*THFO)*ZSIN+(MUY+LMR)*PSO
1+HMR*PHSO)*ZCOS
UR(N)=MU*ZCOS*YCCS-(LAMBDA+(ER+X(N)*YCCS)*(PHSO*ZSIN+THFO*ZCOS
1)-LMR*THFO)*YSIN
C CALCULATIONS FOR TIP SWEEP
IF(N.LT.NTPST) GOTO 9007
URS=UR(N)*COS(TIPSW)+UT(N)*SIN(TIPSW)
UTS=UT(N)*COS(TIPSW)-UR(N)*SIN(TIPSW)
UT(N)=UTS
UR(N)=URS
9007 USO=UP(N)**2+UT(N)**2+UR(N)**2
U(N)=SQRT(USO)
UTUR(N)=SIGN(U(N),UT(N))
UTUR(N)=SIGN(UT(N),UT(N)**2+UR(N)**2)
SWPCOS(N)=ABS(UTUR(N)/UTUR(N))
SWEET(I,N)=ATAN2(SQRT(1.-SWPCOS(N)**2),SWPCOS(N))*RC
PHI(I,N)=ATAN2(UP(N),UTUR(N))*RC
2222 XMACH(I,N)=XMTIP*U(N)
XMACH(I,N)=ABS(XMACH(I,N))
THETAR(N)=(TH(N)-ATN2(ZCOS-B1S*ZSIN-A2S*YCCS(PSI2)-B2S*SIN(PSI2)-TD3
1*BD(I)+T75)/RC
AL(I,N)=PHI(I,N)+ATAN2(ABS(SWPCOS(N))*SIN(THETAR(N)),COS(THETAR
1(N)))*RC
ABAL=ABS(AL(I,N))
IF(ABAL.GT.186.) AL(I,N)=SIGN(ABAL-360.,-AL(I,N))
ALRAD=AL(I,N)/RC
ALTAB=ABS(AL(I,N))
IF(AL(I,N).GT.HIALFA)OR.AL(I,N).LT.LOALFA)XMACHT=0.
IF(N.LE.NSPAR) GO TO 27

```

GRP03890  
 GRP03900  
 GRP03910  
 GRP03920  
 GRP03930  
 GRP03940  
 GRP03950  
 GRP03960  
 GRP03970  
 GRP03980  
 GRP03990  
 GRP04000  
 GRP04010  
 GRP04020  
 GRP04030  
 GRP04040  
 GRP04050  
 GRP04060  
 GRP04070  
 GRP04080  
 GRP04090  
 GRP04100  
 GRP04110  
 GRP04120  
 GRP04130  
 GRP04140  
 GRP04150  
 GRP04160  
 GRP04170  
 GRP04180  
 GRP04190  
 GRP04200  
 GRP04210  
 GRP04220  
 GRP04230  
 GRP04240  
 GRP04250  
 GRP04260  
 GRP04270  
 GRP04280  
 GRP04290  
 GRP04300  
 GRP04310  
 GRP04320  
 GRP04330  
 GRP04340  
 GRP04350  
 GRP04360  
 GRP04370

```

IF (SYM.NE.0.) ALTAB=AL(I,N)
CALL BLIN4 (CLT,NB,5,15,100,CL(I,N),ALTAB,XMACHT,L1)
CALL BLIN4 (CDT,NB,5,15,100,CD(I,N),ALTAB,XMACHT,L2)
IF (L1 + L2 .EQ.2) GOTO 107
IERR = 1
106 IF (IERR .EQ. 0) GOTO 8001
WRITE(6,8821) ALTAB,XMACHT,LL,N,XX(N), IFSI(I), L1,L2
8001 IF (IERR .EQ. 1) GOTO 5000
WRITE(6,8822) ALTAB,XMACHT,LL,N,XX(N), IFSI(I), L1,L2
107 IF (IERR .EQ. 0) GOTO 5000
CD(I,N)=CD(I,N) + DELD
IF (N.EQ.1) CL(I,1)=0.0
GOTO 172
27 IF (SYM.SPR .NE. 0.) ALTAB=AL(I,N)
CALL BLIN4 (BSCLT,1,1,5,71,CL(I,N),ALTAB,XMACHT,L1)
CALL BLIN4 (BSCDT,1,1,5,71,CD(I,N),ALTAB,XMACHT,L2)
IF (L1 + L2 .EQ. 2) GOTO 172
IERR=0
GOTO 106
172 IF (N.EQ.NSEG) CL(I,N)=0.
IF (ABS(SWPCOS(N)) .LT. .5) CL(I,N)=.5*CL(I,N)
IF (ABS(SWPCOS(N)) .LT. .3) CL(I,N)=0.0
IF (AL(I,N) .GE. 0. .OR. SYM.NE.0.) GC TO 5
CL(I,N)=-CL(I,N) *CRDX(N)
UCD(N)=ABS(U(N)) *UTUR(N) + CD(I,N) *UP(N) *ABS(U(N)) *XLFC(N)
5 LOAD(I,N)=CL(I,N) *UTUR(N) *UCD(N)
CU = CD(I,N) + CU
H(1)=H(2) + CU *X(N)
CU=CL(I,N) *UP(N) *UCD(N)
H(2)=H(3) + CU
H(3)=H(4) + CU *X(N)
CU = (CL(I,N) *UTUR(N) + CD(I,N) * UE(N)) *UCD(N)
H(4)=H(5) + CU
H(5)=H(6) + CU *X(N)
H(6)=AM+CU *X(N)
28 AM=AM/SR
C COMPUTE FORCE COEFFICIENTS AROUND AZIMUTH
COL(I)={ER*H(3)+H(4)*YCOS}/TWOPI
COD(I)={ER*H(1)+H(2)*YCOS}/TWOPI
CO(I)={COD(I)-COL(I)}
CZ(I)=-H(5)*YCOS/TWOPI
H13=H(1)-H(3)
CY(I)={H(5)*YSIN*ZCOS-ZSIN *H(1)+H(3)*ZSIN}/TWOPI
HEYH=-H(5)*ER*YCOS-H(6)

```

```

H24=H(2)-H(4)
CP(I)={HEYH*ZCOS-YSIN*ZSIN*H24*{1.-INPL}}/TWOPI
XR(I)={HEYH*ZSIN-YSIN*ZCOS*H24*{1.-INPL}}/TWOPI
HG=2.*PHSO*ZCOS-2.*THPO*ZSIN
BPP(I)=(AM-CWM-(BP(I)*FDMPT*(B(I)-PCR)*SPH/OM)/(SMOM*OM))*HG
IF(SHOM.EQ.0.) BPP(I)=0.0
XMH2=(BPP(I)*YCOS-BP(I)**2*YSIN)
HH(I)=PMEOR*YMH2*ZCOS+ER*CZ(I)*ZCOS-(SPH*(B(I)-PCR)*ZCOS)/
1(RHO*PI*OMEGAR**2**R**3)
1(HL(I)=PMEOR*YMH2*ZSIN+ER*CZ(I)*ZSIN-(SPH*(B(I)-PCR)*ZSIN)/
1(RHO*PI*OMEGAR**2**R**3)
PRINT TRANSIENT AND/OR DEBUGGING IF DESIRED
IF((XMESS(2)+XMESS(1)).EQ.0.) GO TO 30
IF(LL.EQ.1.AND.I.EQ.2) WRITE(6,94) B(1),BP(1),BPP(1)
NPSI=IPSI(I).EQ.0.) GO TO 299
IF(XMESS(1).GO TO 298
IF(I.GT.2)
WRITE(6,58)
298 WRITE(6,91) NPSI,LL,B(I),BP(I),BPP(I),(UP(N),UT(N),U(N),PHI(I,N),
1AL(I,N),XMHACH(I,N),CL(I,N),CB(I,N),LOAD(I,N),NSEG)
GO TO 30
299 WRITE(6,92) NPSI,LL,B(I),BP(I),BPP(I)
30 CONTINUE
C*****
C SAVE STARTING VALUES AT PSI = 0
B0(LL)=B(1)
BPP0(LL)=BPP(1)
IF(LL.LT.2) GO TO 113
C TEST FOR FLAPPING CONVERGENCE
CONV=(ABS(B(KP1)-B(1)).LE.BTOL).AND.(ABS(EP(KP1)-EP(1)).LE.BPTOL)
IF(CONV) GO TO 711
IF(LL.LT.NTRN) GO TO 113
IF(.NOT.(SHIN.AND.ITN.LT.ITLIM).AND.PRNT) WRITE(6,34)
C*****
C COMPUTE AND PRINT HARM. ANAL. OF BETA IN DEGREES
711 BD(1)=B(1)*RC
CALL HARM(K,6,BD,0.0,A0,BUF1,BUF2,BUF3,BUF4,BUF5,I)
IF(.NOT.A1B1) GO TO 164
C COMPUTE DELTA A1S AND B1S
DA1S={BUF1(1)-RA1S}*IGC
DB1S={BUF2(1)-RB1S}*IGC
C INTEGRATE FORCE COEFFICIENTS AROUND AZIMUTH
164 ICQL=CQL(2)
ICOD=COD(2)
ICQ=CQ(2)
ICZ=CZ(2)

```

GRP05360  
GRP05370  
GRP05380  
GRP05390  
GRP05400  
GRP05410  
GRP05420  
GRP05430  
GRP05440  
GRP05450  
GRP05460  
GRP05470  
GRP05480  
GRP05490  
GRP05500  
GRP05510  
GRP05520  
GRP05530  
GRP05540  
GRP05550  
GRP05560  
GRP05570  
GRP05580  
GRP05590  
GRP05600  
GRP05610  
GRP05620  
GRP05630  
GRP05640  
GRP05650  
GRP05660  
GRP05670  
GRP05680  
GRP05690  
GRP05700  
GRP05710  
GRP05720  
GRP05730  
GRP05740  
GRP05750  
GRP05760  
GRP05770  
GRP05780  
GRP05790  
GRP05800  
GRP05810  
GRP05820  
GRP05830  
GRP05840

```

        XCY=CX {2}
        XCY=CY {2}
        XXR=XR {2}
        XCP=CP {2}
        XHH = HH {2}
        XHL = HL {2}
        DO 601 I=3, KP1
            XCQL=XCOL+COL {I}
            XCQD=XCOD+COD {I}
            XCQ=XCQ+CX {I}
            XCZ=XCZ+CX {I}
            XCY=XCY+CY {I}
            XXR=XXR+XR {I}
            XHH = XHH+HH {I}
            XHL = XHL+HL {I}
            XCP=XCP+CP {I}
        C** COMPUTE TOTAL FORCES*****
        XK=K
        F=XNB/XK*HK
        PR=P*PR
        CHF=OM/550.
        Q=XCO*PR
        HP=Q*OMF
        PHP=XCOD*PR*OMF
        ZF=XCZ*P
        AP=XCY*P
        YF=XCY*P
        RM=XXR*PR
        PM=XCP*PR
        XLH = XHL*PR
        XHH = XHH*PR
        AX=ALLR
        IF (.NOT. USVL.OR. UVL.LT.0.) AX=ATAN (LAMBDA/MU- (ZF/HK)/(2.*MU*SQR (
1AMBDA**2+MUSQ)))
        ALS=AX*RC
        ALC=ALS-B1S
        AR=ATAN (RD/RL)
        XRC=SQR (ZF**2+XF**2)
        RR=SQR (RL**2+RD**2)
        CA=COS (AX)
        SA=SIN (AX)
        XCL=-ZF*CA+XF*SA
        XCD=-ZF*SA-XF*CA
        AC=ATAN2 (XCD,XCL)
        VAC=MU*OMEGA*CA/1.688
        IF (.NOT.ALFA) MU=VEL/VAC*MU
        MUSQ=MU**2
        EQD=326.*HP/VAC+XCD

```

```

EQLD=XCL/EQD
EOPA=EOD/RHO*.70116482/VAC**2
ALR=ALC/RC
W=ATAN2(SIN(A1R)/COS(A1R),CA)
SH=SIN(W)
CW=COS(W)
TAU=ATAN(SIN(ALR)/COS(ALR)*CW)
STAU=SIN(TAU)
CTAU=COS(TAU)
THR=XP*(SA*CW*CTAU-CA*STAU)-ZF*(CA*CTAU*CW+SA*STAU)+YP*SW*CTAU
CT=THR/HK
HP=-YP*(CA*CTAU+SA*STAU*CH)-ZF*(SA*CTAU-CA*STAU*CH)-YP*SW*STAU
CH=HF/HK
CLP=XCL/HK
CDP=XCD/HK
CTOS=CT/RS
CHOS=CH/RS
CLPOS=CLP/RS
CDPOS=CDP/RS
RES=SQRT(XF**2+YF**2+ZF**2)
IRF=100/(XCL*R)
LATD=RM*LRP
LONGD=PM*LRP
COANS = Q/(HK*R)
COOS = COANS/RS
C**** APPLY MAJOR ITERATION CONVERGENCE CRITERIA *****
1500 IF (XITLLM.EQ.0.) GO TO 116
      MCONV=ABS(RI-XCL).LE.XLTOL
      IF (.NOT.ALFA) MCONV=MCONV.AND.ABS(RD-YCD).LE.XDTOL
      IF (SHIN) MCONV=MCONV.AND.CONV
      IF (ABIT.NE.0.) MCONV=MCONV.AND.ABS(DA1S).LE.TOLAB.AND.ABS(DB1S).LEGRP06170
      1.TOLAB
      IF (TRIM.NE.0.)MCONV=MCONV.AND.AES(RM).LE.100..AND.ABS(PM).LE.100..GRP06180
      C**** *****
      C IF MAJ. IT. CONVERGED GO TO FINAL PRINTOUT, IF NOT TEST FOT IT. LIMIT GRP06190
      C ****
      IF (SKIP.GT.0..AND..NOT.MCONV) GO TO 1699
      IF (SKIP.GT.0..AND..NOT.MCONV) GO TO 1699
      116 WRITE (6,58)
      WRITE (6,142) A1S,B1S,A2S,B2S,T75,LAMBDA,MU,MUY
      WRITE (6,180) CT,CH,CLP,CDP,CTOS,CHOS,CLPOS,C6POS,CQANS,CQOS
      WRITE (6,181) XCL,XP,RES,XCD,YP,RM
      WRITE (6,182) HP,ZP,PM,EOD,EQLD,EOPA,ALS,THR,Q
      WRITE (6,183) ALC,HF,PHP,LATD,VAC, LONGD, XMH,XLH,ITN
      IF (XITLLM.EQ.0.) GO TO 115
      1699 IF (MCONV) GO TO 115
      C !! *****
      C IF LIMIT NOT EXCEEDED ALTER PARAMETERS, OTHERWISE PRINT FAILURE MESSAGE GRP06310
      C ****
      C ****

```

```

1700 IF (ITN.LT.ITLIM) GO TO 51
      CONTINUE
      WRITE (6,48)
      WRITE (6,56)
      WRITE (6,48)
      ITN=ITN+1
      GO TO 115
C**** ALTER PARAMETERS ACCORDING TO OPTIONS *****
51  RSP=RS+5.73
      DATH=16.*MU/(6.-3.*MUSQ)+RSP/(12.*MUSQ)
      DAL=4.*MU/(2.-MUSQ)+1./HU+RSP/(8.*MUSQ)
      HR=HK*RS/2.
      HJ=.47+.26*MUSQ
      HR5=HR*5.73
      DRTH=HR5*(.3+.48*MUSQ)
      DRL=HR5*HJ
      ABF=0.
      DAB=4.*MUSQ/(MUSQ-2.)-RSP/(8.*MU)-1.
      DRB=-DRL*MU
      IF (.NOT.A1B1) GO TO 52
      IF (.NOT.A1B1) C75*RR4/1760.,((3.- 8.*ER +6.*ER**2)/(ER*R *PMOM *
1  FEI 1.0) +SPH/ONS))
      A1S = A1S - (DA1S*COS(FEI) +DB1S* SIN(FEI))
      ABF = DA1S*SIN(FEI) - DB1S*COS(FEI)
      BIS=B1S+ABF
      ABF=ABF/RC
52  DELR=RR-XRC-DRB*ABF
      DELA=AR-AC-DAB*ABF
      DRALTH=DRL*DATH-DRTH*DAL
      DTH=(RL-XCL-DRB*ABF)/DRTH*RC*IGC*(1.-TOP)
      DLMDA=(RL-XCL-DRB*ABF)/DRL*IGC*TOP
      IF (ALFA) GO TO 888
      DTH=(DRL*DELA-DAL*DELR)/DRALTH*RC*IGC
      DLMDA=(DATH*DELR-DRTH*DELA)/DRALTH*IGC
      IF (.NOT.USVL) GO TO 888
      DALFA=DLMDA/HU
      ALFR=ALLR+DALFA
888  IF (ABS(DTH/10.) > .5) DTH = SIGN(.5*10.,DTH)
      IF (ABS(DLMDA/0.0200) > .5) DLMDA = SIGN(.4*0.0200,DLMDA)
      T75=T75+DTH
311  LAMBDA=LAMBDA+DLMDA
      ITN=ITN+1
C**** TEST FOR LIFT CURVE SLOPE LESS THAN ACCEPTABLE MINIMUM *****
C**** IF (ITN.EQ.1) GO TO 952
      IF (.NOT.ALFA) GO TO 115
      TEMP=XCL-TEMP
      A=TEMP/DTP*RC/DRTH*5.73
      IF (A.LT.ATEST) TEST=.FALSE.

```

GRP06340  
 GRP06350  
 GRP06360  
 GRP06370  
 GRP06380  
 GRP06390  
 GRP06400  
 GRP06410  
 GRP06420  
 GRP06430  
 GRP06440  
 GRP06450  
 GRP06460  
 GRP06470  
 GRP06480  
 GRP06490  
 GRP06500  
 GRP06510  
 GRP06520  
 GRP06530  
 GRP06540  
 GRP06550  
 GRP06560  
 GRP06570  
 GRP06580  
 GRP06590  
 GRP06600  
 GRP06610  
 GRP06620  
 GRP06630  
 GRP06640  
 GRP06650  
 GRP06660  
 GRP06670  
 GRP06680  
 GRP06690  
 GRP06700  
 GRP06710  
 GRP06720  
 GRP06730  
 GRP06740  
 GRP06750  
 GRP06760  
 GRP06770  
 GRP06780  
 GRP06790  
 GRP06800  
 GRP06810  
 GRP06820



```

952 IF (.NOT.TEST) WRITE (6,951) A,AIEST
    TEMP=XCL-DRB*ABF
    DTP=DTH
    *****
    PRINT INITIAL BETA, * AND **, AND SUMMARY OF FINAL REV.
    C 115 IF (XMESS(6).EQ.1..AND.MCONV) GO TO 2501
    GO TO 1501
    2501 WRITE (6,58)
    WRITE (6,134)
    LL=LL-1
    DO 132 I=1,LL
    132 WRITE (6,133) I,B0(I),BP0(I),BPP0(I)
    LL=LL+1
    WRITE (6,135) LL
    MN=K/2+1
    DO 136 I=1,MN
    136 WRITE (6,137) IPSI(I),B(I),BP(I),BPP(I),IPSI(L),BP(L),BPP(L)
    WRITE (6,160)
    WRITE (6,161) A0,(BUF1(I),I=1,6)
    WRITE (6,162) (BUF2(I),I=1,6)
    *****
    C 1501 IF (XMESS(5).EQ.1..AND.MCONV) GO TO 2502
    GO TO 1502
    C** COMPUTE AND PRINT AVERAGES*****
    2502 WRITE (6,58)
    DO 143 I=2,KP1
    143 WRITE (6,144) IPSI(I),(FC(I,J),J=1,8)
    DO 602 I=1,8
    602 AV(I)=TP(I)/XK
    WRITE (6,145) (AV(I),I=1,8)
    DO 603 I=1,8
    603 AV(I)=XNB*AV(I)
    WRITE (6,146) (AV(I),I=1,8)
    DO 604 I=1,8
    604 AV(I)=AV(I)/RS
    WRITE (6,147) (AV(I),I=1,8)
    MN=K/2+1
    I=MN+1
    DO 151 J=1,KP1
    151 IP(CQD(I),LT.CQD(J)) GO TO 152
    CONTINUE
    GO TO 154
    I=J
    152 BCQDOS=CQD(I)*XNB/RS
    154 WRITE (6,153) BCQDOS,IPSI(I)
    *****
    C COMPUTE AND PRINT HARM. ANAL. OF C2 IF DESIRED *****
    C

```

```

1502 IF (XMESS(4).EQ.1..AND.MCONV) GO TO 2503
GO TO 1503
2503 DO 902 I=1,K
902 CZ(I)=CZ(I+1)
WRITE (6,58)
WRITE (6,901)
CALL HARM (K,6,CZ,DPSI,A0,BUF1,BUF2,BUF3,BUF4,BUF5,L)
A0=A0*HK
DO 900 I=1,6
900 BUF1(I)=-BUF1(I)*HK
BUF2(I)=-BUF2(I)*HK
WRITE (6,161) A0,BUF1(I),I=1,6
WRITE (6,162) (BUF2(I),I=1,6)
C *****
C ***** PRINT DATA SECTION AT SPECIFIED INTERVAL IF DESIRED *****
C ***** GC TO 2505 *****
1503 IF (XMESS(7).EQ.1..AND.MCONV) GO TO 2505
GO TO 523
2505 WRITE (6,58)
NP=ABS(PPSI)/DPSI+1.1
NPL1=NP-1
NPL12=NPL1*2
KLN=KPL1-NPL1
DO 73 I=NP,KLN,NPL12
73 J=I+NPL1
PSIP=IPSI(I)
WRITE (6,71) IPSI(I),IPSI(J),XMACH(I,N),CL(I,N),CD(I,N),PHI(I,N)
WRITE (6,72) (XX(N),AL(I,N),XMACH(J,N),CL(J,N),CD(J,N),PHI(J,N),
1 LOAD(I,N),SWEEP(I,N),N=1,NSEG)
2 LOAD(J,N),SWEEP(J,N),N=1,NSEG)
C *****
C ***** COMPUTE AND PRINT HARMONICS OF AIR LOADS IF DESIRED *****
C ***** GO TO 2506 *****
523 IF (XMESS(3).EQ.1..AND.MCONV) GO TO 2506
GO TO 47
2506 WRITE (6,519)
DO 521 N=1,NSEG
520 DUM(I)=LOAD(I+1,N)
NH=MIN1(180./DPSI+.1,DPSI)
CALL HARM (K,NH,DUM,BUF1(I),BUF2(I),BUF3(I),BUF4(I),BUF5(I),I=1,NH)
WRITE (6,522) N,A0,(BUF1(I),BUF2(I),BUF3(I),BUF4(I),BUF5(I),I=1,NH)
521 CONTINUE
C *****
C ***** GO TO RESTART PROCEDURE IF INDICATED *****
C ***** GO TO *****
C ***** IF (XITLIM.NE.0..AND.ITN.LE.ITLIM.AND..NOT.MCONV.AND.TEST) GO TO
47,1111
GO TO 77
1111 GO TO 6969

```

```

77 JOY = 1
6969 IF (JOY.GT.0) GO TO 5000
C*** MOMENT OPTION*****
IF (TRIM.EQ.0.) GO TO 1710
MOMITN=MOMITN + 1
IF (MOMITN.GT.1) GO TO 1701
A1S1 = A1S
B1S1 = B1S
RM1 = RM
FM1 = FM
A1S = IGC * (A1S -.0006*RM)
B1S = IGC * (B1S + .0007*PM)
GO TO 1710
1701 A1S2 = A1S
RM2 = RM
PM2 = PM
B1S2 = B1S
B1S = IGC * (B1S2*PM1-PM2*B1S1) / (PM1-PM2)
A1S = IGC * (A1S2*RM1-RM2*A1S1) / (RM1-RM2)
ABF=B1S/RC
1710 CONTINUE
IF (JEB.LE.15) GO TO 70
WRITE (6,808)
C *****
C GO TO NEXT CASE IF LOC. 99 NOT EQ. ANY NEG NUMBER.
C *****
5000 JOY = 0
JEB = 0
IF (XEND.EQ.2.) GO TO 2000
IF (XEND.GE.0.) GO TO 1000
WRITE (6,5001)
6666 STOP
25 FORMAT (///,1H,42(1H*),5X,25HFLAPPING DID NOT CONVERGE 5X,42(1H*))
34 FORMAT (///,1H,42(1H*),5X,25HFLAPPING DID NOT CONVERGE 5X,42(1H*))
38 FORMAT (///,1H,42(1H*),5X,25HFLAPPING DID NOT CONVERGE 5X,42(1H*))
1HMAJOR ITERATION LIMIT = I3//16H IIFT TOLERANCE=F9.2, 8X15HDRAG TOL
2ERANCE=F8.2}
39 FORMAT (53H0ALPHA OPTION HAS BEEN REQUESTED - - - INPUT ALPHA = P8.
14)
48 FORMAT (1H0,119(1H*))
56 FORMAT (1H0,39(1H*),5X,32HMAJOR ITERATION DID NOT CONVERGE,5X,38(1HGRP08210
1*)
58 FORMAT (1H1)
69 FORMAT (12,10F7.0 / (F9.0,9F7.0))
71 FORMAT (12,29X6HPSI = I4,9H DEGREES)
72 FORMAT (132H0 X ALPHA MACH CL PHI L(LB/IN)
1IN) SWEEP ALPHA MACH CL CD PHI L(LB/IN)
2 SWEET (F7.4,2X,6F8.3,F10.2,5X,6F8.3,F10.2)
173 FORMAT (1H1,50X,ELADE DATA',/)

```

```

74  FORMAT(1H1,50X,'SPAR DATA',/,(10X,10F10.3)) GRP083300
79  FORMAT(1X,12,7X,10F10.3,/(10X,10F10.3)) GRP083310
80  FORMAT(1H1,2X,25HNAVAL AIR SYSTEMS COMMAND,4X,17HAIRFRAME DIVISION GRP083320
1,4X,19HAERO + HYDRO BRANCH,4X,19HPERFORMANCE SECTION 4X,16HROTARY GRP083330
5,16HUNIT/2X,UNITED STATES NAVY DEPARTMENT OF DEFENSE(?),/53XGRP083340
3,16HINPUT QUANTITIES) GRP083350
91  FORMAT(7HOPSI = I3,9H DEGREES,5H REVI3,5X7HBETA = F11.8,5X8HBET GRP083360
1A* = F11.8,5X,9HBETA** = F11.8, UT GRP083370
2 120H0 CL U LOAD(LB/IN)/ PHI ALGRP08380
3PHA MACH NO. GRP08390
4/ (9F12.7)) GRF08400
92  FORMAT(7HOPSI = I3,9H DEGREES,5H REVI3,5X7HBETA = F11.8,5X8HBET GRP08410
1A* = F11.8,5X,9HBETA** = F11.8) GRP08420
94  FORMAT(11H0BETA(0) = ,F11.8,5X,11HBETA*(0) = ,F11.8,5X,12HBETA** (0GRP08430
1) = F11.8) GRP08440
95  FORMAT(17H0REQUESTED A1 = F10.4,6X16HREQUESTED B1 = F9.4,8X25HTOGRP08450
1ERANCE ON A1 AND B1 = F6.3) GRP08460
133  FORMAT(1H029X,12,3X,3F17.7) GRP08470
134  FORMAT(1H0,28X,3HREV,12X,7HBETA(0),10X,8HBETA*(0),8X,9HBETA** GRP08480
1(0)) GRP08490
135  FORMAT(29H0EQUILIBRIUM SOLUTION REV = I2 /4HOPSI5X4HBETA8X5HGRP08500
1BETA*6X6HBETA** 30X3HPSSI5X4HBETA8X5HBETA*6X6HBETA**) GRP08510
137  FORMAT(14,3F12.7,28X13,3F12.7) GRP08520
142  FORMAT(6H0,11X,3HB1S,11X,3HA2S,11X,3HB2S,11X,10HTHETA,75- GRP08530
111X,3HAMBDA(S),11X,6HMU(X)S,11X,6HMU(Y)S,1X,6.2,3F14.2,F18.2, GRP08540
2F21.4,2F16.4) GRP08550
144  FORMAT(11,4X,8(1PE12.4)) GRP08560
145  FORMAT(15H0AVERAGE ,8(1PE12.4)) GRP08570
146  FORMAT(15H (B) *AVE. ,8(1PE12.4)) GRP08580
147  FORMAT(15H (B) *AV/SIG ,8(1PE12.4)) GRP08590
148  FORMAT(52X17HFORCE INTEGRATION//8X3HPSSI10X2HCQ10X3HCQL9X3HCQD9X2GRP08600
1HCZ,10X,2HCX,10X,2HCY,9X,4HCMHS,8X,4HCLHS,/) GRP08610
153  FORMAT(34X18HMAX B*CD/SIGMA = F8.6,16H AT PSI = I3) GRP08620
160  FORMAT(36X48HFOURIER COEFFICIENTS (WITH RESPECT TO THE SHAFT)//16XGRP08630
173HBETA (DEG) = A0-A1*COS(PSI) -B1*SIN(PSI) -A2*COS(2*PSI) -B2*SIN(2*GRP08640
2PSI) //) GRP08650
161  FORMAT(1H0,6X2HA012X2HA112X2HA212X2HA312X2HA412X2HA512X2HA6/7(1PEGRP08660
114.4)) GRP08670
162  FORMAT(1H020X 2HB112X2HB212X2HB312X2HB412X2HB512X2HB6/14X6 (GRP08680
1PE14.4)) GRP08690
169  FORMAT(1H0,0) GRP08700
180  FORMAT(1H0,0) GRP08710
1L* = 1PE14.6,7X10H0CT = 1PE14.6,7X10H0CT/SIGMA = 1PE14.6,7X10H0CT GRP08720
2H/SIGMA = 1PE14.6,7X10H0CL*/SIGMA = 1PE14.6,7X10H0CL*/SIGMA = 1PE14.6,7X10H0CL*/GRP08730
3H CQ = 1PE14.6,7X10H0CQ*/SIGMA = 1PE14.6,7X10H0CQ*/SIGMA = 1PE14.6,7X10H0CQ*/GRP08740
181  FORMAT(1H0,8X,12H1IFT = F11.3,8H POUNDS,8X,12HX FORCE GRP08750
1 = ,F11.3,8H POUNDS,8X,12HRESULTANT = F11.3,8H POUNDS//8X,12HDRA GRP08760
2G = F11.3,8H POUNDS,8X,12HY FORCE = F11.3,8H POUNDS,8X, GRP08770
312HROLL MOM = F11.3,11H FT-POUNDS) GRP08780

```

182 FORMAT (1H0, 7X, 12HHORSEPOWER = F11.3, 16X, 12HZ FORCE = F11.3, 8H GRP08790  
 1 POUNDS, 8X, 12HITCH MOM = F11.3, 11H FT-POUNDS//8X, 12HEQUIV DRAG = F11.3, 8H GRP08800  
 2, F11.3, 8H POUNDS, 8X, 12HEQUIV L/D = F11.3, 16X, 12HEQUIV P.A. = F11.3, 8H GRP08810  
 3, 3, 10H SQ FEET//8X, 12HALPHA(S) = F11.3, 9H DEGREES, 7X, 12HTHRU GRP08820  
 4T = F11.3, 8H POUNDS, 8X, 12HTRCROUE = F11.3, 11H FT-POUNDS) = F11.3, 8H GRP08830  
 183 FORMAT (1H0, 7X, 12HALPHA(C) = F11.3, 9H DEGREES, 7X, 12HH FORCE = F11.3, 8H GRP08840  
 1 F11.3, 8H POUNDS, 8X, 12HPROFIE HP = F11.3, 11H KNOTS9X12HLOGRP08850  
 2, DIS = F11.3, 9H PERCENT//47X, 12H KNOTS9X12HLOGRP08860  
 3NG. DIS. = F11.3, 9H PERCENT//47X, 12H KNOTS9X12HLOGRP08870  
 425HSHEARS HUB PITCH MOMENT = F10.2, 4X 6HFT-LBS //47X, 12H KNOTS9X12HLOGRP08880  
 525HSHEARS HUB ROLL MOMENT = F10.2, 4X 6HFT-LBS //47X, 12H KNOTS9X12HLOGRP08890  
 6 MAJOR ITERATIONS USED = , I4, //119(1H\*) GRP08900  
 200 FORMAT (5X7HSTATION15I7) GRP08910  
 201 FORMAT (14HOMASS SLUG/FT 15F7.4) GRP08920  
 202 FORMAT (8HODELTA X6X15F7.4) GRP08930  
 203 FORMAT (2H0X12X15F7.4) GRP08940  
 204 FORMAT (11H0CHORD FEET3X15F7.4) GRP08950  
 205 FORMAT (11H0TWIST DEG.3X15F7.4) GRP08960  
 206 FORMAT (11H0BLADE DECK.1X15F7.0) GRP08970  
 207 FORMAT (1H0, 9X, 18H AG = F8.2, 5X, 30H FT/SEC = F8.2, 5X, 30H RADIUS GRP08980  
 1 = F8.2, 7X, 27H FEET = F8.2, 5X, 9H DEGREES//10X, 18H BG GRP08990  
 2 = F8.2, 5X, 9H DEGREES//10X, 18H BG GRP09000  
 3 FEET/SEC = F8.2, 5X, 9H DEGREES//10X, 18H BG GRP09010  
 4 //10X, 18H RHO = F13.7, 30H SLUGS/CUBIC FT. = F8.2, 5X, 9H DEGREES GRP09020  
 5 //15H TAN DELTA 3 = F8.2, 5X, 9H = F8.2, 5X, 30H FEET/SEC SQ. = F8.2, 5X, 30H GRP09030  
 208 FORMAT (1H0, 9X, 18H E/R DELTA DRAG = F10.4, //10X, 18H NO. BLADES (B) = F10.4, //10X, 18H GRP09040  
 1 I5, 38X, 15H MOM-INERTIA = F13.7, 15H SLUG FEET SQ.//10X, 18H S GRP09050  
 2 30.4, 33X, 15H = F10.4, 33X, 15H SUM(DX)+E/R = F10.4, //10X, 18H S GRP09060  
 4GMA = F13.7, 3X, 9H SLUG FEET = F9.0, 7X, 15H DELTA PSI = F9.0, 7X, 15H GRP09070  
 5 S//12X16HTRUST FACTOR = F9.0, 7X, 15H DELTA PSI = F9.0, 7X, 15H GRP09080  
 6 9X7HDEGREES//12X16HFLAP DAMPER = F9.0, 7X, 15H DELTA PSI = F9.0, 7X, 15H GRP09090  
 7 10X13HHINGE SPRING=F9.0, 6X14HFT. LB./RADIANS/12X16HIT. LB./RADIANS/SEC. GRP09100  
 8 9=F8.2, 37X13HPRE-CONING = F10.4, 5X7HDEGREES/12X16HTAN D3 BAR GRP09110  
 \* = F8.2, 37X13HSD3 BAR PHASE = F10.4, 5X7HDEGREES/12X16HTAN D3 BAR GRP09120  
 211 FORMAT (20H TOLERANCE ON BETA = F8.5, 5X, 20HTOLERANCE ON BETA\* = F8. GRP09130  
 15, 5X, 2HFLAPPING ITERATION LIMIT = I2) GRP09140  
 225 FORMAT (12X16HPS (CG) = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09150  
 113HV(Y)S = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09160  
 226 FORMAT (12X16HPS (MR) = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09170  
 113HPSI \* = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09180  
 227 FORMAT (12X16HHL (CG) = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09190  
 113HPI \* = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09200  
 228 FORMAT (12X16HHL (MR) = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09210  
 113HTHETA (F) \* = F9.3, 6X 14HKNOTS = F8.3, 8X19HINCHES GRP09220  
 500 FORMAT (I3) GRP09230  
 501 FORMAT (E15.6) GRP09240  
 GRP09250  
 GRP09260  
 GRP09270

```

502 FORMAT (5E14.6)
519 FORMAT (1H1,1X,27X22HHARMONICS OF AIR LOADS)
522 FORMAT (1H1,1X,8H0STATION13,5X5SHAO = F11.7//10X,1HA,14X,1HB,14X,1HC,13X
13HPHI,1X,5HSHRATIO/ (5F15.7))
585 FORMAT (1H1,1X,19X44HSUBROUTINE PTONE CALLED MORE THAN 15 TIMES)
808 FORMAT (1H1,1X,42X35HHARMONIC ANALYSIS OF DIMENSIONAL CZ//27X66HCZ = 10+A1GRP09330
901 *COS(PSI)+B1*SIN(PSI)+A2*COS(2*PSI)+B2*SIN(2*PSI)+MINIMUM//ACCEPTABLGRP09330
951 FORMAT (1H1,1X,19H0LIFT CURVE SLOPE (P6.2,38H) LESS THAN MINIMUM//ACCEPTABLGRP09330
1E VALUE (F4.2,1H1,1X,67HSTALL CRITERION HAS BEEN VIOLATED -- WILL GRP09330
20 TO NEXT CASE (IF ANY))
1010 FORMAT (1H1,1X,9HOCASE NO.13)
1604 FORMAT (1H1,1X,40H0TROUBLE WITH LAMBDA CONV. STATEMENT 225 2F10.6)
5001 FORMAT (1H1,1X,47H1END GENERALIZED ROTOR PERFORMANCE CALCULATIONS)
8821 FORMAT (1H1,1X,1X,1CL AND / OR CD LOOKUP PROBLEM WITH BLADE DATA')
8822 FORMAT (1H1,1X,1X,1CL AND / OR CD LOOKUP PROBLEM WITH SPAR DATA')
8823 FORMAT (1H1,1X,82X,17HNNATURE OF PROBLEM/8X,4HALFA,7Y,8HMACH NO. 8X,4HRC
1EV,1X,2F12.3,2I12,4I12,5X,17,5X,17,
2//,1X,2F12.3,2I12,4I12,5X,17,5X,17,
3//,1X,1=NO PROBLEM, 2=LO MACH, 3=HI MACH, 4=LO ALPHA, 5=HI ALPHA')
END
SUBROUTINE LOADED (UNPUT)
DIMENSION UNPUT(5),C(5)
WRITE(6,2)
FORMAT (1H1,18HINPUT CARD LISTING //)
6 READ(5,1) NNUM,NLOC,C(I),I=1,5)
1 FORMAT (12,14,5F12.0,16)
IF(NNUM.GT.5) NNUM=NNUM/10
J=1ABS(NNUM)
WRITE(6,3) NNUM,NLOC,C(I),I=1,J)
FORMAT (1X,12,14,5F20.10)
IF(NLOC.NE.0) LOC=NLOC
DO 4 I=1,J
UNPUT(LOC)=C(I)
4 LOC=LOC+1
IF(NNUM) 5,7,6
7 WRITE(6,8)
8 FORMAT (1H0, 52X,21HWORD COUNT IS MISSING)
5 RETURN
C *****
SUBROUTINE BLIN4 (T,NB,NBD,M,K,Y,X,Z,L)
DIMENSION T(NBD,M,K),
IF (Z-T(NB,1,2)) 10,5,5
5 DO 1 J=2,26
1 IF (T(NB,J,2)-Z) 1,2,2
GO TO 11
UZ=T(NB,J,2)
2

```

GRP C9770  
GRP 09780  
GRP 09790  
GRP 09800  
GRP 09810  
GRP 09820  
GRP 09830  
GRP 09840  
GRP 09850  
GRP 09860  
GRP 09870  
GRP 09880  
GRP 09890  
GRP 09900  
GRP 09910  
GRP 09920  
GRP 09930  
GRP 09940  
GRP 09950  
GRP 09960  
GRP 09970  
GRP 09980  
GRP 09990  
GRP 10000  
GRP 10010  
GRP 10020  
GRP 10030  
GRP 10040  
GRP 10050  
GRP 10060  
GRP 10070  
GRP 10080  
GRP 10090  
GRP 10100  
GRP 10110  
GRP 10120  
GRP 10130  
GRP 10140  
GRP 10150  
GRP 10160  
GRP 10170  
GRP 10180  
GRP 10190  
GRP 10200  
GRP 10210  
GRP 10220  
GRP 10230  
GRP 10240  
GRP 10250

```

EZ=T(NB,J-1,2)+1,12,7,7
N=T{X-f(NB,J,3)}+1,12,7,7
7 DO 3 I=5,N,2
3 IF (T(NB,J,I)-X) 3,4,4
GO TO 13
4 UZUX=T(NB,J,I)
UZUY=T(NB,J,I+1)
UZLX=T(NB,J,I-2)
UZLY=T(NB,J,I-1)
N=T(NB,J-1,I)*2+1,12,9,9
9 DO 6 I=5,N,2
6 IF (T(NB,J-1,I)-X) 6,8,8
GO TO 13
8 EZUX=T(NB,J-1,I)
EZUY=T(NB,J-1,I+1)
EZLX=T(NB,J-1,I-2)
EZLY=T(NB,J-1,I-1)
UY = {UZLY - EZUY} / {UZ - EZ} * (Z - EZ) + EY
EY = {UY - EY} / {UZ - EZ} * (Z - EZ) + EY
L=1
RETURN
10 L=2
RETURN
11 L=3
RETURN
12 L=4
RETURN
13 L=5
RETURN
END
C ***** HARM(K,NH,Y,ALPHA,AO,A,B,C,PHI,RATIO,LL)
SUBROUTINE DIMENSION A(1),B(1),C(1),PHI(1),RATIO(1),F(1)
PI=3.14159
NK=NH
IF (NH) 15,15,18
15 NH=K/2
18 IF (NH=K/2) 10,10,210
10 LK=K/2
LK=LK*2
IF (K-NH) 60,30,60
30 HAN=NH
CAP=K/2
IF (HAN-CAP) 40,35,40

```

GRP10260  
GRP10270  
GRP10280  
GRP10290  
GRP10300  
GRP10310  
GRP10320  
GRP10330  
GRP10340  
GRP10350  
GRP10360  
GRP10370  
GRP10380  
GRP10390  
GRP10400  
GRP10410  
GRP10420  
GRP10430  
GRP10440  
GRP10450  
GRP10460  
GRP10470  
GRP10480  
GRP10490  
GRP10500  
GRP10510  
GRP10520  
GRP10530  
GRP10540  
GRP10550  
GRP10560  
GRP10570  
GRP10580  
GRP10590  
GRP10600  
GRP10610  
GRP10620  
GRP10630  
GRP10640  
GRP10650  
GRP10660  
GRP10670  
GRP10680  
GRP10690  
GRP10700  
GRP10710  
GRP10720  
GRP10730  
GRP10740

```

35  NK = NH - 1
40  K1 = K / 2
    IF (NH.LT.K1) GO TO 60
    A(K1) = 0.0
    B(K1) = 0.0
    DO 50 I = 1, K
      A(K1) = A(K1) + (-1.0) ** (I - 1) * Y(I)
      B(K1) = B(K1) / FLOAT(K)
50  A(K1) = 0.0
60  A0 = 0.0
70  DO 70 N = 1, K
    A0 = A0 + Y(N)
    A0 = A0 / FLOAT(K)
    DO 90 J = 1, NK
      A(J) = 0.0
      B(J) = 0.0
      DO 90 I = 1, K
        PSI = 6.2831853 / FLOAT(K)
        T = FLOAT(J) * FLOAT(I - 1)
        A(J) = A(J) + Y(I) * COS(T) * PSI
        B(J) = B(J) + Y(I) * SIN(T) * PSI
90  DO 100 J = 1, NK
    A(J) = A(J) * 2.0 / FLOAT(K)
    B(J) = B(J) * 2.0 / FLOAT(K)
100 DO 195 J = 1, NH
    TT = FLOAT(J) * ALPHA / 57.295779
    BPR = A(J) * COS(TT) - B(J) * SIN(TT)
    A(J) = -BPR
    B(J) = BPR
195 DO 110 J = 1, NH
    C(J) = SQRT(A(J) ** 2 + B(J) ** 2)
    G = C(J)
    DO 140 J = 2, NH
      IF (G - C(J)) 130, 130, 140
      G = C(J)
130 CONTINUE
140 DO 150 J = 1, NH
    IF (G) 151, 151, 152
    RATIO(J) = 999999.9999999
    IF (C(J).EQ.0.) RATIO(J) = 1.0
151 GO TO 150
152 RATIO(J) = C(J) / G
150 CONTINUE
    DO 180 J = 1, NH
      IF (B(J).EQ.0.) GO TO 190
      PN = A(J) / B(J)
      PHI(J) = ATAN(PN)
      IF (B(J)) 170, 190, 180
170 PHI(J) = PHI(J) + 3.14159265

```



```

190 PHI(J) = SIGN(PI/2, A(J))
180 PHI(J) = PHI(J) * 57.295779
200 LL = 1
210 RETURN
    LL = 2
    RETURN
    END

```

```

GRP10750
GRP10760
GRP10770
GRP10780
GRP10790
GRP10800
GRP10810
GRP10820

```

## LIST OF REFERENCES

1. NACA Report 487, An Aerodynamic Analysis of the Autogyro with a Comparison Between Calculated and Experimental Results by John B. Wheatley, 1937.
2. NACA Report 716, A Simplified Method of Determining the Characteristics of a Lifting Rotor in Forward Flight by F. J. Bailey, 1941.
3. United Aircraft Research Laboratories Report R-0725-3, A Machine Method for Calculating Helicopter Rotor Performance Including Stall and Drag-Divergence Effects, by Nelson H. Kemp, 1956.
4. Gessow, A. and Myers, G. C., Aerodynamics of the Helicopter, Frederick Ungar Publishing Co., 1967.
5. Sikorsky Aircraft Report 50355, Generalized Rotor Performance Method, by W. H. Gerdee, September 1963.
6. Army Air Mobility Research and Development Laboratory Report TR-74-10A, Rotorcraft Flight Simulation with Aeroelastic Rotor and Improved Aerodynamic Representation, Volume I, Engineer's Manual, by John M. Davis, et al, Chapter 3, June 1974
7. Bramwell, A.R.S., Helicopter Dynamics, John Wiley and Sons, 1976.

# INITIAL DISTRIBUTION LIST

	No. copies
1. Defense Documentation Center Cameron Station Alexandria, Virginia 22314	2
2. Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
3. Department Chairman, Code 67 Department of Aeronautics Naval Postgraduate School Monterey, California 93940	1
4. Professor L.V. Schmidt, Code 67SX Department of Aeronautics Naval Postgraduate School Monterey, California 93940	1
5. Professor M.P. Platzner, Code 67PL Department of Aeronautics Naval Postgraduate School Monterey, California 93940	1
6. Commanding Officer Attn: Mr. George Unger, AIR-530132B Naval Air System Command Washington, D.C. 20361	2
7. Lt James W. Loiselle, USN 2512 Granada Circle Spring Valley, California 92077	1